# Electronics Letters

VOLUME 18, 1982

THE INSTITUTION OF ELECTRICAL ENGINEERS

# Electronics Letters

THE INSTITUTION OF ELECTRICAL ENGINEERS

**ELECTRONICS LETTERS is published fortnightly. * Price £10.00 ($23.50) per issue; annual subscription in UK £103.00, overseas £140.00 ($326.00). Second-class postage paid at New York, NY. All copies for North America are sent by air freight to New York. Airmail direct to subscriber at an additional charge of £30.00. Available also in a concurrent microfiche edition at the same subscription rate as for the printed edition. The subscription for combined paper and microfiche is £130.00 (UK), overseas £190.00 ($435.00)**

*Except in December when only one issue is published. There are 25 issues each year

All subscription inquiries and orders should be sent to the Publication Sales Department, **IEE, Station House, Nightingale Road, Hitchin, Herts. SG5 1SA, England. Telephone Hitchin 53331 (s.t.d. 0462 53331), Telex 825962**

Contributions should be addressed to the Executive Editor, *Electronics Letters,* Publishing Department, Institution of Electrical Engineers, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England

**There is no page charge**

All other correspondence, including advertisements, should be sent to: IEE Publishing Department, PO Box 8, Southgate House, Stevenage, Herts. SG1 1HQ, England. Telephone Stevenage 3311 (s.t.d. 0438 3311), Telex 261176, Telegrams Voltampere Stevenage, England. The telephone number of the IEE London office is 01–836 2441, Telex 261176

The advantages of rapid publication given by *Electronics Letters* are nullified if subscribers are subject to excessive delays in the receipt of the journal. The Executive Editor would be grateful to learn of any difficulties subscribers may experience

This publication is copyright under the Berne Convention and the International Copyright Convention. All rights reserved. Apart from any copying under the UK Copyright Act 1956, part 1, section 7, whereby a single copy of an article may be supplied, under certain conditions, for the purposes of research or private study, by a library of a class prescribed by the UK Board of Trade Regulations (Statutory Instruments, 1957, no 868), no part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means without the prior permission of the copyright owners. Permission is, however, not required to copy abstracts of papers or articles on condition that a full reference to the source is shown

The IEE appreciates that, on certain occasions, it could be very useful for organisations to be able to make copies of articles and papers. An IEE licensing arrangement exists whereby organisations entering into an agreement are legally entitled to make up to ten copies of an IEE paper or article. Full details may be obtained from the IEE Publishing Department at the above address

The appearance of the code at the bottom of an article in this journal indicates the copyright owner's consent that copies of the article may be made in the USA for personal or internal use, or for the personal or internal use of specific clients. This consent is given on the condition, however, that the copier pay the stated per-copy fee through the Copyright Clearance Center, Inc. for copying beyond that permitted by Sections 107 or 108 or the US Copyright Law. This consent does not extend to other kinds of copying, such as copying for general distribution, for advertising or promotional purposes for creating new collective works or for resale. Payment is also required for copying of articles published before 1978

The IEE is not as a body responsible for the opinions expressed by individual authors

The IEE is a member of the Association of Learned & Professional Society Publishers

*Publishing Department:*
IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

*Secretary of the IEE:*
H.H.W.Losty

*Managing Editor:*
Bernard Dunkley

*Executive Editor:*
Kathy Scales

*Assistant Editor:*
Nick Matthews

*Graphics Manager:*
Maurice Partridge

*Marketing Manager:*
Alan Baldwin

**EDITORS**
P.J.B.Clarricoats *(London)*
E.A.Ash *(London)*

*Advertisement Department:*
IEE
PO Box 8
Southgate House
Stevenage
Herts. SG1 1HQ
England

©1982: The Institution of Electrical Engineers

The Institution of Electrical Engineers, Savoy Place, London WC2R 0BL, England

*Typeset in England by:*

Santype International Ltd
Netherhampton Road
Salisbury
Wilts. SP2 8PS

*Printed in England by:*

Unwin Brothers Ltd.,
Old Woking, Surrey

# Electronics Letters

## INDEX VOLUME 18, 1982

### Author index


A

Abe, Y., Kishino, K., Tanbun-Ek, T., Arai, S., Koyama, F., Matsumoto, K., Watanabe, T., and Suematsu, Y. Room-temperature CW operation of 1.60 μm GaInAsP/InP buried-heterostructure integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide 410

Abels, L.L., Barnett, S.A., Ray, M.A., Lastras, A., Kramer, B., Greene, J.E., and Raccah, P.M. see Barnett, S.A.

Acar, C., and Karagöz, C. see Karagöz, C.

Adams, A.R., Patel, D., Greene, P.D., and Henshall, G.D. Influence of pressure on temperature sensitivity of $Ga_xIn_{1-x}As_yP_{1-y}$ lasers 919

Adams, A.R., Patel, D., Greene, P.D., and Henshall, G.D. see Patel, D.

Adatia, N., Ghosh, S., and Watson, B.K. see Ghosh, S.

Adès, C.,Haond, M., and Vu, D.-P. see Haond, M.

Agarwal, S.K., Jain, S.C., and Harsh, S. Variation of minority carrier lifetime with level of injection in p-n junction devices 298

Agusti-Comes, R., and Junyent-Giralt, G. Performance of FH-MFSK serial search synchroniser for mobile radio 393

Ahmed, H., Davis, J.R., and McMahon, R.A. see Davis, J.R.

Ainslie, B.J., Beales, K.J., Cooper, D.M., and Day, C.R. Fabrication and evaluation of MCVD single-mode fibres with and without central index depression 809

Ainslie, B.J., Beales, K.J., Cooper, D.M., Day, C.R., and Rush, J.D. Monomode fibre with ultra-low loss and minimum dispersion at 1.55 μm 842

Aitchison, C.S., and Nazoa-Ruiz, N. see Nazoa-Ruiz, N.

Aizawa, T., Ishihara, T., Enomoto, T., and Yasumoto, M. see Ishihara, T.

Akers, L.A., and Alvarez, A.R. see Alvarez, A.R.

Akiba, S., Utaka, K., Sakai, K., and Matsushima, Y. Low-threshold-current distributed-feedback InGaAsP/InP CW lasers 77

Akiba, S., Matshushima, Y., Sakai, K., Kushiro, Y., Noda, Y., and Utaka, K. see Matshushima, Y.

Akiba, S., Yamamoto, S., Utaka, K., Sakai, K., Matsushima, Y., Sakaguchi, S., and Seki, N. see Yamamoto, S.

Al-Assam, A., Cozens, J.R., Boucouvalas, A.C., Lee, M.J., and Morris, D.G. see Cozens, J.R.

Al-Attar, A., Scott, H.F., and Daniels, D.J. Wideband measurement of microwave characteristics of soils 194

Al-Jalili, Y.O., and Lockhart, G.B. see Lockhart, G.B.

Alard, F., Jeunhomme, L., Monerie, M., Sansonetti, P., and Vassallo, C. Fundamental mode spot-size measurements in single-mode optical fibres (Reply to) 693 e936

Alard, F., Sansonetti, P., Vassallo, C., Kammerer, P., Francois, P.L., Monerie, M., Gabriagues, J.M., and Dupont, P. see Sansonetti, P.

Albrecht, W., Elze, G., Enning, B., Walf, C., and Wenke, G. Experiences with an optical long-haul 2.24 Gbit/s transmission system at a wavelength of 1.3 μm 746

Alexander, S.E. Radio propagation within buildings at 900 MHz 913

Alferness, R.C., Buhl, L.L., and Divino, M.D. Low-loss fibre-coupled waveguide directional coupler modulator 490

Alferness, R.C., Ramaswamy, V., and Divino, M. see Ramaswamy, V.

Allamando, E., Salmer, G., Bouhess, M., and Constant, E. Influence of gate intervals on the behaviour of submicron dual-gate FETs 791

Allnutt, J.E., and Rogers, D.V. Novel method for predicting site diversity gain on satellite-to-ground radio paths 233

Allnutt, J.E., and Ogawa, A. see Ogawa, A.

Allsopp, D., Wu, R.H., and Peaker, A.R. see Wu, R.H.

Alping, A., Andersson, T., Tell, R., and Eng, S.T. 20 Gbit/s optical time multiplexing with TJS GaAlAs lasers 422

Alvarez, A.R., and Akers, L.A. Monte Carlo analysis of sensitivity of threshold voltage in small geometry MOSFETs 42

Amano, K., Niiro, Y., Furusawa, K., Nunokawa, M., and Wakabayashi, H. 50 km, two-repeaters sea trial of optical-fibre submarine cable system 952

Amano, M., Shirafuji, J., Inoue, M., and Inuishi, Y. see Shirafuji, J.

Ameri, S., Wickramasinghe, H.K., and See, C.W. see Wickramasinghe, H.K.

Analouei, A.R., Walton, A.J., and Burrow, N.G. Excess delay factor associated with dominant poles of trimmed distributed RC networks 681

Ananasso, F. Evaluation of outage probability of microwave radio relay systems carrying both analogue (FM) and digital (FSK) RF channels 175

Anand, K.V., Mossadeq, H., and Bennett, R.J. see Mossadeq, H.

Ananda Mohan, P.V., Ramachandran, V., and Swamy, M.N.S. General stray-insensitive first-order active SC network 1

Ananda Mohan, P.V., Ramachandran, V., and Swamy, M.N.S. Parasitic-compensated second-order switched-capacitor filters 531

Anderson, A.P., Melek, M., Brown, B.H., and Conway, J. see Melek, M.

Anderssen, R.S., Calligaro, R.B., Payne, D.N., and Ellem, B.A. see Calligaro, R.B.

Andersson, T., Alping, A., Tell, R., and Eng, S.T. see Alping, A.

Andle, J., Bailey, D.S., Josse, F., Lee, D.L., Soluch, W., Vetelino, J.F., and Chai, B.H.T. see Bailey, D.S.

Andonovic, I., Pun, E.Y.B., Wong, K.K., Laybourn, P.J.R., and De La Rue, R.M. see Pun, E.Y.B.

Ankri, D., and Eastman, L.F. GaAlAs-GaAs ballistic hetero-junction bipolar transistor 750

Aoki, T., Sakai, S., and Umeno, M. see Sakai, S.

Arai, S., Abe, Y., Kishino, K., Tanbun-Ek, T., Koyama, F., Matsumoto, K., Watanabe, T., and Suematsu, Y. see Abe, Y.

Arazi, B. Implementation of digital signatures 900

Archer, M.J. Periodic multielement strip gratings 958

Armand, C., Favennec, P.N., Deveaud, B., Salvi, M., and Martinez, A. see Favennec, P.N.

Arnaud, J., Barthelemy, A., Facq, P., and Froehly, C. see Barthelemy, A.

Arnaud, J., Liang, G.T., and Facq, F. see Liang, G.T.

Arnbak, J., and Kuperus, F. see Kuperus, F.

Asahi, H., Kawamura, Y., Nagai, H., and Ikegami, T. Optically pumped laser action at 77 K of InGaP/InGaAlP double heterostructures grown by MBE 62

Asahi, H., Kawamura, Y., Noguchi, Y., and Nagai, H. see Kawamura, Y.

Asai, K., Murakami, T., and Yamazaki, E. see Murakami, T.

Asai, K., Ohwada, K., Ino, M., and Mizutani, T. see Ohwada, K.

Asai, K., Yamasaki, K., Mizutani, T., and Kurumada, K. see Yamasaki, K.

Asawa, C.K., Yao, S.K., Stearns, R.C., Mota, N.L., and Downs, J.W. High-sensitivity fibre-optic strain sensors for measuring structural distortion 362

Asenov, A.M. Simple model for threshold voltage of a nonuniformly doped short-channel MOS transistor 481

Ash, E.A., Guangqi, Y., and Nikoonahad, M. see Guangqi, Y.

Ash, E.A., and Martin, Y. see Martin, Y.

Ash, E.A., Wickramasinghe, H.K., Martin, Y., and Ball, S. see Wickramasinghe, H.K.

Ashiya, F., Noguchi, K., Murakami, Y., and Yamashita, K. see Noguchi, K.

Ashoor, N., and Singh, V. Remarks on system simplification under consideration of time responses 496

Assenat, P., Hersee, S., Baldy, M., De Cremoux, B., and Duchemin, J.P. see Hersee, S.

Assenat, P., Hersee, S.D., Baldy, M., De Cremoux, B., and Duchemin, J.P. see Hersee, S.D.

Atherton, D.P. Limit cycles in relay systems 922

Auchterlonie, L.J., and Luen, C.H. see Luen, C.H.

Auchterlonie, L.J., and Mahmid, B. see Mahmid, B.

Auchterlonie, L.J., and Smith, D. see Smith, D.

Auld, B.A., Renard, A., and Henaff, J. STW resonances on corrugated plates of finite thickness 183

Awaka, J., Shimada, M., Isobe, T., and Ouchi, E. Effect of antenna polarisation on rain scattering 205

Awano, Y., Tomizawa, K., Hashizume, N., and Kawashima, M. Monte Carlo particle simulation of GaAs submicron $n^+$-i-$n^+$ diode 133

Awano, Y., Tomizawa, K., Hashizume, N., and Suzuki, F. see Tomizawa, K.

Ayasli, Y., Reynolds, L.D., Vorhaus, J.L., and Hanes, L. Monolithic 2-20 GHz GaAs travelling-wave amplifier 596

B

Baert, D., Bonte, L., Vandamme, J., De Bilde, J., and Dhooghe, W. see Bonte, L.

Baghdady, E.J., Gupta, A.K., and Garner, W.B. see Gupta, A.K.

Baher, H. Cascade synthesis of a class of mixed lumped-distributed networks 105

Baher, H. FIR digital filters with simultaneous conditions on amplitude and delay 296

Bailey, D.S., Josse, F., Lee, D.L., Andle, J., Soluch, W., Vetelino, J.F., and Chai, B.H.T. Study of SAW properties of temperature-compensated orientations in berlinite 168

Bailey, M.D., and Rawson, E.G. see Rawson, E.G.

Bailey, M.D., Scifres, D.R., Norton, R.E., Burnham, R.D., and Rawson, E.G. see Scifres, D.R.

Baker, I.M., Ballingall, R.A., Blenkinsop, I.D., Elliott, C.T., and Jenner, D. see Ballingall, R.A.

Balabaud, J.P., Obregon, J., Guillon, P., and Garault, Y. see Obregon, J.

Baldy, M., Hersee, S., Assenat, P., De Cremoux, B., and Duchemin, J.P. see Hersee, S.

Baldy, M., Hersee, S.D., Assenat, P., De Cremoux, B., and Duchemin, J.P. see Hersee, S.D.

Baldy, M., Hersee, S.D., Hirtz, J.P., and Duchemin, J.P. see Hersee, S.D.

Ball, S., Wickramasinghe, H.K., Martin, Y., and Ash, E.A. see Wickramasinghe, H.K.

Ballingall, R.A., Blenkinsop, I.D., Elliott, C.T., Baker, I.M., and Jenner, D. Electronically scanned CMT detector array for the 8-14 μm band 285

Band, K.S., Hobdell, J.L., and Biggin, J.W. see Hobdell, J.L.

Bandurek, G.R., Kashyap, R., Reeve, M.H., Hornung, S., and Nevett, J.E. see Kashyap, R.

Banu, M., and Tsividis, Y. Floating voltage-controlled resistors in CMOS technology 678 e936

Barbaliscia, F., and Paraboni, A. Joint statistics of rain intensity in eight Italian locations for satellite communication networks 118

Barker, R.W.J., and Hart, B.L. see Hart, B.L.

Barlow, A.J., Ramskov-Hansen, J.J., and Payne, D.N. Anisotropy in spun single-mode fibres 200

Barnett, S.A., Ray, M.A., Lastras, A., Kramer, B., Greene, J.E., Raccah, P.M., and Abels, L.L. Growth and optical properties of single-crystal metastable $(GaAs)_{1-x}Ge_x$ alloys 891

Barthelemy, A., Facq, P., Froehly, C., and Arnaud, J. New method for precise characterisation of multimode optical fibres 247

Bartley, N.R., and Bruton, L.T. see Bruton, L.T.

Bates, R.N. Determination of resonant frequency for 2nd-harmonic-mode millimetre-wave transferred-electron oscillators 198

Baudelot, E., Chante, J.P., and Urgell, J.J. Improvement of on-resistance of MOS-gated devices 546

Bava, G.P., Pisani, U., and Pozzolo, V. Active load technique for load-pull characterisation at microwave frequencies 178

Beales, K.J., Ainslie, B.J., Cooper, D.M., and Day, C.R. see Ainslie, B.J.

Beck, C.M., Henry, R.M., Lowe, B.T., and Plaskowski, A. Autocorrelation function parameters used to indicate incipient blockage in a pneumatic transport system 705

Bedair, S.S. Closed-form expressions for the even-mode capacitance of thick coupled microstriplines 561

Bedrosian, S.D., and Xie, W. Fuzzy-measure justification of some grey-tone image experimental data 615

Belfort, A.J., and Cullen, A.L. First-order theory of the five-port symmetrical star junction 841

Belov, A.V., Dianov, E.M., Lebedev, P.N., Guryanov, A.N., and Hopin, V.F. OH absorption in $GeO_2$-doped fused silica fibres 836

Bendali, A., Clair, D., and Tourneur, J. Finite-element approximation of electromagnetic diffraction by arbitrarily shaped surfaces 641

Beneking, H., and Su, L.M. Double heterojunction NpN GaAlAs/GaAs bipolar transistor 25
Beneking, H., Escobosa, A., and Kräutle, H. see Escobosa, A.
Beneking, H., Kräutle, H., and Narozny, P. see Kräutle, H.
Beneking, H., Vescan, L., Selders, J., Kräutle, H., and Kütt, W. see Vescan, L.
Beneking, H., Zhao, Y.Y., and Wei, C.J. see Zhao, Y.Y.
Benelli, G. VHF radio link for ground-air-ground communications using an integrated voice-data modulation 555
Bennett, R.H., Oxley, C.H., and Peake, A.H. see Oxley, C.H.
Bennett, R.J., Mossadeq, H., and Anand, K.V. see Mossadeq, H.
Benson, T.M., Syrbu, A.V., Chand, N., and Houston, P.A. Single-mode InGaAsP/InP buried waveguide structures grown on channelled {111} B InP substrates 812
Bentland, B., Bergman, L.A., Tell, R., and Eng, S.T. Clock recovery for a 5 Gbit/s fibre-optic system 547
Berenz, J.J., and Yen, K.H. see Yen, K.H.
Bergman, L.A., Bentland, B., Tell, R., and Eng, S.T. see Bentland, B.
Bermudez, J.C.M., and Bhattacharyya, B.B. Parasitic insensitive toggle-switched capacitor and its applications to switched-capacitor networks 734 e936
Bernardson, P. Simple and accurate size calculation of MOS transistor 632
Bethea, C.G., Chen, C.Y., Cho, A.Y., and Garbinski, P.A. see Chen, C.Y.
Bethea, C.G., Levine, B.F., Van der Ziel, J.P., and Logan, R.A. see Levine, B.F.
Bhagavatula, V.A. Estimation of single-mode waveguide dispersion using an equivalent-step-index approach 319
Bhattacharyya, A.B., Singh, S.P., and Prabhakar, A. see Singh, S.P.
Bhattacharyya, B.B., and Bermudez, J.C.M. see Bermudez, J.C.M.
Bickers, L., Faulkner, D.W., and Cochrane, P. 140 Mbit/s thick-film hybrid regenerator 553
Bicknell, J. Intermittent fault coverage during test of electronic components and systems 522
Biefeld, R.M., Myers, D.R., Zipperian, T.E., and Dawson, L.R. see Myers, D.R.
Biesterbos, J.W.M., and Salemink, H.W.M. High-frequency intensity noise behaviour during accelerated life tests of narrow-stripe proton-isolated DH AlGaAs lasers for optical communications 300 e584
Biggin, J.W., Hobdell, J.L., and Band, K.S. see Hobdell, J.L.
Binari, S.C., Neidert, R.E., and Weng, T. see Neidert, R.E.
Binet, M. Capacitors made by anodisation of aluminium for wideband GaAs ICs 197
Birch, R.D., Payne, D.N., and Varnham, M.P. Fabrication of polarisation-maintaining fibres using gas-phase etching 1036
Birkedahl, F., Jacobsen, G., Olesen, H., and Tromborg, B. see Jacobsen, G.
Biswas, A., and Das, B.N. see Das, B.N.
Blachman, N.M. Output correlation functions of power-law nonlinearities fed by Gaussian noise 347
Blackborow, P., Smith, G.J., and Milne, W.I. see Smith, G.J.
Blakers, A.W., Green, M.A., and Emery, K. see Green, M.A.
Blauvelt, H., Margalit, S., and Yariv, A. Single-carrier-type dominated impact ionisation in multilayer structures 375
Blenkinsop, I.D., Ballingall, R.A., Elliott, C.T., Baker, I.M., and Jenner, D. see Ballingall, R.A.
Blondeau, R., Razeghi, M., Hirtz, P., Larivain, J.P., Noel, L., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Blow, K.J., Doran, N.J., and Hornung, S. Power spectrum of microbends in monomode optical fibres 448
Board, K., Wood C.E.C., Eastman, L.F., Singer, K., and Malik, R. see Wood C.E.C.
Böck, G. Dispersion characteristics of slot lines on a ferrite substrate by a mode-matching technique 536
Boenke, M.M., Wagner, R.E., and Will, D.J. Transmission experiments through 101 km and 84 km single-mode fibre at 274 Mbit/s and 420 Mbit/s 897
Bois, D., and Rosencher, E. see Rosencher, E.
Boisrobert, C., and Joindot, I. see Joindot, I.
Bonte, L., Baert, D., Vandamme, J., De Bilde, J., and Dhooghe, W. Solution to instability problems of grid-connected PWM DC-AC inverters 600
Boothroyd, A.R., and Naem, A.A. see Naem, A.A.
Borel, J., Tawfik, M.S., Terrier, C., and Caillon, C. see Tawfik, M.S.
Bosch, R., Haydl, W.H., and Rüdiger, J. see Haydl, W.H.
Bosisio, R.G., and Li, S. see Li, S.
Botez, D., and Ettenberg, M. see Ettenberg, M.
Bouadma, N., Bouley, J.C., and Riou, J. Dual-wavelength (GaAl)As laser 871
Bouadma, N., Riou, J., and Bouley, J.C. Short-cavity GaAlAs laser by wet chemical etching 879
Boucouvalas, A.C., and Cozens, J.R. see Cozens, J.R.
Boucouvalas, A.C., Cozens, J.R., Lee, M.J., Morris, D.G., and Al-Assam, A. see Cozens, J.R.
Boucouvalas, A.C., and Papageorgiou, C.D. see Papageorgiou, C.D.
Bouhess, M., Allamando, E., Salmer, G., and Constant, E. see Allamando, E.
Bouley, J.C., Bouadma, N., and Riou, J. see Bouadma, N.
Boutin, N. Synthesis of dual-feedback ideal op-amp oscillator circuits 579
Boutin, N., Dussault, L., and Morissette, S. Results of a new optimisation technique leading to optimum pulses for MSK-type signals 975
Bowers, J.E., Newton, S.A., and Shaw, H.J. Fibre-optic variable delay lines 999
Bowers, J.E., Newton, S.A., Sorin, W.V., and Shaw, H.J. Filter response of single-mode fibre recirculating delay lines 110
Bradsell, P., Shepherd, P.R., Faulkner, N., and Vilar, E. see Shepherd, P.R.
Bradshaw, M.J., Hilsum, C., and Raynes, E.P. New form of liquid crystal touch switch 1106
Brady, M.J., and Comerford, L.D. see Comerford, L.D.
Brain, M.C. Noise, responsivity and prospects for long-term stability of silicon reach-through avalanche photodiodes 65
Brain, M.C., and Smith, D.R. Phototransistors in digital optical communications systems for 1-1.6 μm wavelength 772 e936
Brickell, F., and Westcott, B.S. see Westcott, B.S.
Brodarac, D., Herbst, D., Hosticka, B.J., and Hoefflinger, B. Novel sampled-data MOS multiplier 229
Bromba, M.U.A., and Ziegler, H. Further results on maximally flat nonrecursive digital filters 1014
Brosson, P., Manganote, E.J.T., and Prince, F.C. Dielectric guiding due to an inverted gain profile in GaAs/GaAlAs lasers 932
Brotherton, A.D., Gill, A., Shannon, J.M., and Parker, G.J. Punch-through technique for charge collection in an extrinsic Si IRCCD 167
Brown, B.H., Melek, M., Anderson, A.P., and Conway, J. see Melek, M.
Brown, G.T., Woodward, J., Cockayne, B., and Cameron, D.C. see Woodward, J.
Browne, M.A., Deloughry, R.J., Green, R.G., and Thorn, R. State-sequenced polarity crosscorrelator 528
Browning, M., Hartman, N., Vahey, D., and Kidd, R. see Hartman, N.
Brückner, V., and Kerstan, F. Ultrafast optoelectronic switching in CdS 885
Brugger, U.W., Hökenek, E., and Moschytz, G.S. see Hökenek, E.
Bruton, L.T., and Bartley, N.R. Stable fan filter design using two-variable reactance functions 217
Buchmann, P., and Houghton, A.J.N. Optical Y-junctions and S-bends formed by preferentially etched single-mode rib waveguides in InP 850
Buhl, L.L., Alferness, R.C., and Divino, M.D. see Alferness, R.C.
Burnham, R.D., Scifres, D.R., and Streifer, W. CW room-temperature visible single quantum well $Ga_{0.73}Al_{0.27}As$ diode lasers grown by metal-organic chemical vapour deposition 507
Burnham, R.D., Streifer, W., Scifres, D.R., Lindström, C., Paoli, T.L., and Holonyak, N. Low-threshold single quantum well (60 Å) GaAlAs lasers grown by MO-CVD with Mg AS *p*-type dopant 1095
Burnham, R.D., Lindström, C., Halido, D., and Scifres, D.R. see Lindström, C.
Burnham, R.D., Scifres, D.R., Bailey, M.D., Norton, R.E., and Rawson, E.G. see Scifres, D.R.
Burnham, R.D., Scifres, D.R., and Streifer, W. see Scifres, D.R.
Burns, W.K., Moeller, R.P., and Villarruel, C.A. Observation of low noise in a passive fibre gyroscope 648
Burrow, N.G., Analouei, A.R., and Walton, A.J. see Analouei, A.R.
Burrus, C.A., Lee, T.P., Liu, P.L., and Dentai, A.G. see Lee, T.P.
Burrus, C.A., Lee, T.P., Marcuse, D., Nelson, R.J., and Dentai, A.G. see Lee, T.P.
Burrus, C.A., Liu, P-L., Lee, T.P., Kaminow, I.P., and Ko, J.-S. see Liu, P-L.
Burt, M.G. Auger recombination rate in InGaAsP lasers 806
Buus, J. Theory for self-sustained pulsations in semiconductor lasers 718
Byron, K.C. Influence of waveguide dispersion in fluoride glass fibres 673


## C


Cahill, R., and Parker, E.A. Concentric ring and Jerusalem cross arrays as frequency selective surfaces for a 45D incidence diplexer 313
Cahill, R., and Parker, E.A. Crosspolar levels of ring arrays in reflection of 45° incidence: influence of lattice spacing 1060
Caillon, C., Tawfik, M.S., Terrier, C., and Borel, J. see Tawfik, M.S.
Calligaro, R.B., Payne, D.N., Anderssen, R.S., and Ellem, B.A. Determination of stress profiles in optical-fibre preforms 474
Callsen, H., and Schmidt, L.-P. Quasiplanar 3 dB hybrid for millimetre-wave integrated circuits 161
Callsen, H., and Meinel, H. see Meinel, H.
Callsen, H., and Menzel, W. see Menzel, W.
Cameron, D.C., Irving, L.D., Whitehouse, C.R., and Woodward, J. Planar self-aligned ion-implanted InP MOSFET 534
Cameron, D.C., Woodward, J., Brown, G.T., and Cockayne, B. see Woodward, J.
Cameron, K.H., Chidgey, P.J., and Preston K.R. 102 km optical fibre transmission experiments at 1.52 μ using an external cavity controlled laser transmitter module 650 e802
Cameron, K.H., Wyatt, R., and Smith, D.W. see Wyatt, R.
Campbell, J.C., and Coutts, R.P. Outage prediction of digital radio systems 1071
Cancellieri, G. Attenuation measurements on single pieces of fibre and extrapolation over longer distances 1062
Cannell, G.J., Leach, J.S., Robertson, A.J., and Gurton, P. see Leach, J.S.
Cao, W.L., Li, M.G., Mathur, V.K., and Lee, C.H. see Li, M.G.
Capasso, F. New ultra-low-noise avalanche photodiode with separated electron and hole avalanche regions 12
Capasso, F., Logan, R.A., and Tsang, W.T. Interdigitated pn junction device with novel capacitance-voltage characteristic, ultralow capacitance and low punch-through voltage 760
Capsoni, C., and Matricciani, E. Theoretical random process for prediction of rain attenuation statistics in site diversity satellite links above 10 GHz 917
Carayannis, G., Manolakis, D., and Kalouptsidis, N. see Manolakis, D.
Carey, J.R. Low-noise state-space realisation of bandpass active filter (Comment & Reply) 685
Carlsen, W.J., and Melman, P. see Melman, P.
Carter, A.C., Forbes, N., and Goodfellow, R.C. Monolithic integration of optoelectronic, electronic and passive components in GaAlAs/GaAs multilayers 72
Carter, A.C., Plastow, R., Harding, M., Griffith, I., and Goodfellow, R.C. see Plastow, R.
Cartinhour, J., and Patangia, H.C. see Patangia, H.C.
Castañer, L., and Prat, L. see Prat, L.
Cattermole, K.W., and Sundara Murthy, K.M. see Sundara Murthy, K.M.
Cebulski, R., and King, G.D.H. see King, G.D.H.
Chai, B.H.T., Bailey, D.S., Josse, F., Lee, D.L., Andle, J., Soluch, W., and Vetelino, J.F. see Bailey, D.S.
Chai, Y.G., Maloney, T.J., and Saxena, R.R. see Maloney, T.J.
Chand, N., Syrbu, A.V., and Houston, P.A. Growth effects of $In_{0.53}Ga_{0.47}As$ on InP structured substrates 613
Chand, N., Benson, T.M., Syrbu, A.V., and Houston, P.A. see Benson, T.M.
Chane, J.P., and Gourrier, S. see Gourrier, S.
Chang, F.Y., and Wagner, L.F. Generalised ICCG method for solution of asymmetric, sparse, linear systems of discretised semiconductor device equations 658
Chang, K., Tahim, R.S., and Hayashibara, G.M. see Tahim, R.S.
Chante, J.P., Baudelot, E., and Urgell, J.J. see Baudelot, E.
Chaplart, J., Delagebeaudeuf, D., Delescluse, P., Etienne, P., Massies, J., Laviron, M., and Linh, T. see Delagebeaudeuf, D.
Chaplart, J., Delagebeaudeuf, D., Laviron, M., Delescluse, P., Tung, Pham.N., and Linh, N.T. see Delagebeaudeuf, D.
Chaplart, J., Tung, P.N., Delagebeaudeuf, D., Laviron, M., Delescluse, P., and Linh, N.T. see Tung, P.N.
Chaplart, J., Tung, P.N., Delescluse, P., Delagebeaudeuf, D., Laviron, M., and Linh, N.T. see Tung, P.N.
Chapman, J.A., Stroomer, M.V.C., Powell, M.J., and Easton, B.C. see Stroomer, M.V.C.
Chassay, G. Ray analysis of mutual coupling between point scatterers in RCS diagram 574
Chassay, G. Use of point contributors model for a radar target taking into account mutual coupling by double reflection 893
Chayanov, B.A., Morozov, A.I., Kulakov, M.A., Dorozhkin, L.M., and Pleshkov, G.M. see Morozov, A.I.
Cheah, Y.C., and Paoloni, F.J. Resolution of monochromatic signal sources using a simple receiving antenna array 923
Chen, C.Y., Bethea, C.G., Cho, A.Y., and Garbinski, P.A. Temporal resolution of an $Al_xGa_{1-x}As/GaAs$ bias-free photodetector 890

Chen, J., Sibbett, W., and Vukusic, J.I. Mode locking of Brewster-angled semiconductor lasers 426
Chen, P.Y.P. Fast method for calculating cutoff frequencies in single-mode fibres with arbitrary index profiles 1048
Chen, P.Y.P. Wave propagation in transversely inhomogeneous dielectric waveguide 736
Chen, P.Y.P., Chu, P.L., and Sammut, R.A. see Chu, P.L.
Cheng, C.L., Coldren, L.A., Miller, B.I., Rentschler, J.A., and Shen, C.C. Low-resistance ohmic contacts to p-InP 755
Cheng, D.K., and Liang, C.H. Shaped wire antennas with maximum directivity 816
Chevrier, J., Massies, J., Rochette, J., Delescluse, P., Etienne, P., and Linh, N.T. see Massies, J.
Chida, K., Okazaki, H., and Nakahara, M. Large graded-index preforms fabricated by high-rate VAD 330
Chida, K., Sakaguchi, S, Wagatsuma, M., and Kimura, T. High-speed coating of optical fibres with thermally curable silicone resin using a pressurised die 713
Chidgey, P.J., Cameron, K.H., and Preston K.R. see Cameron, K.H.
Chin, A.K., Temkin, H., and Dutt, B.V. see Temkin, H.
Cho, A.Y., Kollberg, E., Zirath, H., Snell, W.W., and Schneider, M.V. Single-crystal metal-semiconductor microjunctions prepared by molecular beam epitaxy 424
Cho, A.Y., Chen, C.Y., Bethea, C.G., and Garbinski, P.A. see Chen, C.Y.
Christou, A., Davey, J.E., and Covington, D. Thin MBE GaAs millimetre-wave diode using Ge substrate 367
Chu, P.L. Measurement of stresses in elliptical optical fibre or preform 707
Chu, P.L. Relations between moments of index profile and moments of deflection function and phase function of optical fibre or preform 832
Chu, P.L. Single-mode optical-fibre index profiling with improved resolution 911
Chu, P.L. Thermal-stress-induced birefringence in single-mode elliptical optical fibre 45
Chu, P.L., Chen, P.Y.P., and Sammut, R.A. Finite-element analysis of birefringence in azimuthally inhomogeneous optical fibre 441
Chu, P.L., and Whitbread, T. Measurement of stresses in optical fibre or preform 28
Chubachi, N., Kushibiki, J., and Horii, K. see Kushibiki, J.
Chubachi, N., Kushibiki, J., and Ohkubo, A. see Kushibiki, J.
Claassen, M., and Harth, W. Large-signal operation of PIN impatt diodes for pulsed oscillators at millimetre-wave frequencies 737
Clair, D., Bendali, A., and Tourneur, J. see Bendali, A.
Clarke, R., Midgley, D., and Weston, C.R. Frequency control of ultrasonic transducers 684
Clarke, R.N., and Granville-George, D.A. Effects of broadband noise in radio-frequency six-port scattering-parameter measurements 1110
Claxton, P.A., Shirafuji, J., Houston, P.A., and Robson, P.N. Electron mobility in degenerate tellurium doped $In_{0.53}Ga_{0.47}As$ LPE layers 213
Clements, R.M., Santiago, J., and Smy, P.R. see Santiago, J.
Cobb, K.W., and Culshaw, B. Reduction of optical phase noise in semiconductor lasers 336
Cochrane, P., and Powell, E. Simple received signal/eye amplitude monitor for digital repeaters 388
Cochrane, P., Bickers, L., and Faulkner, D.W. see Bickers, L.
Cockayne, B., Wight, D.R., and Wright, P.J. see Wight, D.R.
Cockayne, B., Woodward, J., Brown, G.T., and Cameron, D.C. see Woodward, J.
Cohen, L.G., Mammel, W.L., and Jang, S.J. Low-loss quadruple-clad single-mode lightguides with dispersion below 2 ps/km nm over the 1.28 μm-1.65 μm wavelength range 1023
Cohen, L.G., Mammel, W.L., and Lumish, S. Numerical parametric studies for controlling the wavelength of minimum dispersion in germania fluoro-phosphosilicate single-mode fibres 38
Cohen, L.G., and Stone, J. Interferometric measurements of minimum dispersion spectra in short lengths of single-mode fibre 564
Cohen, L.G., and Stone, J. see Stone, J.
Coldren, L.A., Furuya, K., Miller, B.I., and Rentschler, J.A. Combined dry and wet etching techniques to form planar (011) facets in GaInAsP/InP double heterostructures 235
Coldren, L.A., Cheng, C.L., Miller, B.I., Rentschler, J.A., and Shen, C.C. see Cheng, C.L.
Coldren, L.A., Ebeling, K.J., Miller, B.I., and Rentschler, J.A. see Ebeling, K.J.
Coldren, L.A., Furuya, K., Miller, B.I., and Howard, R.E. see Furuya, K.
Comerford, L.D., and Brady, M.J. Capillary bonded components for injection laser transmitter modules 629
Constant, E., Allamando, E., Salmer, G., and Bouhess, M. see Allamando, E.
Constant, E., Fauquembergue, R., and Pernisek, M. see Fauquembergue, R.
Conway, J., Melek, M., Anderson, A.P., and Brown, B.H. see Melek, M.
Cooper, D.M., Ainslie, B.J., Beales, K.J., and Day, C.R. see Ainslie, B.J.
Coppa, G., and Di Vita, P. Length dependence of joint losses in multimode optical fibres 84
Corke, M., Jackson, D.A., and Kersey, A.D. see Jackson, D.A.
Corke, M., Jackson, D.A., Kersey, A.D., and Jones, J.D.C. see Jackson, D.A.
Corke, M., Jones, J.D.C., Kersey, A.D., and Jackson, D.A. see Jones, J.D.C.
Corke, M., Kersey, A.D., and Jackson, D.A. see Kersey, A.D.
Corsini, P., and Loprione, L. Z8001-based central processing unit with capability addressing 780
Corzani, T., Manià, L., and Falciasecca, G. Radiation loss in open-waveguide directional couplers 847
Cotter, D. Observation of stimulated Brillouin scattering in low-loss silica fibre at 1.3 μm 495
Cotter, D. Suppression of stimulated Brillouin scattering during transmission of high-power narrowband laser light in monomode fibre 638
Cotter, D. Transient stimulated Brillouin scattering in long single-mode fibres 504
Coutts, R.P., and Campbell, J.C. see Campbell, J.C.
Couvreur, C., and Quisquater, J.-J. see Quisquater, J.-J.
Covington, D., Christou, A., and Davey, J.E. see Christou, A.
Cozens, J.R., and Boucouvalas, A.C. Coaxial optical coupler 138
Cozens, J.R., Boucouvalas, A.C., Lee, M.J., Morris, D.G., and Al-Assam, A. Optical coupling in coaxial fibres 679
Craig, A.D., and Simms, P.D. Fast integration techniques for reflector antenna pattern analysis 60
Crecraft, D.I., Davies, C.J.S., and Hall, K.G. Visualisation of ultrasonic waves launched by $PVF_2$ piezofilm transducers 16
Crosignani, B., and Di Porto, P. Degree of polarisation in a birefringent single-mode optical fibre 15
Cullen, A.L. New technique for 2-port measurement using an 8-port directional coupler 343
Cullen, A.L., and Belfort, A.J. see Belfort, A.J.
Culshaw, B., and Cobb, K.W. see Cobb, K.W.


## D


Da Rocha, J.R.F., and O'Reilly, J.J. Modified Chernoff bound for binary optical communication 708
Dahele, J.S., and Lee, K.F. Characteristics of annular-ring microstrip antenna 1051
Daly, P., and Tits, D. Novel technique for antenna gain measurement in satellite earth stations 1089
Dandridge, A., and Goldberg, L. Current-induced frequency modulation in diode lasers 302
Dang, R.L.M., Shigyo, N., and Konaka, M. see Shigyo, N.
Dang, R.L.M., and Wada, T. see Wada, T.
Daniel, J.-P., and Penard, E. see Penard, E.
Daniel, R.W. Sensitivity of principal phases 754
Daniels, D.J., Al-Attar, A., and Scott, H.F. see Al-Attar, A.
Dapkus, P.D., Hong, C.S., Kasemset, D., Patel, N.B., and Kim, M.E. see Hong, C.S.
Das, B., and Kim, B. see Kim, B.
Das, B.N., and Biswas, A. Excitation of multimode guide by stripline-fed slots 801
Das, M.B., and Ghosh, P.K. Low-frequency emissions from deep levels in GaAs MESFETs 207
Das, P., Rademeyer, R., and Davari, B. see Rademeyer, R.
Davari, B., Rademeyer, R., and Das, P. see Rademeyer, R.
Davey, J.E., Christou, A., and Covington, D. see Christou, A.
Davies, C.J.S., Crecraft, D.I., and Hall, K.G. see Crecraft, D.I.
Davis, J.R., McMahon, R.A., and Ahmed, H. Recrystallisation of CVD poly-Si on insulator by dual electron-beam processing 163
Davis, Q.V., Pitcher, P.G., and Hemment, P.L.F. see Pitcher, P.G.
Dawson, L.R., Myers, D.R., Biefeld, R.M., and Zipperian, T.E. see Myers, D.R.
Day, C.R., Ainslie, B.J., Beales, K.J., and Cooper, D.M. see Ainslie, B.J.
De Bilde, J., Bonte, L., Baert, D., Vandamme, J., and Dhooghe, W. see Bonte, L.
De Carvalho, J.M., and Hanson, J.V. Optimal real-time interpolation for D/A conversion of sparsely sampled signals 961
De Cremoux, B., Hersee, S., Baldy, M., Assenat, P., and Duchemin, J.P. see Hersee, S.
De Cremoux, B., Hersee, S.D., Baldy, M., Assenat, P., and Duchemin, J.P. see Hersee, S.D.
de Cremoux, B., Razeghi, M., Hirtz, P., Blondeau, R., Larivain, J.P., Noel, L., and Duchemin, J.P. see Razeghi, M.
de Cremoux, B., Razeghi, M., Poisson, M.A., Larivain, J.P., Duchemin, J.P., and Voos, M. see Razeghi, M.
De La Rue, R.M., Pun, E.Y.B., Wong, K.K., Andonovic, I., and Laybourn, P.J.R. see Pun, E.Y.B.
de la Sen, M. Nonperiodic sampling and identifiability e350
de la Sen, M. Nonperiodic sampling and model matching 311
De La Sen, M., Paz, M.B., Dormido, S., and Mellado, M. see Paz, M.B.
De Mey, G. Parametric photovoltaic cell 334
de Prince, F.C., and Ribeiro, C.A. see Ribeiro, C.A.
Debney, B.T., and Holden, A.J. see Holden, A.J.
Delagebeaudeuf, D., Delescluse, P., Etienne, P., Massies, J., Laviron, M., Chaplart, J., and Linh, T. Tunnelling through GaAs-$Al_xGa_{1-x}$As-GaAs double heterojunctions 85
Delagebeaudeuf, D., Laviron, M., Delescluse, P., Tung, Pham.N., Chaplart, J., and Linh, N.T. Planar enhancement mode two-dimensional electron GaAs FET associated with a low AlGaAs surface potential 103
Delagebeaudeuf, D., and Linh, N.T. Speed power in planar two-dimensional electron GAS FET DCFL circuit: a theoretical approach 510
Delagebeaudeuf, D., Tung, P.N., Delescluse, P., Laviron, M., Chaplart, J., and Linh, N.T. see Tung, P.N.
Delagebeaudeuf, D., Tung, P.N., Laviron, M., Delescluse, P., Chaplart, J., and Linh, N.T. see Tung, P.N.
Delescluse, P., Delagebeaudeuf, D., Etienne, P., Massies, J., Laviron, M., Chaplart, J., and Linh, T. see Delagebeaudeuf, D.
Delescluse, P., Delagebeaudeuf, D., Laviron, M., Tung, Pham.N., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Delescluse, P., Massies, J., Rochette, J., Etienne, P., Chevrier, J., and Linh, N.T. see Massies, J.
Delescluse, P., Tung, P.N., Delagebeaudeuf, D., Laviron, M., Chaplart, J., and Linh, N.T. see Tung, P.N.
Deloughry, R.J., Browne, M.A., Green, R.G., and Thorn, R. see Browne, M.A.
Delsarte, P., and Piret, P. Extension of RSA crypto-structure: a Galois approach (Comment & Reply) 582
Demoment, G., and Segalen, A. see Segalen, A.
Den Dulk, R.C., Niekolaas, G., and Regenbogen, L.K. see Niekolaas, G.
Dentai, A.G., Lee, T.P., Burrus, C.A., and Liu, P.L. see Lee, T.P.
Dentai, A.G., Lee, T.P., Burrus, C.A., Marcuse, D., and Nelson, R.J. see Lee, T.P.
Dereffye, J., and Moupfouma, F. see Moupfouma, F.
DeSimone, D., Xin, S.H., Wood, C.E.C., Palmateer, S., and Eastman, L.F. see Xin, S.H.
Desmedt, Y., Vandewalle, J., and Govaerts, R. How iterative transformations can help to crack the Merkle-Hellman cryptographic scheme 910
Deveaud, B., Favennec, P.N., Salvi, M., Martinez, A., and Armand, C. see Favennec, P.N.
Dhooghe, W., Bonte, L., Baert, D., Vandamme, J., and De Bilde, J. see Bonte, L.
Di Porto, P., and Crosignani, B. see Crosignani, B.
Di Vita, P. Effects of mode conversion on backscattering measurements of multimode optical fibres 637
Di Vita, P., and Coppa, G. see Coppa, G.
Diamessis, J.E., and Therapos, C.P. see Therapos, C.P.
Dianov, E.M., Belov, A.V., Lebedev, P.N., Guryanov, A.N., and Hopin, V.F. see Belov, A.V.
Dietze, W.T., Lewis, C.R., and Ludowise, M.J. see Lewis, C.R.
Dieulesaint, E., Royer, D., and Rakouth, H. Optical excitation of quartz resonators 381
Dillon, C.R. Network equivalence for crystal prototype Brune section 374
Dingfen, Wu., and Heime, K. New explanation of $N_D^{-1}$ dependence of specific contact resistance for n-GaAs 940
Ditzenberger, J.A., Tsang, W.T., and Logan, R.A. see Tsang, W.T.
Ditzenberger, J.A., Tsang, W.T., and Reinhart, F.K. see Tsang, W.T.
Divino, M., Ramaswamy, V., and Alferness, R.C. see Ramaswamy, V.
Divino, M.D., Alferness, R.C., and Buhl, L.L. see Alferness, R.C.
Dix, C., Westbrook, L.D., and Nelson, A.W. see Westbrook, L.D.
Dobrowolski, J.A. Improved six-port circuit for complex reflection coefficient measurements 748
Donalds, L.J., French, W.G., Mitchell, W.C., Swinehart, R.M., and Wei, T. Electric field sensitive optical fibre using piezoelectric polymer coating 327
Doran, N.J., Blow, K.J., and Hornung, S. see Blow, K.J.

Dorda, G., and Schmitt-Landsiedel, S. see Schmitt-Landsiedel, S.
Dormido, S., Paz, M.B., De La Sen, M., and Mellado, M. see Paz, M.B.
Dorozhkin, L.M., Morozov, A.I., Kulakov, M.A., Pleshkov, G.M., and Chayanov, B.A. see Morozov, A.I.
Dostál, T., and Pospíšil, J. Hybrid models of 3-port immittance convertors and current and voltage conveyors 887
Douklias, N., Schöner, G., Klement, E., and Schiffner, G. see Schöner, G.
Downs, J.W., Asawa, C.K., Yao, S.K., Stearns, R.C., and Mota, N.L. see Asawa, C.K.
Drummond, T.J., Su, S.L., Lyons, W.G., Fischer, R., Kopp, W., Morkoc, H., Lee, K., and Shur, M.S. Enhancement of electron velocity in modulation -doped (Al, Ga)As/GaAs FETs at cryogenic temperatures 1057
Drummond, T.J., Su, S.L., Fischer, R., Lyons, W.G., Thorne, R.E., Kopp, W., and Morkoc, H. see Su, S.L.
Dubost, G. Far field radiated by rectangular patch microstrip antenna 991
Dubost, G. Transmission-line model analysis of a lossy rectangular microstrip patch 281
Duchemin, J.P., Hersee, S., Baldy, M., Assenat, P., and De Cremoux, B. see Hersee, S.
Duchemin, J.P., Hersee, S.D., Baldy, M., Assenat, P., and De Cremoux, B. see Hersee, S.D.
Duchemin, J.P., Hersee, S.D., Hirtz, J.P., and Baldy, M. see Hersee, S.D.
Duchemin, J.P., Razeghi, M., Hirtz, P., Blondeau, R., Larivain, J.P., Noel, L., and de Cremoux, B. see Razeghi, M.
Duchemin, J.P., Razeghi, M., Poisson, M.A., Larivain, J.P., de Cremoux, B., and Voos, M. see Razeghi, M.
Duhamel, P., and Hollmann, H. Number-theoretic transforms with 2 as a root of unity 978
Dumas, J.M., Paugam, J., and le Mouellic, C. Evidence of detrimental surface effects on GaAs power MESFETs 1094
Dupont, P., Sansonetti, P., Alard, F., Vassallo, C., Kammerer, P., Francois, P.L., Monerie, M., and Gabriagues, J.M. see Sansonetti, P.
Dürr, W., and Jirmann, J. see Jirmann, J.
Dussault, L., Boutin, N., and Morissette, S. see Boutin, N.
Dutt, B.V., Temkin, H., and Chin, A.K. see Temkin, H.
Dutta, N.K. Temperature dependence of threshold current of GaAs quantum well lasers 451
Duvall, J.P., Matthaei, G.L., Harris, C.E., Kim, Y.M., and Park, D.C. see Matthaei, G.L.
Dvorak, V. Phase-plane analysis of simple Josephson junction model e150
Dyott, R.B., and Schrank P.F. Self-locating elliptically cored fibre with an accessible guiding region 980 e1065

## E

Eastman, L.F., and Ankri, D. see Ankri, D.
Eastman, L.F., Hollis, M.A., and Wood, C.E.C. see Hollis, M.A.
Eastman, L.F., Wood C.E.C., Board, K., Singer, K., and Malik, R. see Wood C.E.C.
Eastman, L.F., Xin, S.H., Wood, C.E.C., DeSimone, D., and Palmateer, S. see Xin, S.H.
Easton, B.C., Stroomer, M.V.C., Powell, M.J., and Chapman, J.A. see Stroomer, M.V.C.
Ebeling, K.J., Coldren, L.A., Miller, B.I., and Rentschler, J.A. Generation of single-longitudinal-mode subnanosecond light pulses by high-speed current modulation of monolithic two-section semiconductor lasers 901
Edahiro, T., Kawachi, M., Kawasaki, B.S., and Hill, K.O. see Kawachi, M.
Edahiro, T., Kawachi, M., and Toba, H. see Kawachi, M.
Edahiro, T., Kawachi, M., Yasu, M., Tomaru, S., and Sakaguchi, S. see Kawachi, M.
Eddolls, D.V., Maher, E.F., Holeman, B.R., and Humphreys, R.G. see Maher, E.F.
Ehrhardt, J.J., and Michel, C. see Michel, C.
Eirug Davies, D., and Kennedy, E.F. Implantation annealing by thermal imaging 282
Ejiri, Y., Namihira, Y., and Mochizuki, K. Stress difference in elliptically cladded fibres 603
Ejiri, Y., Namihira, Y., and Mochizuki, K. see Namihira, Y.
Ejiri, Y., Tatekura, K., and Yamamoto, H. see Tatekura, K.
Ekanayake, N. Serial synthesis of minimum-shift-keyed signals 827
Ellem, B.A., Calligaro, R.B., Payne, D.N., and Anderssen, R.S. see Calligaro, R.B.
Elliott, C.R., Regnault, J.C., and Wakefield, B. Nonradiative regions in GaInAsP/InP double heterostructure laser material: correlation with dislocation clusters in the substrates 7
Elliott, C.T., Ballingall, R.A., Blenkinsop, I.D., Baker, I.M., and Jenner, D. see Ballingall, R.A.
Elze, G., Albrecht, W., Enning, B., Walf, G., and Wenke, G. see Albrecht, W.
Emery, K., Green, M.A., and Blakers, A.W. see Green, M.A.
Eng, S.T., Alping, A., Andersson, T., and Tell, R. see Alping, A.
Eng, S.T., Bentland, B., Bergman, L.A., and Tell, R. see Bentland, B.
Enning, B., Albrecht, W., Elze, G., Walf, G., and Wenke, G. see Albrecht, W.
Enokihara, A., Izutsu, M., and Sueta, T. see Izutsu, M.
Enomoto, T., Ishihara, T., and Yasumoto, Masa-Aki. Integrated tapped MOS analogue delay line using switched capacitor technique 193
Enomoto, T., Ishihara, T., Yasumoto, M., and Aizawa, T. see Ishihara, T.
Enomoto, T., and Yasumoto, M. see Yasumoto, M.
Eriksrud, M., and Mickelson, A.R. Experimental investigation of variation of backscattered power level with numerical aperture in multimode optical fibres 130
Escobosa, A., Kräutle, H., and Beneking, H. Rectifying GaAs-GaAlAs-GaAs structures by MOCVD compositional grading 888
Esser, L.J.M., and Pelgrom, M.J.M. see Pelgrom, M.J.M.
Etienne, P., Delagebeaudeuf, D., Delescluse, P., Massies, J., Laviron, M., Chaplart, J., and Linh, T. see Delagebeaudeuf, D.
Etienne, P., Massies, J., Rochette, J., Delescluse, P., Chevrier, J., and Linh, N.T. see Massies, J.
Ettenberg, M., and Botez, D. High-power diode lasers for optical recording with operating lifetimes in excess of 10 000 h 153
Eu, V.K., Feng, M., Kanbar, H., and Siracusa, M. see Feng, M.
Eu, V.K., Feng, M., Siracusa, M., Watkins, E., Kimura, H., and Winston, H. see Feng, M.
Evanno, M.H., and Vaterkowski, J.L. Velocity/field characteristic measurement using a high-frequency modulated solid-state laser diode 417
Evans, B.G., Upton, S.A.J., and Holt, A.R. see Upton, S.A.J.

## F

Facq, F., Liang, G.T., and Arnaud, J. see Liang, G.T.
Facq, P., Barthelemy, A., Froehly, C., and Arnaud, J. see Barthelemy, A.
Faguet, J., Tsironis, C., Kermarrec, C., and Harrop, P. see Tsironis, C.
Falciasecca, G., Corzani, T., and Manià, L. see Corzani, T.
Fang, S.C., and Tsividis, Y. see Tsividis, Y.
Faruque, S.M. Switched-capacitor FIR cell for n-path filters 431
Faulkner, D.W., Bickers, L., and Cochrane, P. see Bickers, L.
Faulkner, N., Shepherd, P.R., Vilar, E., and Bradsell, P. see Shepherd, P.R.
Fauquembergue, R., Pernisek, M., and Constant, E. Monte-Carlo simulation of space-charge injection FET 670
Favennec, P.N., Deveaud, B., Salvi, M., Martinez, A., and Armand, C. Redistribution of implanted oxygen in GaAs 202
Favennec, P.N., Henry, L., Regreny, A., and Salvi, M. Selected-area molecular beam epitaxy on ion-implanted GaAs substrates 933
Favre, F., and Le Guen, D. Effect of semiconductor laser phase noise on BER performance in an optical DPSK heterodyne-type experiment 964
Feng, M., Eu, V.K., Siracusa, M., Watkins, E., Kimura, H., and Winston, H. Silicon implanted super low-noise GaAs MESFET 21
Feng, M., Kanbar, H., Eu, V.K., and Siracusa, M. High-efficiency GaAs power MESFETs prepared by ion implantation 1097
Feng, Zhe-Chuan, and Liu, Hong-Du. see Liu, Hong-Du.
Ferrandiz, J.M., Garcia-Lopez, J.A., and Selga, J.M. see Garcia-Lopez, J.A.
Fischer, G., and Moschytz, G.S. High-Q– SC biquad with a minimum capacitor spread 1087
Fischer, R., Drummond, T.J., Su, S.L., Lyons, W.G., Kopp, W., Morkoc, H., Lee, K., and Shur, M.S. see Drummond, T.J.
Fischer, R., Su, S.L., Drummond, T.J., Lyons, W.G., Thorne, R.E., Kopp, W., and Morkoc, H. see Su, S.L.
Fisher, C.F., Tran, D.C., and Sigel, G.H. see Tran, D.C.
Flavin, P.G. Fabrication of curved structures by electron-beam lithography 865
Fleischer, P.E., Ganesan, A., and Tow, J. Low-noise state-space realisation of bandpass active filter (Comment) 149
Fleming, R.J., and Soliman, H.M. see Soliman, H.M.
Flinn, I., and Newcomb, C.V. see Newcomb, C.V.
Flood, J.E. Proposed use of rearrangement in multiexchange telecommunication networks 1072
Fonseca, S.B.de A., and Giarola, A.J. Influence of surface-wave excitation on efficiency of space-wave launching in microstrip disc antennas 406
Forbes, N., Carter, A.C., and Goodfellow, R.C. see Carter, A.C.
Forrest, J.R., and Griffin, J.M. see Griffin, J.M.
Forrest, J.R., and Seeds, A.J. see Seeds, A.J.
Francois, P.L. Dispersion-free single-mode doubly clad fibres with small pure bend losses 818
Francois, P.L. Sensitivity to geometrical parameters in a dispersion-free multicomponent fibre 484 e802
Francois, P.L., Sansonetti, P., Alard, F., Vassallo, C., Kammerer, P., Monerie, M., Gabriagues, J.M., and Dupont, P. see Sansonetti, P.
French, W.G., Donalds, L.J., Mitchell, W.C., Swinehart, R.M., and Wei, T. see Donalds, L.J.
Freyer, J., Harth, W., and Leistner, D. see Harth, W.
Frisch, D.A., and Henning, I.D. Dispersion effects using a 1.52 μm laser 129
Frisch, D.A., and Henning, I.D. see Henning, I.D.
Froehly, C., Barthelemy, A., Facq, P., and Arnaud, J. see Barthelemy, A.
Fujii, T., Wada, O., Yamakoshi, S., Hiyamizu, S., and Sakurai, T. see Wada, O.
Fukuoka, Y., and Itoh, T. Analysis of slow-wave phenomena in coplanar waveguide on a semiconductor substrate 589
Furusawa, K., Amano, K., Niiro, Y., Nunokawa, M., and Wakabayashi, H. see Amano, K.
Furuya, K., Miller, B.I., Coldren, L.A., and Howard, R.E. Novel deposit/spin waveguide interconnection (DSWI) technique for semiconductor integrated optics 204
Furuya, K., Coldren, L.A., Miller, B.I., and Rentschler, J.A. see Coldren, L.A.

## G

Gabriagues, J.M., Sansonetti, P., Alard, F., Vassallo, C., Kammerer, P., Francois, P.L., Monerie, M., and Dupont, P. see Sansonetti, P.
Gait, J. Short cycling in the Kravitz-Reed public key encryption system 706
Ganesan, A., Fleischer, P.E., and Tow, J. see Fleischer, P.E.
Gangadharan, T.S. Broadband end launcher for X band rectangular waveguide 354
Garault, Y., Obregon, J., Balabaud, J.P., and Guillon, P. see Obregon, J.
Garbinski, P.A., Chen, C.Y., Bethea, C.G., and Cho, A.Y. see Chen, C.Y.
Garcia-Lopez, J.A., Ferrandiz, J.M., and Selga, J.M. Design of hybrid diversity on overwater paths 420
Garner, W.B., Gupta, A.K., and Baghdady, E.J. see Gupta, A.K.
Geckeler, S. Simple field calculation for monomode optical waveguides 683
Geissler, R. Microwave parametric upper-sideband down convertor with conversion gain 428
Ghezzo, M., Gildenblat, G., and Norton, J. see Gildenblat, G.
Ghosh, P.K., and Das, M.B. see Das, M.B.
Ghosh, S., Adatia, N., and Watson, B.K. Hybrid-mode feed for multiband applications having a dual-depth corrugation boundary 860
Giallorenzi, T.G., Petuchowski, S.J., and Sigel, G.H. see Petuchowski, S.J.
Giannini, F., Salerno, M., and Sorrentino, R. Effects of parasitics in lowpass elliptic filters for MIC 284
Giarola, A.J., and Fonseca, S.B.de A. see Fonseca, S.B.de A.
Gildenblat, G., Ghezzo, M., and Norton, J. Double polysilicon plate capacitors with oxide/nitride insulator 34
Gill, A., Brotherton, A.D., Shannon, J.M., and Parker, G.J. see Brotherton, A.D.
Ginther, R.J., Tran, D.C., Sigel, G.H., and Levin, K.H. see Tran, D.C.
Glen, P.J. Simple low-cost correlator and multiplier circuits 914
Glodis, P.F., and Lin, C. see Lin, C.
Glodis, P.F., Lin, C., Reed, W.A., Pearson, A.D., and Shang, Hen-Tai. see Lin, C.
Glodis, P.F., Lin, C., Tomita, A., Tynes, A.R., and Philen, D.L. see Lin, C.
Gold, M.P., and Hartog, A.H. Determination of structural parameter variations in single-mode optical fibres by time-domain reflectometry 489
Goldberg, L., Taylor, H.F., and Weller, J.F. Feedback effects in a laser diode due to Rayleigh backscattering from an optical fibre 353
Goldberg, L., Taylor, H.F., and Weller, J.F. FM sideband injection locking of diode lasers 1019
Goldberg, L., Taylor, H.F., and Weller, J.F. Locking bandwidth asymmetry in injection-locked GaAlAs lasers 986
Goldberg, L., Weller, J.F., and Taylor, H.F. Microwave signal generation using an optical self-heterodyne technique 317
Goldberg, L., and Dandridge, A. see Dandridge, A.
Gomi, J., Yoneyama, T., and Nishida, S. Wave propagation in transversely inhomogeneous dielectric waveguide 463
Goodfellow, R.C., Carter, A.C., and Forbes, N. see Carter, A.C.
Goodfellow, R.C., Plastow, R., Harding, M., Griffith, I., and Carter, A.C. see Plastow, R.

Gorodetsky, G., Martin, S.J., Gunshor, R.L., and Pierret, R.F. see Martin, S.J.
Gourrier, S., and Chane, J.P. Plasma anodisation of $Ga_{1-x}In_xAs$ (x=0.35 and 0.10) and study of MOS interface properties 156
Govaerts, R., Desmedt, Y., and Vandewalle, J. see Desmedt, Y.
Granville-George, D.A., and Clarke, R.N. see Clarke, R.N.
Green, G., and Mattauch, R.J. see Mattauch, R.J.
Green, M.A., Emery, K., and Blakers, A.W. Silicon solar cells with reduced temperature sensitivity 97
Green, R.G., Browne, M.A., Deloughry, R.J., and Thorn, R. see Browne, M.A.
Greene, J.E., Barnett, S.A., Ray, M.A., Lastras, A., Kramer, B., Raccah, P.M., and Abels, L.L. see Barnett, S.A.
Greene, K.H., Koepf, G.A., and Kalen, D.M. see Koepf, G.A.
Greene, P.D., Adams, A.R., Patel, D., and Henshall, G.D. see Adams, A.R.
Greene, P.D., Patel, D., Adams, A.R., and Henshall, G.D. see Patel, D.
Griffin, E.J. Six-port reflectometer circuit comprising three directional couplers 491
Griffin, J.M., and Forrest, J.R. Broadband circular disc microstrip antenna 266
Griffith, I., Plastow, R., Harding, M., Carter, A.C., and Goodfellow, R.C. see Plastow, R.
Grime, R.R., Keen, K.M., and Stemp, B.E. see Keen, K.M.
Groeseneken, G., and Maes, H.E. see Maes, H.E.
Grosskopf, G., Küller, L., and Patzak, E. Laser mode partition noise in optical wideband transmission links 493
Guangqi, Y., Nikoonahad, M., and Ash, E.A. Pulse-compression subsurface acoustic microscopy 767
Guggenbühl, W., and Weder, E. see Weder, E.
Guillon, P., Obregon, J., Balabaud, J.P., and Garault, Y. see Obregon, J.
Gunawardena, D.S.R., Kayran, A.H., and King, R.A. Some properties of multidimensional sampling rate conversion 321
Gunshor, R.L., Martin, S.J., Pierret, R.F., and Gorodetsky, G. see Martin, S.J.
Gunshor, R.L., Weng, K.C.-K., Pierret, R.F., and Tsubouchi, K. see Weng, K.C.-K.
Gupta, A.K., Garner, W.B., and Baghdady, E.J. Cascaded bandpass vth-law devices 926
Gurton, P., Leach, J.S., Cannell, G.J., and Robertson, A.J. see Leach, J.S.
Guryanov, A.N., Belov, A.V., Dianov, E.M., Lebedev, P.N., and Hopin, V.F. see Belov, A.V.

## H

Hagimoto, K., Ohta, N., and Nakagawa, K. 4 Gbit/s direct modulation of 1.3 μm InGaAsP/InP semiconductor lasers 796
Haigh, D.G., and Stevenson, J.K. see Stevenson, J.K.
Halder, A.K. Karnaugh map extended to six or more variables 868
Halido, D., Lindström, C., and Scifres, D.R. Far-field radiation patterns of multiple quantum well lasers grown by MO-CVD 765
Halido, D., Lindström, C., Scifres, D.R., and Burnham, R.D. see Lindström, C.
Hall, K.G., Crecraft, D.I., and Davies, C.J.S. see Crecraft, D.I.
Hall, P.J. Multiplier/detector for SAW spectrum analysers 699
Hall, P.S., Prior, C.J., and Ramsdale, P.A. First-order design method and experimental results for microstrip surface circulators with external matching circuits 1043
Halme, S.J., Sharma, A.B., Hubach, E.J.R., and Lähteenoja, M. see Sharma, A.B.
Halme, S.J., Sharma, A.B., Lähteenoja, M., and Hubach, E.J.R. see Sharma, A.B.
Hamasaki, Y., Kuhara, Y., Kawakami, A., Murakami, Y., Tatsumi, M., Takimoto, H., Tada, K., and Mitsui, T. see Kuhara, Y.
Hamdy, S.M.A., and Parker, E.A. Comparison of modal analysis and equivalent circuit representation of E-plane arm of the Jerusalem cross 94
Hamdy, S.M.A., and Parker, E.A. Current distribution on the elements of a square loop frequency selective surface 624
Hanamitsu, K., Ohsaka, S., Yoshida, K., Nishi, H., Hori, K., and Takusagawa, M. Semicylindrical Zn-diffused stripe GaAlAs laser diodes with very low threshold currents 853
Hanawa, F., Ohmori, Y., and Nakahara, M. see Ohmori, Y.
Haneishi, M., Nambara, T., and Yoshida, S. Study on ellipticity properties of single-feed-type circularly polarised microstrip antennas 191
Hanes, L., Ayasli, Y., Reynolds, L.D., and Vorhaus, J.L. see Ayasli, Y.
Hanson, J.V., and De Carvalho, J.M. see De Carvalho, J.M.
Haond, M., Adès, C., and Vu, D.-P. Fast annealing of 4 in arsenic-implanted silicon wafers using an imaging furnace 694
Haond, M., and Vu, D.P. Use of incoherent light for annealing implanted Si wafers and growing single-crystal Si on $SiO_2$ 727
Harding, M., Plastow, R., Griffith, I., Carter, A.C., and Goodfellow, R.C. see Plastow, R.
Harmon, R.A. Polarisation stability in long lengths of monomode fibre 1058
Harris, C.E., Matthaei, G.L., Kim, Y.M., Park, D.C., and Duvall, J.P. see Matthaei, G.L.
Harris, C.E., Matthaei, G.L., Park, D.C., and Kim, Y. see Matthaei, G.L.
Harris, D.J., and Mak, S. Impatt oscillator for groove guide at 95 GHz 399
Harrison, H.B., and Reeves, G.K. see Reeves, G.K.
Harrop, P., Tsironis, C., Kermarrec, C., and Faguet, J. see Tsironis, C.
Harsh, S., Agarwal, S.K., and Jain, S.C. see Agarwal, S.K.
Hart, B.L. Automatic start-up technique for complementary PTAT current generators 776
Hart, B.L., and Barker, R.W.J. Modified current mirror with a 'voltage-following' capability 970
Harth, W., Leistner, D., and Freyer, J. FM noise measurement of W-band impatt diodes with a quasi-optical direct detection system 355
Harth, W., and Claassen, M. see Claassen, M.
Hartman, N., Vahey, D., Kidd, R., and Browning, M. Fabrication and testing of a nickel-coated single-mode fibre magnetometer 224
Hartog, A.H., and Gold, M.P. see Gold, M.P.
Hasegawa, H., Ishii, K., Sawada, T., and Ohno, H. see Ishii, K.
Hasegawa, H., and Sawada, T. see Sawada, T.
Hashimoto, K.Y., Igarashi, Y., Kogo, H., and Yamaguchi, M. Radiation conductance of SSBW IDT on rotated Y-cuts of $LiNbO_3$ 331
Hashizume, N., Awano, Y., Tomizawa, K., and Kawashima, M. see Awano, Y.
Hashizume, N., Tomizawa, K., Awano, Y., and Suzuki, F. see Tomizawa, K.
Hayashi, Y., Kitazawa, T., and Kumagami, H. see Kitazawa, T.
Hayashi, Y., and Sakata, I. see Sakata, I.
Hayashibara, G.M., Tahim, R.S., and Chang, K. see Tahim, R.S.
Hayata, K., Koshiba, M., and Suzuki, M. see Koshiba, M.
Haydl, W.H., Bosch, R., and Rüdiger, J. Waveguide/resonant-disc circuits for millimetre-wave devices 307
Healey, P., and Malyon, D.J. OTDR in single-mode fibre at 1.5 μm using heterodyne detection 862
Healey, P., and Smith D.R. OTDR in single-mode fibre at 1.55 μm using a semiconductor laser and PINFET receiver 959
Healey, P., Payne, D.B., and McCartney, D.J. see Payne, D.B.
Healey, P., Stern, J.R., Payne, D.B., McCartney, D.J., Lindsey, P., Russ, D.M., and Stewart, J.H. see Stern, J.R.
Heatley, D.J.T. Unrepeatered video transmission using pulse frequency modulation over 100 km of monomode optical fibre 369
Heidemann, R., Pfeiffer, Th., and Jäger, D. Optoelectronic generation of microwave power 783
Heime, K., and Dingfen, Wu. see Dingfen, Wu.
Heinen, J. 1.3 μm InGaAsP/InP light emitting diodes with internally defined emission area prepared by single-step LPE technique 23
Heinen, J. Preparation and properties of monolithically integrated lenses on InGaAsP/InP light-emitting diodes 831
Heinlein, W.E., and Klein, K.-F. see Klein, K.-F.
Heinlein, W.E., Klein, K.-F., and Witte, K.-H. see Klein, K.-F.
Heinlein, W.E., and Rabov, S. see Rabov, S.
Heinz, C., and Schmidt auf Altenstadt, W. GaSb photodiode for detection of 1.73 μm radiation of Er:YLF laser 859
Hemment, P.L.F., Maydell-Ondrusz, E., and Scovell, P.D. Ion beam annealed $As^+$ implanted silicon 57
Hemment, P.L.F., Maydell-Ondrusz, E.A., Stephens, K.G., and Moffat, S. see Maydell-Ondrusz, E.A.
Hemment, P.L.F., Pitcher, P.G., and Davis, Q.V. see Pitcher, P.G.
Henaff, J., Auld, B.A., and Renard, A. see Auld, B.A.
Henning, I. Technique for measuring true time-resolved spectra of a semiconductor laser 368
Henning, I.D., and Frisch, D.A. Statistical analysis of instantaneous laser spectra 465
Henning, I.D., and Frisch, D.A. see Frisch, D.A.
Henry, C.H., Logan, R.A., van der Ziel, J.P., and Temkin, H. see Logan, R.A.
Henry, L., Lecrosnier, D., L'Haridon, H., Paugam, J., Pelous, G., Richou, F., and Salvi, M. N-channel MISFETs on semi-insulating InP for logic applications 102
Henry, L., Favennec, P.N., Regreny, A., and Salvi, M. see Favennec, P.N.
Henry, R.M., Beck, C.M., Lowe, B.T., and Plaskowski, A. see Beck, C.M.
Henshall, G.D., Adams, A.R., Patel, D., and Greene, P.D. see Adams, A.R.
Henshall, G.D., Patel, D., Adams, A.R., and Greene, P.D. see Patel, D.
Herben, M.H.A.J. Amplitude and phase scintillation measurements on 8.2 km line-of-sight path at 30 GHz 287
Herbst, D., Brodarac, D., Hosticka, B.J., and Hoefflinger, B. see Brodarac, D.
Hersee, S., Baldy, M., Assenat, P., De Cremoux, B., and Duchemin, J.P. Low-threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM VPE 618
Hersee, S.D., Baldy, M., Assenat, P., De Cremoux, B., and Duchemin, J.P. Very low threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM-VPE 870
Hersee, S.D., Hirtz, J.P., Baldy, M., and Duchemin, J.P. High-mobility selectively doped GaAs/AsAlAs structures grown by low-pressure OM-VPE 1076
Hershey, J.E., and Yarlagadda, R. see Yarlagadda, R.
Hickin, J. Iterative approach to multivariable control 671
Higuchi, H., Namizaki, H., Hirano, R., Oomura, E., Sakakibara, Y., and Susaki, W. see Namizaki, H.
Hill, J.J., and Jewson, P.M. Digital method of sweep frequency generation 1017
Hill, K.O., Kawachi, M., and Kawasaki, B.S. see Kawachi, M.
Hill, K.O., Kawachi, M., Kawasaki, B.S., and Edahiro, T. see Kawachi, M.
Hilsum, C., Bradshaw, M.J., and Raynes, E.P. see Bradshaw, M.J.
Hirano, R., Namizaki, H., Higuchi, H., Oomura, E., Sakakibara, Y., and Susaki, W. see Namizaki, H.
Hiraoka, M., and Kawanishi, H. see Kawanishi, H.
Hiraoka, M., Kawanishi, H., Yoshioka, K., Nishio, K., Nakagomi, T., and Tanaka, S. see Kawanishi, H.
Hirota, Y., and Kobayashi, T. see Kobayashi, T.
Hirtz, J.P., Hersee, S.D., Baldy, M., and Duchemin, J.P. see Hersee, S.D.
Hirtz, P., Razeghi, M., Blondeau, R., Larivain, J.P., Noel, L., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Hiyamizu, S., Wada, O., Yamakoshi, S., Fujii, T., and Sakurai, T. see Wada, O.
Hobdell, J.L., Biggin, J.W., and Band, K.S. Low-loss Lange coupler 815
Hodgkinson, T.G., Smith, D.W., and Wyatt, R. 1.5 μm optical heterodyne system operating over 30 km of monomode fibre 929
Hodgkinson, T.G., Wyatt, R., and Smith, D.W. Experimental assessment of a 140 Mbit/s coherent optical receiver at 1.52 μm 523
Hoefflinger, B., Brodarac, D., Herbst, D., and Hosticka, B.J. see Brodarac, D.
Hökenek, E., Brugger, U.W., and Moschytz, G.S. New frequency transformation for the accurate design of SC ladder filters 276
Holden, A.J., and Debney, B.T. Improved theory of ballistic transport in one dimension 558
Holeman, B.R., Maher, E.F., Eddolls, D.V., and Humphreys, R.G. see Maher, E.F.
Hollis, M.A., Eastman, L.F., and Wood, C.E.C. Measurement of J/V characteristics of a GaAs submicron $n^+$-$n^-$-$n^+$ diode 570
Hollmann, H., and Duhamel, P. see Duhamel, P.
Holmes, F.E., and Jamal, H. see Jamal, H.
Holmes, J.N. Buffering strategy for variable-symbol-rate speech waveform coders 691
Holonyak, N., Burnham, R.D., Streifer, W., Scifres, D.R., Lindström, C., and Paoli, T.L. see Burnham, R.D.
Holt, A.R., Upton, S.A.J., and Evans, B.G. see Upton, S.A.J.
Honda, T., Mizutani, T., Ishida, S., and Kawasaki, Y. see Mizutani, T.
Hong, C.S., Kasemset, D., Patel, N.B., Kim, M.E., and Dapkus, P.D. Low-threshold oxide stripe GaAs/GaAlAs lasers grown by MOCVD 497
Hong, U.S., and Jansen, R.H. Numerical analysis of shielded dielectric resonators including substrate, support disc and tuning post 1000
Hooper, R.C., Smith, D.R., Smyth, P.P., and Wake, D. see Smith, D.R.
Hopin, V.F., Belov, A.V., Dianov, E.M., Lebedev, P.N., and Guryanov, A.N. see Belov, A.V.
Hori, K., Hanamitsu, K., Ohsaka, S., Yoshida, K., Nishi, H., and Takusagawa, M. see Hanamitsu, K.
Horiguchi, M., Jinguji, K., Shibata, S., Kanamori, T., Mitachi, S., and Manabe, T. see Jinguji, K.
Horii, K., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Hornung, S., Blow, K.J., and Doran, N.J. see Blow, K.J.
Hornung, S., Kashyap, R., Reeve, M.H., Bandurek, G.R., and Nevett, J.E. see Kashyap, R.
Hornung, S., and Nelson, B.P. see Nelson, B.P.
Hosticka, B.J., Kleine, U., Vogt, H., and Zimmer, G. DICMOS-novel MOS logic 930
Hosticka, B.J., Brodarac, D., Herbst, D., and Hoefflinger, B. see Brodarac, D.
Houghton, A.J.N., and Buchmann, P. see Buchmann, P.

Houston, P.A., Benson, T.M., Syrbu, A.V., and Chand, N. see Benson, T.M.
Houston, P.A., Chand, N., and Syrbu, A.V. see Chand, N.
Houston, P.A., Claxton, P.A., Shirafuji, J., and Robson, P.N. see Claxton, P.A.
Howard, R.E., Furuya, K., Miller, B.I., and Coldren, L.A. see Furuya, K.
Howard, R.E., Stolen, R.H., and Pleibel, W. see Stolen, R.H.
Huang, F., and Paige, E.G.S. Influence of size and shape on reflection of surface acoustic waves by thin aluminium dots on lithium niobate 232
Hubach, E.J.R., Sharma, A.B., Halme, S.J., and Lähteenoja, M. see Sharma, A.B.
Hubach, E.J.R., Sharma, A.B., Lahteenoja, M., and Halme, S.J. see Sharma, A.B.
Hughes, K.A. Mobile propagation in London at 936 MHz 141
Humpage, W.D., and Wong, K.P. z-plane analysis of networks of distributed and discrete systems 502
Humphreys, R.G., Maher, E.F., Eddolls, D.V., and Holeman, B.R. see Maher, E.F.
Hurst, S.L., Miller, D.M., and Muzio, J.C. Spectral method of Boolean function complexity 572
Hurst, S.L., Muzio, J., and Miller, D.M. see Muzio, J.

## I

Ibrahim, M.F., and Parsons, J.D. Urban mobile radio propagation at 900 MHz 113
Iga, K., Motegi, Y., and Soda, H. see Motegi, Y.
Iga, K., Oikawa, M., and Misawa, S. see Oikawa, M.
Igarashi, Y., Hashimoto, K.Y., Kogo, H., and Yamaguchi, M. see Hashimoto, K.Y.
Iio, S., Nakano, H., and Yamauchi, J. see Nakano, H.
Ikegami, T., Asahi, H., Kawamura, Y., and Nagai, H. see Asahi, H.
Ikegami, T., Itaya, Y., Matsuoka, T., Nakano, Y., Suzuki, Y., and Kuroiwa, K. see Itaya, Y.
Ikegami, T., Matsuoka, T., Nagai, H., Itaya, Y., Noguchi, Y., and Suzuki, Y. see Matsuoka, T.
Inaba, H., Onodera, N., and Ito, H. see Onodera, N.
Inada, K., Yamauchi, R., and Miyamoto, M. see Yamauchi, R.
Ingram, D.G.W., and Tjhung, T.T. Application of transform techniques to digital line codes and data transmission 949
Ino, M., Ohwada, K., Mizutani, T., and Asai, K. see Ohwada, K.
Inoue, M., Shirafuji, J., Amano, M., and Inuishi, Y. see Shirafuji, J.
Inuishi, Y., Shirafuji, J., Amano, M., and Inoue, M. see Shirafuji, J.
Irving, L.D., Cameron, D.C., Whitehouse, C.R., and Woodward, J. see Cameron, D.C.
Ishida, S., Mizutani, T., Honda, T., and Kawasaki, Y. see Mizutani, T.
Ishihara, K., Murakami, Y., Negishi, Y., and Kojima, N. see Murakami, Y.
Ishihara, K., Noguchi, K., Murakami, Y., and Kimura, Y. see Noguchi, K.
Ishihara, K., Yabuta, T., and Negishi, Y. see Yabuta, T.
Ishihara, T., Enomoto, T., Yasumoto, M., and Aizawa, T. High-speed NMOS operational amplifier fabricated using VLSI technology 159
Ishihara, T., Enomoto, T., and Yasumoto, Masa-Aki. see Enomoto, T.
Ishii, H., Koshiba, M., and Suzuki, M. see Koshiba, M.
Ishii, K., Sawada, T., Ohno, H., and Hasegawa, H. InGaAs enhancement-mode MISFETs using double-layer gate insulator 1034
Ishikawa, R., Seki, M., Kobayashi, K., Odagiri, Y., Shikada, M., and Tanigawa, T. see Seki, M.
Isobe, T., Awaka, J., Shimada, M., and Ouchi, E. see Awaka, J.
Itaya, Y., Matsuoka, T., Nakano, Y., Suzuki, Y., Kuroiwa, K., and Ikegami, T. New 1.5 μm wavelength GaInAsP/InP distributed feedback laser 1006
Itaya, Y., Matsuoka, T., Nagai, H., Noguchi, Y., Suzuki, Y., and Ikegami, T. see Matsuoka, T.
Ito, H., Onodera, N., and Inaba, H. see Onodera, N.
Itoh, T., and Fukuoka, Y. see Fukuoka, Y.
Itoh, T., and Shih, Y.C. see Shih, Y.C.
Iwasaki, T., Yokoshima, I., and Nakamura, K. Pyroelectric substitution method for calibrating optical fibre components attenuation 385
Iwashita, K., Nakagawa, K., Matsouka, T., and Nakahara, M. 400 Mbit/s transmission test using a 1.53 μm DFB laser diode and 104 km single-mode fibre 937
Iwashita, K., Nakagawa, K., Nakano, Y., and Suzuki, Y. Chirp pulse transmission through a single-mode fibre 873
Izutsu, M., Enokihara, A., and Sueta, T. Optical-waveguide micro-displacement sensor 867

## J

Jacard, B., Valenzuela, A., and Maldonado, O. Parallel-planes approximation for propagation in rectangular tunnels 1011
Jackson, D.A., Kersey, A.D., and Corke, M. Confocal Fabry-Perot sensor 227
Jackson, D.A., Kersey, A.D., Corke, M., and Jones, J.D.C. Pseudoheterodyne detection scheme for optical interferometers 1081
Jackson, D.A., Jones, J.D.C., Corke, M., and Kersey, A.D. see Jones, J.D.C.
Jackson, D.A., Kersey, A.D., and Corke, M. see Kersey, A.D.
Jacobsen, G., Olesen, H., Birkedahl, F., and Tromborg, B. Current/frequency-modulation characteristics for directly optical frequency-modulated injection lasers at 830 nm and 1.3 μm 874
Jäger, D., Heidemann, R., and Pfeiffer, Th. see Heidemann, R.
Jain, S.C., Agarwal, S.K., and Harsh, S. see Agarwal, S.K.
Jamal, H., and Holmes, F.E. Novel SC integrator realising the bilinear z-transform 390
Jang, S.J., Cohen, L.G., and Mammel, W.L. see Cohen, L.G.
Janković, N.D. T-emitter bipolar power transistor with negative-temperature-gradient current gain 1085
Jankovic, N.D., and Popovic, R.S. New high-voltage CMOS technology 115
Jansen, R.H., and Hong, U.S. see Hong, U.S.
Jansen, R.H., and Kirschning, M. see Kirschning, M.
Jayasimha, K.N., and Parthasarathy, R. see Parthasarathy, R.
Jenkins, W.K. Residue number system error checking using expanded projection 927
Jenner, D., Ballingall, R.A., Blenkinsop, I.D., Elliott, C.T., and Baker, I.M. see Ballingall, R.A.
Jeunhomme, L., Alard, F., Monerie, M., Sansonetti, P., and Vassallo, C. see Alard, F.
Jewson, P.M., and Hill, J.J. see Hill, J.J.
Jinguji, K., Horiguchi, M., Shibata, S., Kanamori, T., Mitachi, S., and Manabe, T. Material dispersion in fluoride glasses 164
Jirmann, J., and Dürr, W. Optogalvanic stabilisation of a $CO_2$ laser with an electrodynamic tuning element 69
Jirmann, J., and Stanik, K. Simple RF-excited $CO_2$ laser 790
Joindot, I., and Boisrobert, C. Intensity fluctuations in longitudinal modes of a nearly single-mode AlGaAs laser 304
Jones, J.D.C., Corke, M., Kersey, A.D., and Jackson, D.A. Miniature solid-state directional laser Doppler velocimeter 967
Jones, J.D.C., Jackson, D.A., Kersey, A.D., and Corke, M. see Jackson, D.A.
Jordan, J.R., and Kiani-Shabestari, B. FIR filter for generating multi-level signals from single-bit noise sequences 739
Josse, F., Bailey, D.S., Lee, D.L., Andle, J., Soluch, W., Vetelino, J.F., and Chai, B.H.T. see Bailey, D.S.
Junyent-Giralt, G., and Agusti-Comes, R. see Agusti-Comes, R.

## K

Kaede, K., Mito, I., Kitamura, M., Odagiri, Y., Seki, M., Sugimoto, M., and Kobayashi, K. see Mito, I.
Kagiwada, R.S., Yen, K.H., Stokes, R.B., Lau, K.F., and Kong, A. see Yen, K.H.
Kalen, D.M., Koepf, G.A., and Greene, K.H. see Koepf, G.A.
Kalouptsidis, N., Manolakis, D., and Carayannis, G. see Manolakis, D.
Kamei, H., Takeda, Y., and Sasaki, A. see Takeda, Y.
Kamibayashi, T., Mimura, Y., Shinbori, O., and Ota, C. see Mimura, Y.
Kaminow, I.P., Liu, P-L., Lee, T.P., Burrus, C.A., and Ko, J.-S. see Liu, P-L.
Kammerer, P., Sansonetti, P., Alard, F., Vassallo, C., Francois, P.L., Monerie, M., Gabriagues, J.M., and Dupont, P. see Sansonetti, P.
Kamoto, T., Tsuyuki, S., Suto, K., and Sakai, T. see Tsuyuki, S.
Kanamori, T., Jinguji, K., Horiguchi, M., Shibata, S., Mitachi, S., and Manabe, T. see Jinguji, K.
Kanbar, H., Feng, M., Eu, V.K., and Siracusa, M. see Feng, M.
Kanbe, H., Mikami, O., Nakagome, H., and Yamauchi, Y. see Mikami, O.
Kaneda, T., Shirai, T., Yamazaki, S., Yasuda, K., Mikawa, T., and Nakajima, K. see Shirai, T.
Karagöz, C., and Acar, C. Strays-insensitive switched-capacitor network realisation for nth-order voltage transfer functions 966
Karim, A.A.A., Nagarajan, R., and Mirza, K.B. Discrete time MRAS with reduced implementation complexity e150
Kasemset, D., Hong, C.S., Patel, N.B., Kim, M.E., and Dapkus, P.D. see Hong, C.S.
Kashyap, R., Reeve, M.H., Hornung, S., Bandurek, G.R., and Nevett, J.E. Measurement of strain relief in an experimental optical fibre cable 263
Katić, O., and Popovich, M.V. see Popovich, M.V.
Kato, Y., Kitayama, K., Seikai, S., and Uchida, N. Modal equalisation for two-mode fibre link using a step-index fibre 356
Kato, Y., Tanifuji, T., Tokuda, M., and Uchida, N. New optical monitoring method for arc-fusion splice of single-mode fibres and high-precision estimation of splice loss 972
Kato, Y., Yoshimi, M., Kawabuchi, K., Takigawa, T., and Takahashi, M. see Yoshimi, M.
Katoh, K., Yasui, M., and Watanabe, H. Amorphous-silicon silicon-nitride field-effect transistors 599
Kawabuchi, K., Yoshimi, M., Takigawa, T., Takahashi, M., and Kato, Y. see Yoshimi, M.
Kawachi, M., Edahiro, T., and Toba, H. Microlens formation on VAD single-mode fibre ends 71
Kawachi, M., Kawasaki, B.S., and Hill, K.O. Suppression of unwanted self-focusing effects in nonlinear optical experiments using liquid crystal 609
Kawachi, M., Kawasaki, B.S., Hill, K.O., and Edahiro, T. Fabrication of single-polarisation single-mode-fibre couplers 962
Kawachi, M., Yasu, M., Tomaru, S., Edahiro, T., and Sakaguchi, S. Wholly synthesised VAD single-mode fibre 328
Kawakami, A., Kuhara, Y., Hamasaki, Y., Murakami, Y., Tatsumi, M., Takimoto, H., Tada, K., and Mitsui, T. see Kuhara, Y.
Kawamura, Y., Noguchi, Y., Asahi, H., and Nagai, H. MBE-grown InGaAs/InP BH lasers with LPE burying layers 91
Kawamura, Y., Asahi, H., Nagai, H., and Ikegami, T. see Asahi, H.
Kawana, A., Yamada, J., Nagai, H., Kimura, T., and Miya, T. see Yamada, J.
Kawanishi, H., and Hiraoka, M. $Ga_xIn_{1-x}As_yP_{1-y}/Ga_xIn_{1-x}As_yP_{1-y}$ DH visible LED grown on (100) GaAs by LPE in the range of 670-680 nm 602
Kawanishi, H., Hiraoka, M., Yoshioka, K., Nishio, K., Nakagomi, T., and Tanaka, S. LPE growth of $In_{0.48}Ga_{0.52}As_{0.01}P_{0.99}$ lattice-matched to GaAs from an In melt rich in P 384
Kawasaki, B.S., Kawachi, M., and Hill, K.O. see Kawachi, M.
Kawasaki, B.S., Kawachi, M., Hill, K.O., and Edahiro, T. see Kawachi, M.
Kawasaki, Y., Mizutani, T., Ishida, S., and Honda, T. see Mizutani, T.
Kawashima, M., Awano, Y., Tomizawa, K., and Hashizume, N. see Awano, Y.
Kayran, A.H., Gunawardena, D.S.R., and King, R.A. see Gunawardena, D.S.R.
Kayran, A.H., and King, R.A. see King, R.A.
Keen, K.M. Ground station antenna crosspolarisation measurements with an imperfectly polarised ancillary antenna 924
Keen, K.M., Grime, R.R., and Stemp, B.E. Improvements to a surface-wave antenna measurement range with troublesome site effects 439
Kennedy, E.F., and Eirug Davies, D. see Eirug Davies, D.
Kermarrec, C., Tsironis, C., Faguet, J., and Harrop, P. see Tsironis, C.
Kersey, A.D., Jackson, D.A., and Corke, M. High-sensitivity fibre-optic accelerometer 559
Kersey, A.D., Jackson, D.A., and Corke, M. Passive compensation scheme suitable for use in the single-mode fibre interferometer 392
Kersey, A.D., Jackson, D.A., and Corke, M. see Jackson, D.A.
Kersey, A.D., Jackson, D.A., Corke, M., and Jones, J.D.C. see Jackson, D.A.
Kersey, A.D., Jones, J.D.C., Corke, M., and Jackson, D.A. see Jones, J.D.C.
Kerstan, F., and Brückner, V. see Brückner, V.
Kheirallah, H.N., and Olsen, R.L. Comparison of a one- and a two-frequency technique for frequency scaling of rain attenuation statistics 51
Kiani-Shabestari, B., and Jordan, J.R. see Jordan, J.R.
Kidd, R., Hartman, N., Vahey, D., and Browning, M. see Hartman, N.
Kikuchi, H., Suzuki, H., and Yamao, Y. see Suzuki, H.
Kikuchi, K., and Okoshi, T. Simple formula giving spectrum-narrowing ratio of semiconductor-laser output obtained by optical feedback 10
Kim, B., and Das, B. Rapid method of determination of carrier mobility against temperature in GaAs MESFETs 844
Kim, D.Y., and Kim, J.K. New runlength-limited and DC-free line code of minimum bandwidth 1040
Kim, J.K., and Kim, D.Y. see Kim, D.Y.
Kim, J.K., and Shim, Y.S. see Shim, Y.S.
Kim, M.E., Hong, C.S., Kasemset, D., Patel, N.B., and Dapkus, P.D. see Hong, C.S.
Kim, Y., Matthaei, G.L., Harris, C.E., and Park, D.C. see Matthaei, G.L.

Kim, Y.M., Matthaei, G.L., Harris, C.E., Park, D.C., and Duvall, J.P. see Matthaei, G.L.
Kimura, H., Feng, M., Eu, V.K., Siracusa, M., Watkins, E., and Winston, H. see Feng, M.
Kimura, T., Chida, K., Sakaguchi, S, and Wagatsuma, M. see Chida, K.
Kimura, T., and Kobayashi, S. see Kobayashi, S.
Kimura, T., Mukai, T., and Yamamoto, Y. see Mukai, T.
Kimura, T., Saito, S., and Yamamoto, Y. see Saito, S.
Kimura, T., Wagatsuma, M., Shuto, Y., and Yamakawa, S. see Wagatsuma, M.
Kimura, T., Yamada, J., Kawana, A., Nagai, H., and Miya, T. see Yamada, J.
Kimura, Y., Noguchi, K., Murakami, Y., and Ishihara, K. see Noguchi, K.
King, G.D.H., and Cebulski, R. Analogue-to-digital conversion using integrated electro-optic interferometers 1099
King, R.A., and Kayran, A.H. Simple design technique for inherently stable fan filters 127
King, R.A., Gunawardena, D.S.R., and Kayran, A.H. see Gunawardena, D.S.R.
Kinoshita, J., Uematsu, Y., and Okuda, H. see Uematsu, Y.
Kirschning, M., and Jansen, R.H. Accurate model for effective dielectric constant of microstrip with validity up to millimetre-wave frequencies 272
Kishimoto, R. Optical coupler for laser redundancy system 140
Kishino, K., Abe, Y., Tanbun-Ek, T., Arai, S., Koyama, F., Matsumoto, K., Watanabe, T., and Suematsu, Y. see Abe, Y.
Kitamura, M., Mito, I., Kaede, K., Odagiri, Y., Seki, M., Sugimoto, M., and Kobayashi, K. see Mito, I.
Kitamura, M., Mito, I., Kobayashi, Ke., and Kobayashi, Ko. see Mito, I.
Kitayama, K., Kato, Y., Seikai, S., and Uchida, N. see Kato, Y.
Kitazawa, T., Kumagami, H., and Hayashi, Y. Unsymmetric broadside-coupled striplines 425
Klein, K.-F., and Heinlein, W.E. Orientation- and polarisation-dependent cutoff wavelengths in elliptical-core single-mode fibres 640
Klein, K.-F., and Heinlein, W.E. Orientation-dependent time delays of the first higher-order mode in elliptical-core fibres 947
Klein, K.-F., Heinlein, W.E., and Witte, K.-H. Excitation-dependent material dispersion in graded-index fibres 100
Kleine, U., and Pandel, J. Novel switched-capacitor pseudo-N-path filter 66
Kleine, U., Hosticka, B.J., Vogt, H., and Zimmer, G. see Hosticka, B.J.
Klement, E., Schöner, G., Schiffner, G., and Douklias, N. see Schöner, G.
Ko, J.-S., Liu, P-L., Lee, T P., Burrus, C.A., and Kaminow, I.P. see Liu, P-L.
Kobayashi, K., Nishimoto, H., and Lang, R. Experimental observation of asymmetric detuning characteristics in semiconductor laser injection locking 54
Kobayashi, K., Mito, I., Kitamura, M., Kaede, K., Odagiri, Y., Seki, M., and Sugimoto, M. see Mito, I.
Kobayashi, K., Seki, M., Odagiri, Y., Shikada, M., Tanigawa, T., and Ishikawa, R. see Seki, M.
Kobayashi, Ke., Mito, I., Kitamura, M., and Kobayashi, Ko. see Mito, I.
Kobayashi, Ko., Mito, I., Kitamura, M., and Kobayashi, Ke. see Mito, I.
Kobayashi, S., and Kimura, T. Optical phase modulation in an injection locked AlGaAs semiconductor laser 210
Kobayashi, T., and Hirota, Y. Inversion-mode InP MISFET employing phosphorus-nitride gate insulator 180
Kobayashi, T., and Yamaguchi, E. see Yamaguchi, E.
Koepf, G.A., Kalen, D.M., and Greene, K.H. Raman amplification at 1.118 μm in single-mode fibre and its limitation by Brillouin scattering 942
Kogo, H., Hashimoto, K.Y., Igarashi, Y., and Yamaguchi, M. see Hashimoto, K.Y.
Kohno, M., Suemune, I., and Yamanishi, M. see Suemune, I.
Kojima, N., Murakami, Y., Ishihara, K., and Negishi, Y. see Murakami, Y.
Kollberg, E., Cho, A.Y., Zirath, H., Snell, W.W., and Schneider, M.V. see Cho, A.Y.
Konaka, M., Shigyo, N., and Dang, R.L.M. see Shigyo, N.
Kong, A., Yen, K.H., Stokes, R.B., Lau, K.F., and Kagiwada, R.S. see Yen, K.H.
Koo, K.P., and Tran, D.C. Glass-gel-coated single-mode-fibre coupler with programmable power splitting ratio 941
Kopp, W., Drummond, T.J., Su, S.L., Lyons, W.G., Fischer, R., Morkoc, H., Lee, K., and Shur, M.S. see Drummond, T.J.
Kopp, W., Su, S.L., Fischer, R., Drummond, T.J., Lyons, W.G., Thorne, R.E., and Morkoc, H. see Su, S.L.
Koshiba, M., Hayata, K., and Suzuki, M. Approximate scalar finite-element analysis of anisotropic optical waveguides 411
Koshiba, M., Hayata, K., and Suzuki, M. Finite-element analysis of flat overlay waveguides for acoustic surface waves using acoustic surface impedance 530 e936
Koshiba, M., Ishii, H., and Suzuki, M. Simple equivalent network for a rectangular dielectric image guide 473
Koshiba, M., Okada, M., and Suzuki, M. Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method e150
Koshiba, M., Ooishi, K., Miki, T., and Suzuki, M. Finite-element analysis of the discontinuities in a dielectric slab waveguide bounded by parallel plates 33
Koshiba, M., Sato, M., and Suzuki, M. Application of finite-element method to H-plane waveguide discontinuities 364 e802
Koshiba, M., and Suzuki, M. Numerical analysis of planar arbitrarily anisotropic defused optical waveguides using finite-element method 579
Koyama, F., Abe, Y., Kishino, K., Tanbun-Ek, T., Arai, S., Matsumoto, K., Watanabe, T., and Suematsu, Y. see Abe, Y.
Kramer, B., Barnett, S.A., Ray, M.A., Lastras, A., Greene, J.E., Raccah, P.M., and Abels, L.L. see Barnett, S.A.
Kräutle, H., Narozny, P., and Beneking, H. Lateral pnp GaAs bipolar transistor prepared by ion implantation 259
Kräutle, H., Escobosa, A., and Beneking, H. see Escobosa, A.
Kräutle, H., Vescan, L., Selders, J., Kütt, W., and Beneking, H. see Vescan, L.
Kravitz, D.W., and Reed, I.S. Extension of RSA crypto-structure: A Galois approach 255
Krogager, E. Reflection of spherical waves at plane interfaces where relative index of refraction is near unity 689
Krowne, C.M. Radiation patterns in far field from two H-plane coupled rectangular microstrip antennas 645
Kudsia, C.M., Shamasundara, H.N., and Swamy, M.N.S. see Shamasundara, H.N.
Kuhara, Y., Hamasaki, Y., Kawakami, A., Murakami, Y., Tatsumi, M., Takimoto, H., Tada, K., and Mitsui, T. BSO/fibre-optic voltmeter with excellent temperature stability 1055
Kulakov, M.A., Morozov, A.I., Dorozhkin, L.M., Pleshkov, G.M., and Chayanov, B.A. see Morozov, A.I.
Küller, L., Grosskopf, G., and Patzak, E. see Grosskopf, G.
Kumagami, H., Kitazawa, T., and Hayashi, Y. see Kitazawa, T.
Kuntman, H. Modified Ebers-Moll model 293
Kuperus, F., and Arnbak, J. Packet radio in a Rayleigh channel 506
Kuroiwa, K., Itaya, Y., Matsuoka, T., Nakano, Y., Suzuki, Y., and Ikegami, T. see Itaya, Y.
Kurokawa, T., Yoshizawa, T., and Nara, S. see Yoshizawa, T.
Kurumada, K., Yamasaki, K., Asai, K., and Mizutani, T. see Yamasaki, K.
Kurumada, K., Yamasaki, K., and Yamane, Y. see Yamasaki, K.
Kushibiki, J., Horii, K., and Chubachi, N. Leaky SAW velocity on water/silicon boundary measured by acoustic line-focus beam 732
Kushibiki, J., Ohkubo, A., and Chubachi, N. Effect of leaky SAW parameters on V(z) curves obtained by acoustic microscopy 668
Kushioiki, J., Ohkubo, A., and Chubachi, N. Propagation characteristics of leaky SAWs on water/$LiNbO_3$ boundary measured by acoustic microscope with line-focus beam 6
Kushibiki, J., Ohkubo, A., and Chubachi, N. Theorectical analysis for V(z) curves obtained by acoustic microscope with line-focus beam 663
Kushiro, Y., Matshushima, Y., Akiba, S., Sakai, K., Noda, Y., and Utaka, K. see Matshushima, Y.
Kütt, W., Vescan, L., Selders, J., Kräutle, H., and Beneking, H. see Vescan, L.

## L

L'Haridon, H., Henry, L., Lecrosnier, D., Paugam, J., Pelous, G., Richou, F., and Salvi, M. see Henry, L.
Lähteenoja, M., Sharma, A.B., Halme, S.J., and Hubach, E.J.R. see Sharma, A.B.
Lahteenoja, M., Sharma, A.B., Hubach, E.J.R., and Halme, S.J. see Sharma, A.B.
Lampariello, P., and Oliner, A.A. see Oliner, A.A.
Lang, R., Kobayashi, K., and Nishimoto, H. see Kobayashi, K.
Langeac, D. Temperature sensing in twisted single-mode fibres 1022
Langley, R.J., and Parker, E.A. Equivalent circuit model for arrays of square loops 294
Langlois, P.J. Memory based transforms 146
Langlois, P.J. Switching speed of a circuit with positive feedback 172
Larivain, J.P., Razeghi, M., Hirtz, P., Blondeau, R., Noel, L., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Larivain, J.P., Razeghi, M., Poisson, M.A., de Cremoux, B., Duchemin, J.P., and Voos, M. see Razeghi, M.
Larsen, J.R. Results of XPD site-diversity measurements at 11.8 GHz 81
Lastras, A., Barnett, S.A., Ray, M.A., Kramer, B., Greene, J.E., Raccah, P.M., and Abels, L.L. see Barnett, S.A.
Lau, C., and Sewell, J.I. Compact matrix scheme for use in computer analysis of switched-capacitor networks 840
Lau, K.F., Yen, K.H., Stokes, R.B., Kong, A., and Kagiwada, R.S. see Yen, K.H.
Laurinavičius, L., and Tolutis, R. Semiconductor alloy resonator-type HF isolators 243
Lavie, D., and Taylor, W.K. Effects of border variations due to spatial quantisation on binary-image template matching 418
Laviron, M., Delagebeaudeuf, D., Delescluse, P., Tung, Pham.N., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Laviron, M., Tung, P.N., Delagebeaudeuf, D., Delescluse, P., Chaplart, J., and Linh, N.T. see Tung, P.N.
Laviron, M., Tung, P.N., Delescluse, P., Delagebeaudeuf, D., Chaplart, J., and Linh, N.T. see Tung, P.N.
Laybourn, P.J.R., Pun, E.Y.B., Wong, K.K., Andonovic, I., and De La Rue, R.M. see Pun, E.Y.B.
Le Guen, D., and Favre, F. see Favre, F.
le Mouellic, C., Dumas, J.M., and Paugam, J. see Dumas, J.M.
Leach, J.S., Cannell, G.J., Robertson, A.J., and Gurton, P. Low-loss splicing of a 62.4 km single-mode-fibre link 697
Lebedev, P.N., Belov, A.V., Dianov, E.M., Guryanov, A.N., and Hopin, V.F. see Belov, A.V.
Lecrosnier, D., Henry, L., L'Haridon, H., Paugam, J., Pelous, G., Richou, F., and Salvi, M. see Henry, L.
Lee, C.H., Li, M.G., Cao, W.L., and Mathur, V.K. see Li, M.G.
Lee. C.H., Vaucher, A.M., and Li, M.G. see Vaucher, A.M.
Lee, D.L., Bailey, D.S., Josse, F., Andle, J., Soluch, W., Vetelino, J.F., and Chai, B.H.T. see Bailey, D.S.
Lee, K., Drummond, T.J., Su, S.L., Lyons, W.G., Fischer, R., Kopp, W., Morkoc, H., and Shur, M.S. see Drummond, T.J.
Lee, K.F., and Dahele, J.S. see Dahele, J.S.
Lee, M.J., Cozens, J.R., Boucouvalas, A.C., Morris, D.G., and Al-Assam, A. see Cozens, J.R.
Lee, T.P., Burrus, C.A., Liu, P.L., and Dentai, A.G. High-efficiency short-cavity InGaAsP laser with one high-reflectivity mirror 805
Lee, T.P., Burrus, C.A., Marcuse, D., Nelson, R.J., and Dentai, A.G. Measurement of beam parameters of index-guided and gain-guided single-frequency InGaAsP injection lasers 902
Lee, T.P., Liu, P-L., Burrus, C.A., Kaminow, I.P., and Ko, J.-S. see Liu, P-L.
Lee, W.S., and Swanson, J.G. Switching behaviour of $Al_2O_3$-n GaAs MISFETs 1049
Lehto, A., Saniie, J., Luukkala, M., and Rajala, R. see Saniie, J.
Leistner, D., Harth, W., and Freyer, J. see Harth, W.
Lemaire, P.J., and Stone, J. see Stone, J.
Lendvay, E. Liquid phase epitaxy of a new semiconductor AlGaInSb 407
Lenham, A.P., and Wes., R.H. see West, R.H.
Lepschy, A., Mian, G., and Viaro, U. Frequency-domain approach to model-reduction problem 829
Leuzzi, G., and Sorrentino, R. see Sorrentino, R.
Levin, K.H., Tran, D.C., Sigel, G.H., and Ginther, R.J. see Tran, D.C.
Levine, B.F., Van der Ziel, J.P., Logan, R.A., and Bethea, C.G. High-quantum -efficiency low-threshold microcleaved $Al_xGa_{1-x}As$ lasers 690
Lewis, C.R., Dietze, W.T., and Ludowise, M.J. OM-VPE growth of Mg-doped GaAs 569
Li, M.G., Cao, W.L., Mathur, V.K., and Lee, C.H. Wide bandwidth, high-repetition-rate optoelectronic modulation of millimetre waves in GaAs waveguide 454
Li, M.G., Vaucher, A.M., and Lee. C.H. see Vaucher, A.M.
Li, S., and Bosisio, R.G. Automatic analysis of two-port active microwave network 1033
Liang, C.H., and Cheng, D.K. see Cheng, D.K.
Liang, G.T., Facq, F., and Arnaud, J. Image transmission through a single optical fibre by colour coding 660
Lillienhof, H.-J., Pantschew, B., and Schulz, D. Printed geodesic lenses in glass with ion-exchanged film waveguides 344
Lim, C.M., and Yu, Y.N. Output feedback optimal controller for linear single-input system 36

Lin, C., and Glodis, P.F. Tunable fibre Raman oscillator in the 1.32-1.41 μm spectral region using a low-loss, low OH⁻ single-mode fibre 696
Lin, C., Reed, W.A., Pearson, A.D., Shang, Hen-Tai., and Glodis, P.F. Designing single-mode fibres for near-IR(1.1-1.7 μm) frequency generation by phase-matched four-photon mixing in the minimum chromatic dispersion region 87
Lin, C., Tomita, A., Tynes, A.R., Glodis, P.F., and Philen, D.L. Picosecond dispersionless transmission of InGaAsP injection laser pulses at the minimum chromatic dispersion wavelength in a 27 km-long single-mode fibre 882
Lindsey, P., Stern, J.R., Payne, D.B., McCartney, D.J., Healey, P., Russ, D.M., and Stewart, J.H. see Stern, J.R.
Lindström, C., Halido, D., Scifres, D.R., and Burnham, R.D. CW longitudinal mode spectra of multiple quantum well stripe lasers 876
Lindström, C., Burnham, R.D., Streifer, W., Scifres, D.R., Paoli, T.L., and Holonyak, N. see Burnham, R.D.
Lindström, C., Halido, D., and Scifres, D.R. see Halido, D.
Linh, N.T., and Delagebeaudeuf, D. see Delagebeaudeuf, D.
Linh, N.T., Delagebeaudeuf, D., Laviron, M., Delescluse, P., Tung, Pham.N., and Chaplart, J. see Delagebeaudeuf, D.
Linh, N.T., Massies, J., Rochette, J., Delescluse, P., Etienne, P., and Chevrier, J. see Massies, J.
Linh, N.T., Tung, P.N., Delagebeaudeuf, D., Laviron, M., Delescluse, P., and Chaplart, J. see Tung, P.N.
Linh, N.T., Tung, P.N., Delescluse, P., Delagebeaudeuf, D., Laviron, M., and Chaplart, J. see Tung, P.N.
Linh, T., Delagebeaudeuf, D., Delescluse, P., Etienne P., Massies, J., Laviron, M., and Chaplart, J. see Delagebeaudeuf, D.
Liu, Hong-Du., and Feng, Zhe-Chuan Lloyd's mirror interference in a medium - A new method for determining photoelastic index variation 251
Liu, P-L., Lee, T.P., Burrus, C.A., Kaminow, I.P., and Ko, J.-S. Observation of transient spectra and mode partition noise of injection lasers 904
Liu, P.L., Lee, T.P., Burrus, C.A., and Dentai, A.G. see Lee, T.P.
Lockhart, G.B., and Al-Jalili, Y.O. Method for superimposing data on amplitude-modulated signals 379
Logan, R.A., Henry, C.H., van der Ziel, J.P., and Temkin, H. Low-threshold GaInAsP/InP MESA lasers 782
Logan, R.A., van der Ziel, J.P., Temkin, H., and Henry, C.H. InGaAsP/InP (1.3 μm) buried-crescent lasers with separate optical confinement 895
Logan, R.A., Capasso, F., and Tsang, W.T. see Capasso, F.
Logan, R.A., Levine, B.F., Van der Ziel, J.P., and Bethea, C.G. see Levine, B.F.
Logan, R.A., and Tsang, W.T. see Tsang, W.T.
Logan, R.A., Tsang, W.T., and Ditzenberger, J.A. see Tsang, W.T.
Lopriore, L., and Corsini, P. see Corsini, P.
Lowe, B.T., Beck, C.M., Henry, R.M., and Piaskowski, A. see Beck, C.M.
Lucarini, G., Piazza, F., Morandi, C., and Pierfederici, A. Automatic temperature mapping system based on holographic interferometry 623
Ludowise, M.J., Lewis, C.R., and Dietze, W.T. see Lewis, C.R.
Luen, C.H., and Auchterlonie, L.J. Fine tuning of a millimetre-wave open resonator 358
Lumish, S., Cohen, L.G., and Mammel, W.L. see Cohen, L.G.
Luukkala, M., Saniie, J., Lehto, A., and Rajala, R. see Saniie, J.
Lynch, A.C. Microwave open resonator: a paradox 464
Lyons, W.G., Drummond, T.J., Su, S.L., Fischer, R., Kopp, W., Morkoc, H., Lee, K., and Shur, M.S. see Drummond, T.J.
Lyons, W.G., Su, S.L., Fischer, R., Drummond, T.J., Thorne, R.E., Kopp, W., and Morkoc, H. see Su, S.L.

## M

McCanny, J.V., and McWhirter, J.G. Implementation of signal processing functions using 1-bit systolic arrays 241
McCartney, D.J., Payne, D.B., and Healey, P. see Payne, D.B.
McCartney, D.J., Stern, J.R., Payne, D.B., Healey, P., Lindsey, P., Russ, D.M., and Stewart, J.H. see Stern, J.R.
Macchiarella, G. Analysis of rain attenuation models for slant path 486
McDonna, A.P., and Malyon, D.J. see Malyon, D.J.
McIntyre, N. Calculation of I/V characteristics for ion-implanted GaAs MESFETs 208
Maclean, T.S.M. New application for radiation resistance 378
McMahon, R.A., Davis, J.R., and Ahmed, H. see Davis, J.R.
Macura, A., and Rutkowski, J. New method of approximating the acceptable region of non-linear resistive networks 654
McWhirter, J.G., and McCanny, J.V. see McCanny, J.V.
Maes, H.E., and Groeseneken, G. Determination of spatial surface state density distribution in MOS and SIMOS transistors after channel hot electron injection 372
Maher, E.F., Eddolls, D.V., Holeman, B.R., and Humphreys, R.G. Electron-irradiated extrinsic silicon detectors for 3-5 μm focal-plane arrays 216
Mahmid, B., and Auchterlonie, L.J. Measurement of mutual scattering between spheres by use of microwave open resonator e240
Maione, B., and Turchiano, B. New method for approximating time-delay systems with delay-free systems 622
Mak, S., and Harris, D.J. see Harris, D.J.
Maldonado, O., Jacard, B., and Valenzuela, A. see Jacard, B.
Malik, R., Wood C.E.C., Eastman, L.F., Board, K., and Singer, K. see Wood C.E.C.
Malkomes, M. Mutual coupling between microstrip patch antennas 520
Maloberti, F., and Montecchi, F. Low-frequency noise reduction in SC ladder filters 674
Maloberti, F., and Montecchi, F. Parasitic insensitive toggle-switched capacitor and its applications to switched-capacitor networks (Comment) 1061
Maloney, T.J., Saxena, R.R., and Chai, Y.G. AlGaAs/GaAs JFETs by organometallic and molecular beam epitaxy 112
Malyon, D.J., and McDonna, A.P. 102 km unrepeatered monomode fibre system experiment at 140 Mbit/s with an injection locked 1.52 μm laser transmitter 445
Malyon, D.J., and Healey, P. see Healey, P.
Malyon, D.J., and Smith, D.W. see Smith, D.W.
Mammel, W.L., Cohen, L.G., and Jang, S.J. see Cohen, L.G.
Mammel, W.L., Cohen, L.G., and Lumish, S. see Cohen, L.G.
Manabe, T., Jinguji, K., Horiguchi, M., Shibata, S., Kanamori, T., and Mitachi, S. see Jinguji, K.
Manganote, E.J.T., Brosson, P., and Prince, F.C. see Brosson, P.
Manià, L., Corzani, T., and Falciasecca, G. see Corzani, T.
Manning, J., Su, C.B., Schlafer, J., and Olshansky, R. see Su, C.B.
Manolakis, D., Kalouptsidis, N., and Carayannis, G. Efficient determination of FIR Wiener filters with linear phase 429
Marcuse, D. Quantum mechanical explanation of spontaneous emission K-factor 920
Marcuse, D., Lee, T.P., Burrus, C.A., Nelson, R.J., and Dentai, A.G. see Lee, T.P.
Margalit, S., Blauvelt, H., and Yariv, A. see Blauvelt, H.
Marougi, S.D. Effect of disc reflectors on radiation impedance of short-backfire antenna 154
Marrone, M.J., and Rashleigh, S.C. see Rashleigh, S.C.
Marshall, S.A. Cauer continued fraction methods for model reduction (Comment & Reply) 788
Martin, K. New clock feedthrough cancellation technique for analogue MOS switched-capacitor circuits 39
Martin, S.J., Gunshor, R.L., Pierret, R.F., and Gorodetsky, G. Uniaxially strained $ZnO/SiO_2/Si$ SAW resonators 1030
Martin, Y., and Ash, E.A. Photodisplacement microscopy using a semiconductor laser 763
Martin, Y., Wickramasinghe, H.K., Ball, S., and Ash, E.A. see Wickramasinghe, H.K.
Martinelli, G. Efficient adaptive linear predictor 617
Martinez, A., Favennec, P.N., Deveaud, B., Salvi, M., and Armand, C. see Favennec, P.N.
Massies, J., Rochette, J., Delescluse, P., Etienne, P., Chevrier, J., and Linh, N.T. High-mobility $Ga_{0.47}In_{0.53}As$ thin epitaxial layers grown by MBE, very closely lattice-matched to InP 758
Massies, J., Delagebeaudeuf, D., Delescluse, P., Etienne, P., Laviron, M., Chaplart, J., and Linh, T. see Delagebeaudeuf, D.
Mathur, V.K., Li, M.G., Cao, W.L., and Lee, C.H. see Li, M.G.
Matricciani, E. Effects of filtering on rate of change of rain-induced attenuation 477
Matricciani, E. Effects of filtering on statistics of rain-induced fade durations 253
Matricciani, E., and Capsoni, C. see Capsoni, C.
Matshushima, Y., Akiba, S., Sakai, K., Kushiro, Y., Noda, Y., and Utaka, K. High-speed-response InGaAs/InP heterostructure avalanche photodiode with InGaAsP buffer layers 945
Matsouka, T., Iwashita, K., Nakagawa, K., and Nakahara, M. see Iwashita, K.
Matsumoto, K., Abe, Y., Kishino, K., Tanbun-Ek, T., Arai, S., Koyama, F., Watanabe, T., and Suematsu, Y. see Abe, Y.
Matsuoka, T., Nagai, H., Itaya, Y., Noguchi, Y., Suzuki, Y., and Ikegami, T. CW operation of DFB-BH GaInAsP/InP lasers in 1.5 μm wavelength region 27
Matsuoka, T., Suzuki, Y., Noguchi, Y., and Nagai, H. GaInAsP/InP DH laser on semi-insulating InP substrate with terrace structrue 359
Matsuoka, T., Itaya, Y., Nakano, Y., Suzuki, Y., Kuroiwa, K., and Ikegami, T. see Itaya, Y.
Matsushima, Y., Akiba, S., Utaka, K., and Sakai, K. see Akiba, S.
Matsushima, Y., Yamamoto, S., Utaka, K., Akiba, S., Sakai, K., Sakaguchi, S., and Seki, N. see Yamamoto, S.
Matsuyama, I., Susa, K., Satoh, S., and Suganuma, T. see Susa, K.
Mattauch, R.J., and Green, G. Improved whisker pointing technique for micron-size diode contact 143
Matthaei, G.L., Harris, C.E., Kim, Y.M., Park, D.C., and Duvall, J.P. Simple dielectric waveguide bandpass filter 798
Matthaei, G.L., Harris, C.E., Park, D.C., and Kim, Y. Dielectric-waveguide filters using parallel-coupled grating resonators 509
Mattos, T.J.S., Prince, F.C., and Patel, N.B. see Prince, F.C.
Maupfouma, F., and Tiffon, J. Raindrop size distribution from microwave scattering measurements in equatorial and tropical climates 1012
Maurice, D. Phase-shift keying: symbol error rate in presence of random fluctuation noise - an elementary treatment 1112
May, E.J.P., and Mehdi, H.H. Sensitivity of the symmetric form filter 8
Maydell-Ondrusz, E., Hemment, P.L.F., and Scovell, P.D. see Hemment, P.L.F.
Maydell-Ondrusz, E.A., Hemment, P.L.F., Stephens, K.G., and Moffat, S. Processing of titanium films on silicon using a multiscanned electron beam 752
Meckelburg, H.-J. Scatterer reconstruction from multistatic far-field data 341
Mehdi, H.H., and May, E.J.P. see May, E.J.P.
Meinel, H., and Callsen, H. Fin-line pin-diode attenuators and switches for 94 GHz range 541
Meinel, H., and Schmidt, L.-P. see Schmidt, L.-P.
Meissner, J. Calculation of coupling of two grooves in a parallel-plate guide 956
Melek, M., Anderson, A.P., Brown, B.H., and Conway, J. Measurements substantiating localised microwave hyperthermia within a thorax phantom 437
Mellado, M., Paz, M.B., De La Sen, M., and Dormido, S. see Paz, M.B.
Melman, P., and Carlsen, W.J. Elastic tube splice performance with single-mode and multimode fibres 320
Menzel, W., and Callsen, H. 94 GHz balanced fin-line mixer 5
Menzel, W., and Callsen, H. Ultrabroadband balanced fin-line mixer 724
Mercier, L., Vander Vorst, A., and Vanhoenacker, D. see Vander Vorst, A.
Mian, G., Lepschy, A., and Viaro, U. see Lepschy, A.
Michel, C., and Ehrhardt, J.J. Oxidation of (n)-InP by nitric acid 305
Mickelson, A.R., and Eriksrud, M. see Eriksrud, M.
Midgley, D., Clarke, R., and Weston, C.R. see Clarke, R.
Migny, P., and Placais, B. Turn-on delay for Josephson logic devices with high damping 777
Mikami, O., Nakagome, H., Yamauchi, Y., and Kanbe, H. 1.5 μm GaInAsP/InP buried heterostructure lasers fabricated by hybrid combination of liquid-and vapour-phase epitaxy 237
Mikami, O., Saitoh, T., and Nakagome, H. 1.5 μm GaInAsP/InP distributed Bragg reflector lasers with built-in optical waveguide 458
Mikami, O., Saitoh, T., and Nakagome, H. see Saitoh, T.
Mikawa, T., Shirai, T., Yamazaki, S., Yasuda, K., Nakajima, K., and Kaneda, T. see Shirai, T.
Miki, T., Koshiba, M., Ooishi, K., and Suzuki, M. see Koshiba, M.
Millar, C.A. Fundamental mode spot-size measurement in single-mode optical fibres (Comment) 395
Miller, B.I., Cheng, C.L., Coldren, L.A., Rentschler, J.A., and Shen, C.C. see Cheng, C.L.
Miller, B.I., Coldren, L.A., Furuya, K., and Rentschler, J.A. see Coldren, L.A.
Miller, B.I., Ebeling, K.J., Coldren, L.A., and Rentschler, J.A. see Ebeling, K.J.
Miller, B.I., Furuya, K., Coldren, L.A., and Howard, R.E. see Furuya, K.
Miller, D.M., Hurst, S.L., and Muzio, J.C. see Hurst, S.L.
Miller, D.M., Muzio, J., and Hurst, S.L. see Muzio, J.
Milne, W.I., Smith, G.J., and Blackborow, P. see Smith, G.J.

Mimura, Y., Shinbori, O., Kamibayashi, T., and Ota, C. High-strength small reinforcement for spliced optical fibre 190
Mirza, K.B., Karim, A.A.A., and Nagarajan, R. see Karim, A.A.A.
Misawa, S., Oikawa, M., and Iga, K. see Oikawa, M.
Mitachi, S., and Miyashita, T. Preparation of low-loss fluoride glass fibre 170
Mitachi, S., Jinguji, K., Horiguchi, M., Shibata, S., Kanamori, T., and Manabe, T. see Jinguji, K.
Mitchell, W.C., Donalds, L.J., French, W.G., Swinehart, R.M., and Wei, T. see Donalds, L.J.
Mito, I., Kitamura, M., Kaede, K., Odagiri, Y., Seki, M., Sugimoto, M., and Kobayashi, K. InGaAsP planar buried heterostructure laser diode (PBH-LD) with very low threshold current 2
Mito, I., Kitamura, M., Kobayashi, Ke., and Kobayashi, Ko. Double-channel planar buried-heterostructure laser diode with effective current confinement 953
Mitsui, T., Kuhara, Y., Hamasaki, Y., Kawakami, A., Murakami, Y., Tatsumi, M., Takimoto, H., and Tada, K. see Kuhara, Y.
Miya, T., Yamada, J., Kawana, A., Nagai, H., and Kimura, T. see Yamada, J.
Miyamoto, M., Yamauchi, R., and Inada, K. see Yamauchi, R.
Miyashita, T., and Mitachi, S. see Mitachi, S.
Mizutani, T., Ishida, S., Honda, T., and Kawasaki, Y. Threshold voltage of ion implanted GaAs MESFET 53
Mizutani, T., Ohwada, K., Ino, M., and Asai, K. see Ohwada, K.
Mizutani, T., Yamasaki, K., Asai, K., and Kurumada, K. see Yamasaki, K.
Mochizuki, K. Autocorrelation function measurements with fibre interferometers 820
Mochizuki, K., Ejiri, Y., and Namihira, Y. see Ejiri, Y.
Mochizuki, K., Namihira, Y., and Ejiri, Y. see Namihira, Y.
Modone, E., Parisi, G., and Roba, G. Low-loss fibres by a pressurised MCVD method 721
Moeller, R.P., Burns, W.K., and Villarruel, C.A. see Burns, W.K.
Moffat, S., Maydell-Ondrusz, E.A., Hemment, P.L.F., and Stephens, K.G. see Maydell-Ondrusz, E.A.
Monerie, M. Analytical approximation for W-type fibre propagation parameters 386
Monerie, M. Fundamental-mode cutoff in depressed inner cladding fibres 642
Monerie, M., Alard, F., Jeunhomme, L., Sansonetti, P., and Vassallo, C. see Alard, F.
Monerie, M., Sansonetti, P., Alard, F., Vassallo, C., Kammerer, P., Francois, P.L., Gabriagues, J.M., and Dupont, P. see Sansonetti, P.
Montecchi, F., and Maloberti, F. see Maloberti, F.
Moon, R., and Stephenson, F.W. Second-order Q and $\omega$ shifts in RC active filters having nonideal amplifiers 365
Morandi, C., Lucarini, G., Piazza, F., and Pierfederici, A. see Lucarini, G.
Morgan, D.P., Warne, D.H., and Selviah, D.R. Narrow-aperture chirp transducers for SAW convolvers 80
Morgan, D.P., Selviah, D.R., and Warne, D.H. see Selviah, D.R.
Morgan, G.B. Stabilisation of a W-band microstrip oscillator by a dielectric resonator 556
Morgan, R.A., and Pollard, C.J. Enhancement of resist plasma erosion rates by electron-beam hardening 1038
Morissette, S., Boutin, N., and Dussault, L. see Boutin, N.
Morkoc, H. Short-channel GaAs FET fabricated like a MESFET but operating like a JFET 258
Morkoc, H., Drummond, T.J., Su, S.L., Lyons, W.G., Fischer, R., Kopp, W., Lee, K., and Shur, M.S. see Drummond, T.J.
Morkoc, H., Su, S.L., Fischer, R., Drummond, T.J., Lyons, W.G., Thorne, R.E., and Kopp, W. see Su, S.L.
Morozov, A.I., Kulakov, M.A., Dorozhkin, L.M., Pleshkov, G.M., and Chayanov, B.A. Organic piezoelectric high-frequency thin-film transducers 878
Morque, A., Valette, S., and Mottier, P. see Valette, S.
Morris, D.G., Cozens, J.R., Boucouvalas, A.C., Lee, M.J., and Al-Assam, A. see Cozens, J.R.
Morris, G. Currents induced on a conducting half-plane by a plane wave at arbitrary incidence 610
Moschytz, G.S., and Fischer, G. see Fischer, G.
Moschytz, G.S., Hökenek, E., and Brugger, U.W. see Hökenek, E.
Mossadeq, H., Bennett, R.J., and Anand, K.V. Optimisation of implantation conditions for the formation of buried $SiO_2$ layers in silicon 215
Mota, N.L., Asawa, C.K., Yao, S.K., Stearns, R.C., and Downs, J.W. see Asawa, C.K.
Motegi, Y., Soda, H., and Iga, K. Surface-emitting GaInAsP/InP injection laser with short cavity length 461
Mottier, P., Valette, S., and Morque, A. see Valette, S.
Moupfouma, F., and Dereffye, J. Empirical model for rainfall rate distribution 460
Mukai, T., Yamamoto, Y., and Kimura, T. S/N performance of an AlGaAs laser preamplifier and a linear repeater system 382
Murakami, T., Asai, K., and Yamazaki, E. Vector quantiser of video signals 1005
Murakami, Y., Ishihara, K., Negishi, Y., and Kojima, N. Microbending losses of $P_2O_5$-doped graded-index multimode fibre 774
Murakami, Y., Kuhara, Y., Hamasaki, Y., Kawakami, A., Tatsumi, M., Takimoto, H., Tada, K., and Mitsui, T. see Kuhara, Y.
Murakami, Y., Noguchi, K., Kimura, Y., and Ishihara, K. see Noguchi, K.
Murakami, Y., Noguchi, K., Yamashita, K., and Ashiya, F. see Noguchi, K.
Muzio, J., Miller, D.M., and Hurst, S.L. Number of spectral coefficients necessary to identify a class of Boolean functions 577
Muzio, J.C., Hurst, S.L., and Miller, D.M. see Hurst, S.L.
Myers, D.R., Biefeld, R.M., Zipperian, T.E., and Dawson, L.R. Encapsulant-free annealing of ion-implanted GaP 323

## N

Naem, A.A., and Boothroyd, A.R. Compensation tendency of short-channel and narrow-channel effects in small-geometry IGFETs 135
Nagai, H., Asahi, H., Kawamura, Y., and Ikegami, T. see Asahi, H.
Nagai, H., Kawamura, Y., Noguchi, Y., and Asahi, H. see Kawamura, Y.
Nagai, H., Matsuoka, T., Itaya, Y., Noguchi, Y., Suzuki, Y., and Ikegami, T. see Matsuoka, T.
Nagai, H., Matsuoka, T., Suzuki, Y., and Noguchi, Y. see Matsuoka, T.
Nagai, H., Nakano, Y., Takehei, K., Noguchi, Y., and Suzuki, Y. see Nakano, Y.
Nagai, H., Yamada, J., Kawana, A., Kimura, T., and Miya, T. see Yamada, J.
Nagarajan, R., Karim, A.A.A., and Mirza, K.B. see Karim, A.A.A.
Nair, K.G., and Paul, P.O. see Paul, P.O.
Naitoh, M., Sakai, S., and Umeno, M. InGaAsP/InP Schottky collector phototransistor 656
Nakagawa, K., Hagimoto, K., and Ohta, N. see Hagimoto, K.
Nakagawa, K., Iwashita, K., Matsouka, T., and Nakahara, M. see Iwashita, K.
Nakagawa, K., Iwashita, K., Nakano, Y., and Suzuki, Y. see Iwashita, K.
Nakagome, H., Mikami, O., and Saitoh, T. see Mikami, O.
Nakagome, H., Mikami, O., Yamauchi, Y., and Kanbe, H. see Mikami, O.
Nakagome, H., Saitoh, T., and Mikami, O. see Saitoh, T.
Nakagomi, T., Kawanishi, H., Hiraoka, M., Yoshioka, K., Nishio, K., and Tanaka, S. see Kawanishi, H.
Nakahara, M., Chida, K., and Okazaki, H. see Chida, K.
Nakahara, M., Iwashita, K., Nakagawa, K., and Matsouka, T. see Iwashita, K.
Nakahara, M., Ohmori, Y., and Hanawa, F. see Ohmori, Y.
Nakahara, M., Suda, H., and Sudo, S. see Suda, H.
Nakajima, K., Shirai, T., Yamazaki, S., Yasuda, K., Mikawa, T., and Kaneda, T. see Shirai, T.
Nakamura, K., Iwasaki, T., and Yokoshima, I. see Iwasaki, T.
Nakamura, M., Tamura, T., and Ozeki, T. Optical receiver front-end nonlinear distortion 361
Nakano, H., Yamauchi, J., and Iio, S. Tapered backfire helical antenna with loaded termination 158
Nakano, Y., Takehei, K., Noguchi, Y., Suzuki, Y., and Nagai, H. Output power saturation of BH laser under high current operation 501
Nakano, Y., Itaya, Y., Matsuoka, T., Suzuki, Y., Kuroiwa, K., and Ikegami, T. see Itaya, Y.
Nakano, Y., Iwashita, K., Nakagawa, K., and Suzuki, Y. see Iwashita, K.
Nalbantoğlu, A.H. New computation method for characteristic modes 994
Nambara, T., Haneishi, M., and Yoshida, S. see Haneishi, M.
Namihira, Y., Ejiri, Y., and Mochizuki, K. Birefringence in elliptical-cladding single-polarisation fibres 89
Namihira, Y., Wakabayashi, H., and Yamamoto, H. High-stability measuring equipment for very small variations of optical-fibre loss 124
Namihira, Y., Ejiri, Y., and Mochizuki, K. see Ejiri, Y.
Namizaki, H., Hirano, R., Higuchi, H., Oomura, E., Sakakibara, Y., and Susaki, W. Shunt current and excess temperature sensitivity of $I_{th}$ and $\eta_{ss}$ in 1.3 $\mu$m InGaAsP DH lasers 703
Nandi, R. Novel grounded-capacitor ideal FDNR and oscillator using current conveyors 145
Nandi, R. Novel variable-frequency oscillator with single resistor control using DVCCS/DVCVS 144
Naqai, H., Suzuki, Y., and Noguchi, Y. InGaAsP/InP dual-wavelength BH laser array 371
Nara, S., Yoshizawa, T., and Kurokawa, T. see Yoshizawa, T.
Narozny, P., Kräutle, H., and Beneking, H. see Kräutle, H.
Narraway, J.J., and Venkatesan, R. Digital filters with fast coefficient implementation 852
Nassau, K., and Wemple, S.H. Material dispersion slope in optical-fibre waveguides 450
Nazoa-Ruiz, N., and Aitchison, C.S. Use of low dielectric constant substrates for microstrip time-delay triggered Trapatt oscillators 1052
Negishi, Y., Murakami, Y., Ishihara, K., and Kojima, N. see Murakami, Y.
Negishi, Y., Yabuta, T., and Ishihara, K. see Yabuta, T.
Neidert, R.E., Binari, S.C., and Weng, T. Dielectric constant of semi-insulating indium phosphide 987
Nelson, A.W., Westbrook, L.D., and Dix, C. see Westbrook, L.D.
Nelson, B.P., and Hornung, S. Transmission characteristics of a cabled and jointed 30 km monomode optical fibre link 270
Nelson, R.J., Lee, T.P., Burrus, C.A., Marcuse, D., and Dentai, A.G. see Lee, T.P.
Nešić, A. Slotted antenna array excited by a coplanar waveguide 275
Nevett, J.E., Kashyap, R., Reeve, M.H., Hornung, S., and Bandurek, G.R. see Kashyap, R.
Newcomb, C.V., and Flinn, I. Improving the linearity of piezoelectric ceramic actuators 442
Newton, S.A., Bowers, J.E., and Shaw, H.J. see Bowers, J.E.
Newton, S.A., Bowers, J.E., Sorin, W.V., and Shaw, H.J. see Bowers, J.E.
Neyer, A., and Voges, E. Hybrid electro-optical multivibrator operating by finite feedback delay 59
Nichols, P.D. Comparison between techniques for measuring the $LP_{11}$-mode cutoff wavelength in monomode fibres 1008
Nicholson, P.L. Novel architecture for a time division switch 1100
Niekolaas, G., Den Dulk, R.C., and Regenbogen, L.K. False-lock sources in charge-pump phase-lock loops 568
Niiro, Y., Amano, K., Furusawa, K., Nunokawa, M., and Wakabayashi, H. see Amano, K.
Nikoonahad, M., Guangqi, Y., and Ash, E.A. see Guangqi, Y.
Nishi, H., Hanamitsu, K., Ohsaka, S., Yoshida, K., Hori, K., and Takusagawa, M. see Hanamitsu, K.
Nishida, S., Gomi, J., and Yoneyama, T. see Gomi, J.
Nishimoto, H., Kobayashi, K., and Lang, R. see Kobayashi, K.
Nishimura, M., Okoshi, T., Oyamada, K., and Yokota, H. see Okoshi, T.
Nishio, K., Kawanishi, H., Hiraoka, M., Yoshioka, K., Nakagomi, T., and Tanaka, S. see Kawanishi, H.
Noda, J., Sasaki, Y., and Shibata, N. see Sasaki, Y.
Noda, Y., Matshushima, Y., Akiba, S., Sakai, K., Kushiro, Y., and Utaka, K. see Matshushima, Y.
Noel, L., Razeghi, M., Hirtz, P., Blondeau, R., Larivain, J.P., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Noguchi, K., Murakami, Y., Kimura, Y., and Ishihara, K. Ultralong multimode optical fibre fault location using Raman optical time domain reflectometry 542
Noguchi, K., Murakami, Y., Yamashita, K., and Ashiya, F. 52 km-long single-mode optical fibre fault location using the stimulated Raman scattering effect 41
Noguchi, Y., Kawamura, Y., Asahi, H., and Nagai, H. see Kawamura, Y.
Noguchi, Y., Matsuoka, T., Nagai, H., Itaya, Y., Suzuki, Y., and Ikegami, T. see Matsuoka, T.
Noguchi, Y., Matsuoka, T., Suzuki, Y., and Nagai, H. see Matsuoka, T.
Noguchi, Y., Nakano, Y., Takehei, K., Suzuki, Y., and Nagai, H. see Nakano, Y.
Noguchi, Y., Naqai, H., and Suzuki, Y. see Naqai, H.
Norton, J., Gildenblat, G., and Ghezzo, M. see Gildenblat, G.
Norton, R.E., Scifres, D.R., Bailey, M.D., Burnham, R.D., and Rawson, E.G. see Scifres, D.R.
Nunokawa, M., Amano, K., Niiro, Y., Furusawa, K., and Wakabayashi, H. see Amano, K.
Nunokawa, M., Tatekura, K., and Yamamoto, H. see Tatekura, K.

## O

O'Reilly, J.J. Temporal quantisation noise 219
O'Reilly, J.J., and Da Rocha, J.R.F. see Da Rocha, J.R.F.

Obregon, J., Balabaud, J.P., Guillon, P., and Garault, Y. New radial power combiner using tubular dielectric cavities 771
Obregon, J., and Perez, F. see Perez, F.
Odagiri, Y., Mito, I., Kitamura, M., Kaede, K., Seki, M., Sugimoto, M., and Kobayashi, K. see Mito, I.
Odagiri, Y., Seki, M., Kobayashi, K., Shikada, M., Tanigawa, T., and Ishikawa, R. see Seki, M.
Ogawa, A., and Allnutt, J.E. Correlation of 6 and 4 GHz depolarisation on slant paths 230
Ohkubo, A., Kushibiki, J., and Chubachi, N. see Kushibiki, J.
Ohm, G., and Schmöller, G. 750 MHz microstrip bandpass filter on barium tetratitanate substrate 661
Ohmori, Y., Hanawa, F., and Nakahara, M. Fabrication of low-loss $Al_2O_3$-doped silica fibres 761
Ohno, H., Ishii, K., Sawada, T., and Hasegawa, H. see Ishii, K.
Ohsaka, S., Hanamitsu, K., Yoshida, K., Nishi, H., Hori, K., and Takusagawa, M. see Hanamitsu, K.
Ohta, N., Hagimoto, K., and Nakagawa, K. see Hagimoto, K.
Ohwada, K., Ino, M., Mizutani, T., and Asai, K. GaAs 256-bit static RAM 299
Oikawa, M., Iga, K., and Misawa, S. Optical tap array using distributed-index planar microlens 316
Okada, M., Koshiba, M., and Suzuki, M. see Koshiba, M.
Okazaki, H., Chida, K., and Nakahara, M. see Chida, K.
Okoshi, T., Oyamada, K., Nishimura, M., and Yokota, H. Side-tunnel fibre: an approach to polarisation-maintaining waveguiding scheme 824
Okoshi, T., and Kikuchi, K. see Kikuchi, K.
Okuda, H., Uematsu, Y., and Kinoshita, J. see Uematsu, Y.
Olesen, H., Jacobsen, G., Birkedahl, F., and Tromborg, B. see Jacobsen, G.
Oliner, A.A., and Lampariello, P. Novel leaky-wave antenna for millimetre waves based on groove guide 1105
Olsen, R.L., and Kheirallah, H.N. see Kheirallah, H.N.
Olshansky, R., Su, C.B., Schlafer, J., and Manning, J. see Su, C.B.
Onodera, N., Ito, H., and Inaba, H. High-peak-power picosecond optical pulse generation from highly RF-modulated InGaAsP DH diode laser 811
Ooishi, K., Koshiba, M., Miki, T., and Suzuki, M. see Koshiba, M.
Oomura, E., Namizaki, H., Hirano, R., Higuchi, H., Sakakibara, Y., and Susaki, W. see Namizaki, H.
Ota, C., Mimura, Y., Shinbori, O., and Kamibayashi, T. see Mimura, Y.
Ouchi, E., Awaka, J., Shimada, M., and Isobe, T. see Awaka, J.
Owen, B. PIN-GaAs FET optical receiver with a wide dynamic range 626
Oxley, C.H., Peake, A.H., and Bennett, R.H. Q-band (26-40 GHz) GaAs FET single-stage amplifier 260
Oyamada, K., Okoshi, T., Nishimura, M., and Yokota, H. see Okoshi, T.
Ozeki, T., Nakamura, M., and Tamura, T. see Nakamura, M.


## P


Paige, E.G.S., and Huang, F. see Huang, F.
Pal, J. System reduction by Cauer continued-fraction expansion about s=a and s=∞ alternately (Comment & Reply) 1009
Pal, K., and Singh, R. Inductorless current conveyor allpass filter using grounded capacitors 47 e240
Palmateer, S., Xin, S.H., Wood, C.E.C., DeSimone, D., and Eastman, L.F. see Xin, S.H.
Pandel, J., and Kleine, U. see Kleine, U.
Pantschew, B., Lillienhof, H.-J., and Schulz, D. see Lillienhof, H.-J.
Paoli, T.L., Burnham, R.D., Streifer, W., Scifres, D.R., Lindström, C., and Holonyak, N. see Burnham, R.D.
Paoloni, F.J., and Cheah, Y.C. see Cheah, Y.C.
Papachristou, C.A., Sarma, D., and Saifuddin, F.T. see Sarma, D.
Papadourakis, G.M., and Taylor F.J. Uniform analogue to digital conversion of a normal random process 666
Papageorgiou, C.D., and Boucouvalas, A.C. Propagation constants of cylindrical dielectric waveguides with arbitrary refractive-index profile using 'resonance' technique 786
Paraboni, A., and Barbaliscia, F. see Barbaliscia, F.
Parisi, G., Modone, E., and Roba, G. see Modone, E.
Park, D.C., Matthaei, G.L., Harris, C.E., Kim, Y.M., and Duvall, J.P. see Matthaei, G.L.
Parker, E.A., and Cahill, R. see Cahill, R.
Parker, E.A., and Hamdy, S.M.A. see Hamdy, S.M.A.
Parker, E.A., and Langley, R.J. see Langley, R.J.
Parker, G.J., Brotherton, A.D., Gill, A., and Shannon, J.M. see Brotherton, A.D.
Parsons, J.D., and Ibrahim, M.F. see Ibrahim, M.F.
Parthasarathy, R., and Jayasimha, K.N. System reduction by Cauer continued-fraction expansion about s=a and s=∞ alternately 376
Patangia, H.C., and Cartinhour, J. 2-phase circulating shift register for switched-capacitor N-path filters 444
Patel, D., Adams, A.R., Greene, P.D., and Henshall, G.D. Pressure dependence of threshold current in $Ga_xIn_{1-x}As_yP_{1-y}$ lasers 527
Patel, D., Adams, A.R., Greene, P.D., and Henshall, G.D. see Adams, A.R.
Patel, N.B., Hong, C.S., Kasemset, D., Kim, M.E., and Dapkus, P.D. see Hong, C.S.
Patel, N.B., Prince, F.C., and Mattos, T.J.S. see Prince, F.C.
Patzak, E. Spontaneous emission factor of narrow-stripe gain-guided diode lasers (Comment and Reply) 278
Patzak, E., Grosskopf, G., and Küller, L. see Grosskopf, G.
Paugam, J., Dumas, J.M., and le Mouellic, C. see Dumas, J.M.
Paugam, J., Henry, L., Lecrosnier, D., L'Haridon, H., Pelous, G., Richou, F., and Salvi, M. see Henry, L.
Paul, P.O., and Nair, K.G. Rotation of plane of polarisation of a beam of microwaves by corrugated reflection surfaces 338
Payne, D.B., McCartney, D.J., and Healey, P. Fusion splicing of a 31.6 km monomode optical fibre system 82
Payne, D.B., Stern, J.R., McCartney, D.J., Healey, P., Lindsey, P., Russ, D.M., and Stewart, J.H. see Stern, J.R.
Payne, D.N., Barlow, A.J., and Ramskov-Hansen, J.J. see Barlow, A.J.
Payne, D.N., Birch, R.D., and Varnham, M.P. see Birch, R.D.
Payne, D.N., Calligaro, R.B., Anderssen, R.S., and Ellem, B.A. see Calligaro, R.B.
Paz, M.B., De La Sen, M., Dormido, S., and Mellado, M. Compensation of discrete systems to variations in their parameters by changing sampling period 404
Peake, A.H., Oxley, C.H., and Bennett, R.H. see Oxley, C.H.
Peaker, A.R., Wu, R.H., and Allsopp, D. see Wu, R.H.
Pearsall, T.P. ZAP! Introducing the zero-bias avalanche photodiode 512
Pearson, A.D., Lin, C., Reed, W.A., Shang, Hen-Tai., and Glodis, P.F. see Lin, C.
Pearton, S.J., and Tavendale, A.J. Hydrogen passivation of deep donor centres in high-purity epitaxial GaAs 715
Pei, S.-C. Multidimensional bilinear transformations 1069
Pelgrom, M.J.M., and Esser, L.J.M. Bidirectional ripple clock scheme for serial-parallel-serial charge-coupled devices 289
Pelous, G., Henry, L., Lecrosnier, D., L'Haridon, H., Paugam, J., Richou, F., and Salvi, M. see Henry, L.
Penard, E., and Daniel, J.-P. Mutual coupling between microstrip antennas 605
Perez, F., and Obregon, J. Low-frequency limitations of ultrabroadband matched microwave amplifiers 31
Pernisek, M., Fauquembergue, R., and Constant, E. see Fauquembergue, R.
Petty, M.C. Hydrogen-induced DLTS signal in Pd/n-Si Schottky diodes 314
Petuchowski, S.J., Sigel, G.H., and Giallorenzi, T.G. Single-mode-fibre point and extended temperature sensors 814
Pfeiffer, Th., Heidemann, R., and Jäger, D. see Heidemann, R.
Philen, D.L., Lin, C., Tomita, A., Tynes, A.R., and Glodis, P.F. see Lin, C.
Piazza, F., Lucarini, G., Morandi, C., and Pierfederici, A. see Lucarini, G.
Pic, E., and Saguet, P. see Saguet, P.
Piccari, L., and Spano, P. New method for measuring ultrawide frequency response of optical detectors 116
Picton, P.D. High-speed processing of serial input logic data 148
Pierfederici, A., Lucarini, G., Piazza, F., and Morandi, C. see Lucarini, G.
Pierret, R.F., Martin, S.J., Gunshor, R.L., and Gorodetsky, G. see Martin, S.J.
Pierret, R.F., Weng, K.C.-K., Gunshor, R.L., and Tsubouchi, K. see Weng, K.C.-K.
Pietzsch, J. Astigmatism of semiconductor lasers with $\cosh^{-2}(x)$ profile of gain 1015
Piret, P., and Delsarte, P. see Delsarte, P.
Pisani, U., Bava, G.P., and Pozzolo, V. see Bava, G.P.
Pitcher, P.G., Hemment, P.L.F., and Davis, Q.V. Formation of shallow photodiodes by implantation of boron into mercury cadmium telluride 1090
Placais, B., and Migny, P. see Migny, P.
Plaskowski, A., Beck, C.M., Henry, R.M., and Lowe, B.T. see Beck, C.M.
Plastow, R., Harding, M., Griffith, I., Carter, A.C., and Goodfellow, R.C. Low-threshold current CW operation of multimode infil buried heterostructure 1.3 μm GaInAsP lasers 262
Platte, W. Small-reflection operation of substrate-edge excited optoelectronic mocrostrip transmission-type switches 977
Pleibel, W., Stolen, R.H., and Howard, R.E. see Stolen, R.H.
Pleshkov, G.M., Morozov, A.I., Kulakov, M.A., Dorozhkin, L.M., and Chayanov, B.A. see Morozov, A.I.
Poignant, H. Multiphonon absorption in infra-red fluoride glasses 199
Poignant, H., and Tran, D.C. Viscosity and optical measurement on fluoride glasses 1044
Poisson, M.A., Razeghi, M., Larivain, J.P., de Cremoux, B., Duchemin, J.P., and Voos, M. see Razeghi, M.
Pollard, C.J., and Morgan, R.A. see Morgan, R.A.
Poo, G.S. Power spectra of 6B4T and 3B2T codes 884
Pöpel, R. First measurement of a superconducting microstrip-line attenuation constant at 10 GHz 1103
Popovic, R.S., and Jankovic, N.D. see Jankovic, N.D.
Popovich, M.V., and Katić, O. Novel active-compensated variable-phase inverting integrator 1080
Pospíšil, J., and Dostál, T. see Dostál, T.
Pospíšl, J. Resistive multiport scattering matrix realisation using operational amplifiers 525
Powell, E., and Cochrane, P. see Cochrane, P.
Powell, M.J., Stroomer, M.V.C., Easton, B.C., and Chapman, J.A. see Stroomer, M.V.C.
Pozzolo, V., Bava, G.P., and Pisani, U. see Bava, G.P.
Prabhakar, A., Singh, S.P., and Bhattacharyya, A.B. see Singh, S.P.
Prat, L., and Castañer, L. Anlysis of efficiency limitations in high-low emitter back surface field silicon solar cells 789 e896
Preston, K.R. Simple spectral control technique for external cavity laser transmitters 1092
Preston K.R., Cameron, K.H., and Chidgey, P.J. see Cameron, K.H.
Prince, F.C., Mattos, T.J.S., and Patel, N.B. Optical gain measurements of 1.3 μm $In_{1-x}Ga_xAs_yP_{1-y}$ as function of injected current density 1054
Prince, F.C., Brosson, P., and Manganote, E.J.T. see Brosson, P.
Prior, C.J., Hall, P.S., and Ramsdale, P.A. see Hall, P.S.
Pun, E.Y.B., Wong, K.K., Andonovic, I., Laybourn, P.J.R., and De La Rue, R.M. Efficient waveguide Bragg-deflection grating on $LiNbO_3$ 740 e896


## Q


Qi-Jie, Z., and Sinha, N.K. Identification of continuous-time state-space model from samples of input-output data 50
Quisquater, J.-J., and Couvreur, C. Fast decipherment algorithm for RSA public-key cryptosystem 905


## R


Rabov, S., and Heinlein, W.E. Measurement of polarisation mode dispersion in elliptical-core single-mode fibres at 1.3μm 907
Raccah, P.M., Barnett, S.A., Ray, M.A., Lastras, A., Kramer, B., Greene, J.E., and Abels, L.L. see Barnett, S.A.
Rademeyer, R., Davari, B., and Das, P. Semiconductor surface studies with SAW oscillator structures 1065
Ragaie, H.F. Enhanced low temperature diffusion of electron-beam evaporated aluminium into $SiO_2$ thin films 74
Rahman Khan, A.K.M.M. Analytical and simulation study of simple rearrangeable multiexchange networks 1073
Rajala, R., Saniie, J., Luukkala, M., and Lehto, A. see Saniie, J.
Rajgopal, K., and Ramakrishna, K. see Ramakrishna, K.
Rakouth, H., Dieulesaint, E., and Royer, D. see Dieulesaint, E.
Ramachandran, V., Ananda Mohan, P.V., and Swamy, M.N.S. see Ananda Mohan, P.V.
Ramakrishna, K., and Rajgopal, K. Design of high-order filters with restricted component values 457
Ramaswamy, V., Alferness, R.C., and Divino, M. High efficiency single-mode fibre to Ti:$LiNbO_3$ waveguide coupling 30
Rammos, E. New wideband high-gain stripline planar array for 12 GHz satellite TV 252
Ramsdale, P.A., Hall, P.S., and Prior, C.J. see Hall, P.S.
Ramskov-Hansen, J.J., Barlow, A.J., and Payne, D.N. see Barlow, A.J.

Rashleigh, S.C., and Marrone, M.J. Polarisation-holding in a high-birefringence fibre 326
Rashvand, H.F. Implantation of microprocessors in trellis decoding of convolutional codes 121
Rathore, T.S. Application of complementary transformation to NIC compensated amplifiers 400
Rawson, E.G., and Bailey, M.D. Fused conically tapered fibre-optical power divider 447
Rawson, E.G., Scifres, D.R., Bailey, M.D., Norton, R.E., and Burnham, R.D. see Scifres, D.R.
Ray, M.A., Barnett, S.A., Lastras, A., Kramer, B., Greene, J.E., Raccah, P.M., and Abels, L.L. see Barnett, S.A.
Raynes, E.P., Bradshaw, M.J., and Hilsum, C. see Bradshaw, M.J.
Razeghi, M., Hirtz, P., Blondeau, R., Larivain, J.P., Noel, L., de Cremoux, B., and Duchemin, J.P. Room temperature CW operation of GaInAsP/InP double heterostructure diode lasers emitting at 1.5 μm grown by low pressure metalorganic chemical vapour deposition (LP-MO CVD) 132
Razeghi, M., Poisson, M.A., Larivain, J.P., de Cremoux, B., Duchemin, J.P., and Voos, M. TEG in LP-MO CVD $Ga_{0.47}In_{0.53}As$-InP superlattice 339
Reames, C.P., and Willson, A.N. Global convergence of Newton's method in the DC analysis of single-transistor networks 519
Reddy, D.R., Reddy, P.S., and Swamy, M.N.S. see Reddy, P.S.
Reddy, P.S., Reddy, D.R., and Swamy, M.N.S. Modification of shanks conjecture on stability of 2-D planar least-square inverse polynomials 456
Reed, I.S., and Kravitz, D.W. see Kravitz, D.W.
Reed, W.A., Lin, C., Pearson, A.D., Shang, Hen-Tai., and Glodis, P.F. see Lin, C.
Reeve, M.H., Kashyap, R., Hornung, S., Bandurek, G.R., and Nevett, J.E. see Kashyap, R.
Reeves, G.K., and Harrison, H.B. Contact resistance of polysilicon silicon interconnections 1083
Regenbogen, L.K., Niekolaas, G., and Den Dulk, R.C. see Niekolaas, G.
Regnault, J.C., Elliott, C.R., and Wakefield, B. see Elliott, C.R.
Regreny, A., Favennec, P.N., Henry, L., and Salvi, M. see Favennec, P.N.
Reinhart, F.K., Tsang, W.T., and Ditzenberger, J.A. see Tsang, W.T.
Renard, A., Auld, B.A., and Henaff, J. see Auld, B.A.
Rentschler, J.A., Cheng, C.L., Coldren, L.A., Miller, B.I., and Shen, C.C. see Cheng, C.L.
Rentschler, J.A., Coldren, L.A., Furuya, K., and Miller, B.I. see Coldren, L.A.
Rentschler, J.A., Ebeling, K.J., Coldren, L.A., and Miller, B.I. see Ebeling, K.J.
Reynolds, L.D., Ayasli, Y., Vorhaus, J.L., and Hanes, L. see Ayasli, Y.
Ribeiro, C.A., and de Prince, F.C. Optoelectronic digital/analogue convertor-emitter 1021
Richman, G.D. Behaviour of spectrum-conserving RBQPSK digital radio during multipath propagation 467
Richou, F., Henry, L., Lecrosnier, D., L'Haridon, H., Paugam, J., Pelous, G., and Salvi, M. see Henry, L.
Riou, J., Bouadma, N., and Bouley, J.C. see Bouadma, N.
Roba, G., Modone, E., and Parisi, G. see Modone, E.
Robertson, A.J., Leach, J.S., Cannell, G.J., and Gurton, P. see Leach, J.S.
Robson, P.N., Claxton, P.A., Shirafuji, J., and Houston, P.A. see Claxton, P.A.
Rochette, J., Massies, J., Delescluse, P., Etienne, P., Chevrier, J., and Linh, N.T. see Massies, J.
Rode, M., and Weidel, E. Compact and rugged all-fibre coupler for wavelength division multiplexing 989
Rogers, D.V., and Allnutt, J.E. see Allnutt, J.E.
Rosencher, E., and Bois, D. Comparison of interface state density in MIS structure deduced from DLTS and Terman measurements 545
Royer, D., Dieulesaint, E., and Rakouth, H. see Dieulesaint, E.
Rüdiger, J., Haydl, W.H., and Bosch, R. see Haydl, W.H.
Rush, J.D., Ainslie, B.J., Beales, K.J., Cooper, D.M., and Day, C.R. see Ainslie, B.J.
Russ, D.M., Stern, J.R., Payne, D.B., McCartney, D.J., Healey, P., Lindsey, P., and Stewart, J.H. see Stern, J.R.
Rutkowski, J., and Macura, A. see Macura, A.

## S

Saguet, P., and Pic, E. Utilisation d'un nouveau type de noeud dans la methode TLM en 3 dimensions 478
Saifuddin, F.T., Sarma, D., and Papachristou, C.A. see Sarma, D.
Saillard, J. Anisotropic linear target recognition from RCS diagram 181
Saillard, J. RCS diagram records processing in Chebyshev space 729 e896
Saito, S., Yamamoto, Y., and Kimura, T. Optical FSK signal detection in a heterodyne system using semiconductor lasers 470
Saito, S., Yamamoto, Y., and Kimura, T. Semiconductor laser FSK modulation and optical direct discrimination detection 468
Saitoh, T., Mikami, O., and Nakagome, H. New chemical etching solution for InP and GaInAsP gratings 408
Saitoh, T., Mikami, O., and Nakagome, H. see Mikami, O.
Sakaguchi, S, Chida, K., Wagatsuma, M., and Kimura, T. see Chida, K.
Sakaguchi, S., Kawachi, M., Yasu, M., Tomaru, S., and Edahiro, T. see Kawachi, M.
Sakaguchi, S., Yamamoto, S., Utaka, K., Akiba, S., Sakai, K., Matsushima, Y., and Seki, N. see Yamamoto, S.
Sakai, K., Akiba, S., Utaka, K., and Matsushima, Y. see Akiba, S.
Sakai, K., Matshushima, Y., Akiba, S., Kushiro, Y., Noda, Y., and Utaka, K. see Matshushima, Y.
Sakai, K., Yamamoto, S., Utaka, K., Akiba, S., Matsushima, Y., Sakaguchi, S., and Seki, N. see Yamamoto, S.
Sakai, S., Aoki, T., and Umeno, M. Dual wavelength InGaAsP/InP TJS lasers 18
Sakai, S., Aoki, T., and Umeno, M. InGaAsP/InP dual wavelength lasers 17
Sakai, S., Aoki, T., and Umeno, M. InGaAsP/InP LEDs integrated with monitoring detector 157
Sakai, S., Naitoh, M., and Umeno, M. see Naitoh, M.
Sakai, T., Tsuyuki, S., Suto, K., and Kamoto, T. see Tsuyuki, S.
Sakakibara, Y., Namizaki, H., Hirano, R., Higuchi, H., Oomura, E., and Susaki, W. see Namizaki, H.
Sakata, I., and Hayashi, Y. Changes in photovoltaic and dark electrical properties of hydrogenerated amorphous silicon diodes induced by forward bias carrier injection 1075
Sakurai, T., Wada, O., Yamakoshi, S., Fujii, T., and Hiyamizu, S. see Wada, O.
Salemink, H.W.M., and Biesterbos, J.W.M. see Biesterbos, J.W.M.
Salerno, M., Giannini, F., and Sorrentino, R. see Giannini, F.
Salmer, G., Allamando, E., Bouhess, M., and Constant, E. see Allamando, E.
Salvi, M., Favennec, P.N., Deveaud, B., Martinez, A., and Armand, C. see Favennec, P.N.
Salvi, M., Favennec, P.N., Henry, L., and Regreny, A. see Favennec, P.N.
Salvi, M., Henry, L., Lecrosnier, D., L'Haridon, H., Paugam, J., Pelous, G., and Richou, F. see Henry, L.
Sammut, R.A. Momentary look at noncircular monomode fibres 221
Sammut, R.A., Chu, P.L., and Chen, P.Y.P. see Chu, P.L.
Saniie, J., Luukkala, M., Lehto, A., and Rajala, R. Thermal wave imaging through radio frequency induction heating 651
Sansonetti, P. Modal dispersion in single-mode fibres: simple approximation issued from mode spot size spectral behaviour 647
Sansonetti, P. Prediction of modal dispersion in single-mode fibres from spectral behaviour of mode spot size 136
Sansonetti, P., Alard, F., Vassallo, C., Kammerer, P., Francois, P.L., Monerie, M., Gabriagues, J.M., and Dupont, P. Evidence of fundamental mode cutoff in depressed inner cladding single-mode fibres 989
Sansonetti, P., Alard, F., Jeunhomme, L., Monerie, M., and Vassallo, C. see Alard, F.
Santiago, J., Smy, P.R., and Clements, R.M. Breakdown voltage of a plasma-filled gap 165
Sarje, A.K. Asummability testing 938
Sarma, D., Papachristou, C.A., and Saifuddin, F.T. Fault coverage of pattern-sensitive fault-detection algorithms for semiconductor memories 950
Saruwatari, M., and Sugie, T. see Sugie, T.
Sasaki, A., Takeda, Y., and Kamei, H. see Takeda, Y.
Sasaki, Y., Shibata, N., and Noda, J. Splicing of single-polarisation fibres by an optical short-pulse method 997
Sato, M., Koshiba, M., and Suzuki, M. see Koshiba, M.
Sato, T., and Suzuki, Y. see Suzuki, Y.
Sato, T., Takahashi, H., and Sugimoto, I. see Takahashi, H.
Satoh, S., Susa, K., Matsuyama, I., and Suganuma, T. see Susa, K.
Sawada, T., and Hasegawa, H. InP high mobility enhancement MISFETs using anodically grown double-layer gate insulator 742
Sawada, T., Ishii, K., Ohno, H., and Hasegawa, H. see Ishii, K.
Saxena, A.K. $Ga_{1-x}Al_xAs$ material for high-sensitivity pressure sensors 644
Saxena, R.R., Maloney, T.J., and Chai, Y.G. see Maloney, T.J.
Schach, S.R. Algorithm for finding the common spanning trees of two graphs (Comment & Reply) 988
Schiffner, G., Schöner, G., Klement, E., and Douklias, N. see Schöner, G.
Schlafer, J., Su, C.B., Manning, J., and Olshansky, R. see Su, C.B.
Schmidt auf Altenstadt, W., and Heinz, C. see Heinz, C.
Schmidt, L.-P., and Meinel, H. Broadband millimetre-wave PIN-diode attenuator with double-ridge waveguide flanges 839
Schmidt, L.-P., and Callsen, H. see Callsen, H.
Schmitt-Landsiedel, S., and Dorda, G. Spatial distribution of hot electrons as a physical limit to MOS transistor performance 1041
Schmöller, G., and Ohm, G. see Ohm, G.
Schneider, M.V., Cho, A.Y., Kollberg, E., Zirath, H., and Snell, W.W. see Cho, A.Y.
Schöner, G., Klement, E., Schiffner, G., and Douklias, N. Novel method for making single-mode optical fibre directional couplers 566
Schrank P.F., and Dyott, R.B. see Dyott, R.B.
Schulz, D., Lillienhof, H.-J., and Pantschew, B. see Lillienhof, H.-J.
Schüppert, B. Conversion loss of an MIC balanced mixer: calculation and measurements 823
Scifres, D.R., Bailey, M.D., Norton, R.E., Burnham, R.D., and Rawson, E.G. Diode laser array excited star coupler suitable for Fibernet II 1028
Scifres, D.R., Burnham, R.D., and Streifer, W. Lateral grating array high power CW visible semiconductor laser 549
Scifres, D.R., Burnham, R.D., and Streifer, W. see Burnham, R.D.
Scifres, D.R., Burnham, R.D., Streifer, W., Lindström, C., Paoli, T.L., and Holonyak, N. see Burnham, R.D.
Scifres, D.R., Halido, D., and Lindström, C. see Halido, D.
Scifres, D.R., Lindström, C., Halido, D., and Burnham, R.D. see Lindström, C.
Scott, H.F., Al-Attar, A., and Daniels, D.J. see Al-Attar, A.
Scovell, P.D., Hemment, P.L.F., and Maydell-Ondrusz, E. see Hemment, P.L.F.
See, C.W., Wickramasinghe, H.K., and Ameri, S. see Wickramasinghe, H.K.
Seeds, A.J., and Forrest, J.R. Reduction of FM noise in impatt oscillators by optical illumination e106
Segalen, A., and Demoment, G. Constrained LMS adaptive algorithm 226
Seikai, S., Kato, Y., Kitayama, K., and Uchida, N. see Kato, Y.
Seikai, S., Shibata, N., Uchida, N., and Tateda, M. see Shibata, N.
Seki, M., Kobayashi, K., Odagiri, Y., Shikada, M., Tanigawa, T., and Ishikawa, R. 20-channel micro-optic grating demultiplexer for 1.1-1.6 μm band using a small focusing parameter graded-index rod lens 257
Seki, M., Mito, I., Kitamura, M., Kaede, K., Odagiri, Y., Sugimoto, M., and Kobayashi, K. see Mito, I.
Seki, N., Yamamoto, S., Utaka, K., Akiba, S., Sakai, K., Matsushima, Y., and Sakaguchi, S. see Yamamoto, S.
Selders, J., Vescan, L., Kräutle, H., Kütt, W., and Beneking, H. see Vescan, L.
Selga, J.M., Garcia-Lopez, J.A., and Ferrandiz, J.M. see Garcia-Lopez, J.A.
Selviah, D.R., Warne, D.H., and Morgan, D.P. Spatial uniformity measurement of SAW convolvers 837
Selviah, D.R., Morgan, D.P., and Warne, D.H. see Morgan, D.P.
Senani, R. Novel lossless synthetic floating inductor employing a grounded capacitor 413 e584
Sewell, J.I., and Lau, C. see Lau, C.
Shamasundara, H.N., Kudsia, C.M., and Swamy, M.N.S. Sensitivity comparison of symmetric and asymmetric dual-mode bandpass filters 552
Shang, Hen-Tai., Lin, C., Reed, W.A., Pearson, A.D., and Glodis, P.F. see Lin, C.
Shannon, J.M., Brotherton, A.D., Gill, A., and Parker, G.J. see Brotherton, A.D.
Sharma, A.B., Halme, S.J., Hubach, E.J.R., and Lähteenoja, M. Effect of source near- and far-field variations on the accuracy of multimode fibre attenuation measurements 49
Sharma, A.B., Hubach, E.J.R., Lahteenoja, M., and Halme, S.J. Technique for minimising effect of detector inhomogeneity on fibre attenuation measurements 56
Sharma, A.B., Lähteenoja, M., Halme, S.J., and Hubach, E.J.R. Technique for reducing spatial and wavelength variations of launch spot in fibre attenuation measurements 244
Shaw, H.J., Bowers, J.E., and Newton, S.A. see Bowers, J.E.
Shaw. H.J., Bowers, J.E., Newton, S.A., and Sorin, W.V. see Bowers, J.E.
Shen, C.C., Cheng, C.L., Coldren, L.A., Miller, B.I., and Rentschler, J.A. see Cheng, C.L.
Shepherd, P.R., Faulkner, N., Vilar, E., and Bradsell, P. Relation between power spectrum and phase spectrum of oscillators 614

Shibata, N., Uchida, N., Tateda, M., and Seikai, S. Normalised frequency dependence of polarisation mode dispersion due to thermal-stress-induced birefringence in an elliptical core single-mode fibre 563

Shibata, N., Sasaki, Y., and Noda, J. see Sasaki, Y.

Shibata, S., Jinguji, K., Horiguchi, M., Kanamori, T., Mitachi, S., and Manabe, T. see Jinguji, K.

Shibukawa, A., Yamamoto, A., Uemura, C., and Yamaguchi, M. see Yamamoto, A.

Shigyo, N., Konaka, M., and Dang, R.L.M. Three-dimensional simulation of inverse narrow-channel effect 274

Shih, Y.C., and Itoh, T. Analysis of conductor-backed coplanar waveguide 538

Shih, Y.C., and Itoh, T. Analysis of printed transmission lines for monolithic integrated circuits 585

Shikada, M., Seki, M., Kobayashi, K., Odagiri, Y., Tanigawa, T., and Ishikawa, R. see Seki, M.

Shim, Y.S., and Kim, J.K. Graphic image coding based on a pattern-dependent runlength model 476

Shimada, M., Awaka, J., Isobe, T., and Ouchi, E. see Awaka, J.

Shinbori, O., Mimura, Y., Kamibayashi, T., and Ota, C. see Mimura, Y.

Shirafuji, J., Amano, M., Inoue, M., and Inuishi, Y. Characteristics of anodic native oxide MIS diodes of $In_{0.53}Ga_{0.47}As$ 653

Shirafuji, J., Claxton, P.A., Houston, P.A., and Robson, P.N. see Claxton, P.A.

Shirai, T., Yamazaki, S., Yasuda, K., Mikawa, T., Nakajima, K., and Kaneda, T. 1.0-1.6 μm planar avalanche photodiode by LPE grown InP/InGaAs/InP DH structure 575

Shtrikman, H., and Tamari, N. see Tamari, N.

Shur, M.S. Low field mobility, effective saturation velocity and performance of submicron GaAs MESFETs 909

Shur, M.S., Drummond, T.J., Su, S.L., Lyons, W.G., Fischer, R., Kopp, W., Morkoc, H., and Lee, K. see Drummond, T.J.

Shuto, Y., Wagatsuma, M., Kimura, T., and Yamakawa, S. see Wagatsuma, M.

Sibbett, W., Chen, J., and Vukusic, J.I. see Chen, J.

Sibley, M.J.N., and Unwin, R.T. Transmipedance optical preamplifier having a common-collector front end 985

Siegenthaler, T., and Wah, P.K.S. see Wah, P.K.S.

Sigel, G.H., Petuchowski, S.J., and Giallorenzi, T.G. see Petuchowski, S.J.

Sigel, G.H., Tran, D.C., and Fisher, C.F. see Tran, D.C.

Sigel, G.H., Tran, D.C., Levin, K.H., and Ginther, R.J. see Tran, D.C.

Simmons, T.J., and Smith, D.C. Direct measurement of FM noise in 80 GHz solid-state oscillators 308

Simms, P.D., and Craig, A.D. see Craig, A.D.

Simon, J.C. Polarisation characteristics of a travelling-wave-type semiconductor laser amplifier 438

Singer, K., Wood C.E.C., Eastman, L.F., Board, K., and Malik, R. see Wood C.E.C.

Singh, R., and Pal, K. see Pal, K.

Singh, S.P., Prabhakar, A., and Bhattacharyya, A.B. C-2C ladder voltage dividers for application in all-MOS A/D convertors 537

Singh, V., and Ashoor, N. see Ashoor, N.

Sinha, N.K., and Qi-Jie, Z. see Qi-Jie, Z.

Siracusa, M., Feng, M., Eu, V.K., Watkins, E., Kimura, H., and Winston, H. see Feng, M.

Siracusa, M., Feng, M., Kanbar, H., and Eu, V.K. see Feng, M.

Skalický, P. Direct coupling between two dielectric resonators 332

Smith, D., and Auchterlonie, L.J. Observation of crosspolar effects using a mocrowave open resonator 1031

Smith, D.C., and Simmons, T.J. see Simmons, T.J.

Smith, D.R., Hooper, R.C., Smyth, P.P., and Wake, D. Experimental comparison of a germanium avalanche photodicde and InGaAs PINFET receiver for longer wavelength optical communication systems 453

Smith, D.R., and Brain, M.C. see Brain, M.C.

Smith D.R., and Healey, P. see Healey, P.

Smith, D.W., and Malyon, D.J. Experimental 1.51 μm monomode fibre link containing an injection locked repeater 43

Smith, D.W., Hodgkinson, T.G., and Wyatt, R. see Hodgkinson, T.G.

Smith, D.W., Wyatt, R., and Cameron, K.H. see Wyatt, R.

Smith, G.J., Milne, W.I., and Blackborow, P. Large-area low-frequency discharge-produced a-Si:H 211

Smith, I.R., and Wickramasinghe, H.K. Differential phase contrast in the acoustic microscope 92

Smith, I.R., and Wickramasinghe, H.K. SAW attenuation measurement in the acoustic microscope 955

Smy, P.R., Santiago, J., and Clements, R.M. see Santiago, J.

Smyth, P.P., Smith, D.R., Hooper, R.C., and Wake, D. see Smith, D.R.

Snell, W.W., Cho, A.Y., Kollberg, E., Zirath, H., and Schneider, M.V. see Cho, A.Y.

Soda, H., Motegi, Y., and Iga, K. see Motegi, Y.

Soliman, H.M., and Fleming, R.J. Optimal scalar Lyapunov functions for decentralised stabilisation of interconnected systems 993

Soluch, W. New technique for wavefront distortion compensation of apodised interdigital transducers 1002

Soluch, W., Bailey, D.S., Josse, F., Lee, D.L., Andle, J., Vetelino, J.F., and Chai, B.H.T. see Bailey, D.S.

Solymar, L., and Syms, R.R.A. see Syms, R.R.A.

Sorin, W.V., Bowers, J.E., Newton, S.A., and Shaw, H.J. see Bowers, J.E.

Sorrentino, R., and Leuzzi, G. Full-wave analysis of integrated transmission lines on layered lossy media 607

Sorrentino, R., Giannini, F., and Salerno, M. see Giannini, F.

Souza, J.R., and Talboys, E.C. S-parameter characterisation of a transition from a 50 Ω coaxial line to a non-50 Ω microstrip line 348

Spano, P., and Piccari, L. see Piccari, L.

Sridhar, N., and Srivastava, G.P. Theoretical analysis of hybrid modes in a dual-depth corrugated waveguide feed 793 e896

Srivastava, G.P., and Sridhar, N. see Sridhar, N.

Stancil, D.D. Microwave diplexer using magnetostatic surface and backward volume waves 269

Stanier, B.J., and Ward, J.S. see Ward, J.S.

Stanik, K., and Jirmann, J. see Jirmann, J.

Stearns, R.C., Asawa, C.K., Yao, S.K., Mota, N.L., and Downs, J.W. see Asawa, C.K.

Stemp, B.E., Keen, K.M., and Grime, R.R. see Keen, K.M.

Stephens, K.G., Maydell-Ondrusz, E.A., Hemment, P.L.F., and Moffat, S. see Maydell-Ondrusz, E.A.

Stephenson, F.W., and Moon, R. see Moon, R.

Stern, J.R., Payne, D.B., McCartney, D.J., Healey, P., Lindsey, P., Russ, D.M., and Stewart, J.H. Field installation of a 31.5 km monomode optical fibre system operated at 140 Mbit/s and 650 Mbit/s 631

Stevenson, J.K., and Haigh, D.G. Special cases of Fliege's complementary transformation for active RC networks 514

Stewart, J.H., Stern, J.R., Payne, D.B., McCartney, D.J., Healey, P., Lindsey, P., and Russ, D.M. see Stern, J.R.

Stokes, R.B., Yen, K.H., Lau, K.F., Kong, A., and Kagiwada, R.S. see Yen, K.H.

Stolen, R.H., Howard, R.E., and Pleibel, W. Substrate-tube lithography for optical fibres 764

Stone, J., and Cohen, L.G. Minimum-dispersion spectra of single-mode fibres measured with subpicosecond resolution by white-light crosscorrelation 716

Stone, J., and Lemaire, P.J. OH reduction in preforms by isotope exchange (Comment) 185

Stone, J., and Lemaire, P.J. Reduction of loss due to OH in optical fibres by a two-step OH→ OD exchange process 78

Stone, J., and Cohen, L.G. see Cohen, L.G.

Streifer, W., Burnham, R.D., and Scifres, D.R. see Burnham, R.D.

Streifer, W., Burnham, R.D., Scifres, D.R., Lindström, C., Paoli, T.L., and Holonyak, N. see Burnham, R.D.

Streifer, W., Scifres, D.R., and Burnham, R.D. see Scifres, D.R.

Stroomer, M.V.C., Powell, M.J., Easton, B.C., and Chapman, J.A. Amorphous-silicon TFT array for LCD addressing 858

Stumper, U. New nondirectional waveguide multicoupler as part of a simple microwave six-port reflectometer 757

Su, C.B., Schlafer, J., Manning, J., and Olshansky, R. Measurement of radiative and Auger recombination rates in p-type InGaAsP diode lasers 595

Su, C.B., Schlafer, J., Manning, J., and Olshansky, R. Measurement of radiative recombination coefficient and carrier leakage in 1.3μm InGaAsP lasers with lightly doped active layers 1108

Su, L.M., and Beneking, H. see Beneking, H.

Su, S.L., Fischer, R., Drummond, T.J., Lyons, W.G., Thorne, R.E., Kopp, W., and Morkoc, H. Modulation-doped (Al, Ga)As/GaAs FETs with high transconductance and electron velocity 794

Su, S.L., Drummond, T.J., Lyons, W.G., Fischer, R., Kopp, W., Morkoc, H., Lee, K., and Shur, M.S. see Drummond, T.J.

Suda, H., Sudo, S., and Nakahara, M. Deposition mechanism of fine glass particles and high-rate production of fibre preforms in the VAD process 779

Sudo, S., Suda, H., and Nakahara, M. see Suda, H.

Suematsu, Y., Abe, Y., Kishino, K., Tanbun-Ek, T., Arai, S., Koyama, F., Matsumoto, K., and Watanabe, T. see Abe, Y.

Suemune, I., Kohno, M., and Yamanishi, M. Room-temperature operation of a transverse-distributed-feedback cavity laser 745

Sueta, T., Izutsu, M., and Enokihara, A. see Izutsu, M.

Suganuma, T., Susa, K., Matsuyama, I., and Satoh, S. see Susa, K.

Sugie, T., and Saruwatari, M. Nonreciprocal circuit for laser-diode-to-single-mode-fibre coupling employing a YIG sphere 1026

Sugimoto, I., Takahashi, H., and Sato, T. see Takahashi, H.

Sugimoto, M., Mito, I., Kitamura, M., Kaede, K., Odagiri, Y., Seki, M., and Kobayashi, K. see Mito, I.

Sumida, M., and Takemoto, K. Lens aberration effect on a laser-diode-to-single-mode-fibre coupler 586

Sundara Murthy, K.M., and Cattermole, K.W. Power spectra of digital FM signals with complex signalling pulse shapes 848

Susa, K., Matsuyama, I., Satoh, S., and Suganuma, T. New optical fibre fabrication method 499

Susaki, W., Namizaki, H., Hirano, R., Higuchi, H., Oomura, E., and Sakakibara, Y. see Namizaki, H.

Suto, K., Tsuyuki, S., Kamoto, T., and Sakai, T. see Tsuyuki, S.

Suzuki, F., Tomizawa, K., Awano, Y., and Hashizume, N. see Tomizawa, K.

Suzuki, H., Yamao, Y., and Kikuchi, H. Single-chip CMOS MSK coherent demodulator 581

Suzuki, M., and Koshiba, M. see Koshiba, M.

Suzuki, M., Koshiba, M., and Hayata, K. see Koshiba, M.

Suzuki, M., Koshiba, M., and Ishii, H. see Koshiba, M.

Suzuki, M., Koshiba, M., and Okada, M. see Koshiba, M.

Suzuki, M., Koshiba, M., Ooishi, K., and Miki, T. see Koshiba, M.

Suzuki, M., Koshiba, M., and Sato, M. see Koshiba, M.

Suzuki, Y., and Sato, T. 7 Gbit/s coherent pulse generation in an actively mode-locked GaAlAs diode laser 821

Suzuki, Y., Itaya, Y., Matsuoka, T., Nakano, Y., Kuroiwa, K., and Ikegami, T. see Itaya, Y.

Suzuki, Y., Iwashita, K., Nakagawa, K., and Nakano, Y. see Iwashita, K.

Suzuki, Y., Matsuoka, T., Nagai, H., Itaya, Y., Noguchi, Y., and Ikegami, T. see Matsuoka, T.

Suzuki, Y., Matsuoka, T., Noguchi, Y., and Nagai, H. see Matsuoka, T.

Suzuki, Y., Nakano, Y., Takehei, K., Noguchi, Y., and Nagai, H. see Nakano, Y.

Suzuki, Y., Naqai, H., and Noquchi, Y. see Naqai, H.

Swamy, M.N.S., Ananda Mohan, P.V., and Ramachandran, V. see Ananda Mohan, P.V.

Swamy, M.N.S., Reddy, P.S., and Reddy, D.R. see Reddy, P.S.

Swamy, M.N.S., Shamasundara, H.N., and Kudsia, C.M. see Shamasundara, H.N.

Swanson, J.G., and Lee, W.S. see Lee, W.S.

Swinehart, R.M., Donalds, L.J., French, W.G., Mitchell, W.C., and Wei, T. see Donalds, L.J.

Syms, R.R.A., and Solymar, L. Determination of material characteristics of bleached photographic emulsions used in volume phase holography 249

Syrbu, A.V., Benson, T.M., Chand, N., and Houston, P.A. see Benson, T.M.

Syrbu, A.V., Chand, N., and Houston, P.A. see Chand, N.


## T


Tada, K., Kuhara, Y., Hamasaki, Y., Kawakami, A., Murakami, Y., Tatsumi, M., Takimoto, H., and Mitsui, T. see Kuhara, Y.

Tahim, R.S., Hayashibara, G.M., and Chang, K. W-band broadband integrated circuit mixers 471

Takahashi, H., Sugimoto, I., and Sato, T. Germanium-oxide glass optical fibre prepared by VAD method 398

Takahashi, M., Yoshimi, M., Kawabuchi, K., Takigawa, T., and Kato, Y. see Yoshimi, M.

Takeda, Y., Kamei, H., and Sasaki, A. Mobility calculation of two-dimensional electron gas in GaAs/AlGaAs heterostructure at 4.2 K 309

Takehei, K., Nakano, Y., Noguchi, Y., Suzuki, Y., and Nagai, H. see Nakano, Y.

Takemoto, K., and Sumida, M. see Sumida, M.

Takigawa, T., Yoshimi, M., Kawabuchi, K., Takahashi, M., and Kato, Y. see Yoshimi, M.

Takimoto, H., Kuhara, Y., Hamasaki, Y., Kawakami, A., Murakami, Y., Tatsumi, M., Tada, K., and Mitsui, T. see Kuhara, Y.

Takusagawa, M., Hanamitsu, K., Ohsaka, S., Yoshida, K., Nishi, H., and Hori, K. see Hanamitsu, K.

Talboys, E.C., and Souza, J.R. see Souza, J.R.

Tamari, N., and Shtrikman, H. High-$T_0$ low-threshold crescent InGaAsP MESA-substrate buried-heterojunction lasers 177

Tamura, T., Nakamura, M., and Ozeki, T. see Nakamura, M.

Tan, E.C. Transfer functions of wave-digital filters 722
Tan, E.C. Variable lowpass wave-digital filters 324
Tanaka, S., Kawanishi, H., Hiraoka, M., Yoshioka, K., Nishio, K., and Nakagomi, T. see Kawanishi, H.
Tanbun-Ek, T., Abe, Y., Kishino, K., Arai, S., Koyama, F., Matsumoto, K., Watanabe, T., and Suematsu, Y. see Abe, Y.
Tanifuji, T., Kato, Y., Tokuda, M., and Uchida, N. see Kato, Y.
Tanigawa, T., Seki, M., Kobayashi, K., Odagiri, Y., Shikada, M., and Ishikawa, R. see Seki, M.
Tateda, M., Shibata, N., Uchida, N., and Seikai, S. see Shibata, N.
Tatekura, K., Yamamoto, H., and Ejiri, Y. Strain of optical fibres of an optical submarine cable on the sea bed 414
Tatekura, K., Yamamouchi, H., and Nunokawa, M. Novel core alignment method for low-loss splicing of single-mode fibres utilising UV-excited fluorescence of Ge-doped silica core 712
Tatsumi, M., Kuhara, Y., Hamasaki, Y., Kawakami, A., Murakami, Y., Takimoto, H., Tada, K., and Mitsui, T. see Kuhara, Y.
Taub, D.M. Worst-case arbitration time in S-100-type computer bus systems 833
Tavendale, A.J., and Pearton, S.J. see Pearton, S.J.
Tawfik, M.S., Terrier, C., Caillon, C., and Borel, J. Exact design of switched-capacitor bandpass ladder filters 1101
Taylor F.J., and Papadourakis, G.M. see Papadourakis, G.M.
Taylor, H.F., Goldberg, L., and Weller, J.F. see Goldberg, L.
Taylor, J. Exact design of elliptic switched-capacitor filters by synthesis 807
Taylor, W.K., and Lavie, D. see Lavie, D.
Tell, R., Alping, A., Andersson, T., and Eng, S.T. see Alping, A.
Tell, R., Bentland, B., Bergman, L.A., and Eng, S.T. see Bentland, B.
Temkin, H., Chin, A.K., and Dutt, B.V. Schottky barrier restricted GaAlAs laser 701
Temkin, H., Logan, R.A., Henry, C.H., and van der Ziel, J.P. see Logan, R.A.
Temkin, H., Logan, R.A., van der Ziel, J.P., and Henry, C.H. see Logan, R.A.
Terrier, C., Tawfik, M.S., Caillon, C., and Borel, J. see Tawfik, M.S.
Therapos, C.P. Direct method of reducing order of linear systems using Koenig's theorem 826
Therapos, C.P. Suboptimal control with incomplete state feedback 996
Therapos, C.P., and Diamessis, J.E. Numerical inversion of a class of Laplace transforms 620
Thorn, R., Browne, M.A., Deloughry, R.J., and Green, R.G. see Browne, M.A.
Thorne, R.E., Su, S.L., Fischer, R., Drummond, T.J., Lyons, W.G., Kopp, W., and Morkoc, H. see Su, S.L.
Tiffon, J., and Maupfouma, F. see Maupfouma, F.
Tits, D., and Daly, P. see Daly, P.
Tjhung, T.T., and Ingram, D.G.W. see Ingram, D.G.W.
Toba, H., Kawachi, M., and Edahiro, T. see Kawachi, M.
Todokoro, Y. Novel triple-layer resist system 543
Tokuda, M., Kato, Y., Tanifuji, T., and Uchida, N. see Kato, Y.
Tolutis, R., and Laurinavičius, L. see Laurinavičius, L.
Tomaru, S., Kawachi, M., Yasu, M., Edahiro, T., and Sakaguchi, S. see Kawachi, M.
Tomita, A., Lin, C., Tynes, A.R., Glodis, P.F., and Philen, D.L. see Lin, C.
Tomizawa, K., Awano, Y., Hashizume, N., and Suzuki, F. Monte Carlo simulation of GaAs submicron $n^-$-n-$n^-$ diode with GaAlAs heterojunction cathode 1067
Tomizawa, K., Awano, Y., Hashizume, N., and Kawashima, M. see Awano, Y.
Tourneur, J., Bendali, A., and Clair, D. see Bendali, A.
Tow, J., Fleischer, P.E., and Ganesan, A. see Fleischer, P.E.
Tran, D.C., Fisher, C.F., and Sigel, G.H. Fluoride glass preforms prepared by a rotational casting process 657
Tran, D.C., Sigel, G.H., Levin, K.H., and Ginther, R.J. Rayleigh scattering in $ZrF_4$-based glasses 1046
Tran, D.C., and Koo, K.P. see Koo, K.P.
Tran, D.C., and Poignant, H. see Poignant, H.
Tromborg, B., Jacobsen, G., Olesen, H., and Birkedahl, F. see Jacobsen, G.
Tsang, W.T., and Logan, R.A. (AlGa)As strip buried-heterostructure lasers prepared by hybrid crystal growth 397
Tsang, W.T., Logan, R.A., and Ditzenberger, J.A. Stripe-geometry laser with in-situ ohmic contact and self-aligned native surface oxide mask for current isolation prepared by molecular beam epitaxy 123
Tsang, W.T., Logan, R.A., and Ditzenberger, J.A. Ultra-low threshold, graded-index waveguide, separate confinement, CW buried-heterostructure lasers 845
Tsang, W.T., Reinhart, F.K., and Ditzenberger, J.A. Molecular-beam epitaxially grown 1.3 μm GaInAsP/InP double-heterostructure lasers 785
Tsang, W.T., Capasso, F., and Logan, R.A. see Capasso, F.
Tsironis, C., Kermarrec, C., Faguet, J., and Harrop, P. Stable monolithic GaAs FET oscillator 345
Tsividis, Y., and Fang, S.C. Simple method for obtaining the equations of switched-capacitor circuits 728
Tsividis, Y., and Banu, M. see Banu, M.
Tsividis, Y., and Ye, R. see Ye, R.
Tsoi, A.C. Adaptive prediction of an ARMA lattice 222
Tsubouchi, K., Weng, K.C.-K., Gunshor, R.L., and Pierret, R.F. see Weng, K.C.-K.
Tsuyuki, S., Suto, K., Kamoto, T., and Sakai, T. Monolithic integrated amplifiers for 400 Mbit/s optical repeater 340
Tuladhar, K.K. Active-phase-compensated biquadratic highpass filter 184
Tung, P.N., Delagebeaudeuf, D., Laviron, M., Delescluse, P., Chaplart, J., and Linh, N.T. High-speed two-dimensional electron-Gas FET logic 109
Tung, P.N., Delescluse, P., Delagebeaudeuf, D., Laviron, M., Chaplart, J., and Linh, N.T. High-speed low-power DCFL using planar two-dimensional electron GAS FET technology 517
Tung, Pham.N., Delagebeaudeuf, D., Laviron, M., Delescluse, P., Chaplart, J., and Linh, N.T. see Delagebeaudeuf, D.
Turchiano, B., and Maione, B. see Maione, B.
Turley, S.E.H. Anomalous effect of carriers on dielectric constant of (In, Ga) (As, P) lasers operating at 1.3 μm wavelength 590
Turner, L.E. Second-order recursive digital filter that is free from all constant-input limit cycles 743
Tynes, A.R., Lin, C., Tomita, A., Glodis, P.F., and Philen, D.L. see Lin, C.


## U


Uchida, N., Kato, Y., Kitayama, K., and Seikai, S. see Kato, Y.
Uchida, N., Kato, Y., Tanifuji, T., and Tokuda, M. see Kato, Y.
Uchida, N., Shibata, N., Tateda, M., and Seikai, S. see Shibata, N.
Uematsu, Y., Okuda, H., and Kinoshita, J. Room-temperature CW operation of 1.3 μm distributed-feedback GaInAsP/InP lasers 857
Uemura, C., and Yamamoto, A. see Yamamoto, A.
Uemura, C., Yamamoto, A., Shibukawa, A., and Yamaguchi, M. see Yamamoto, A.
Umeno, M., Naitoh, M., and Sakai, S. see Naitoh, M.
Umeno, M., Sakai, S., and Aoki, T. see Sakai, S.
Unwin, R.T., and Sibley, M.J.N. see Sibley, M.J.N.
Upton, S.A.J., Evans, B.G., and Holt, A.R. Relationship between path length and attenuation of radio waves transmitted in a uniform rain-filled medium 515
Urgell, J.J., Baudelot, E., and Chante, J.P. see Baudelot, E.
Utaka, K., Akiba, S., Sakai, K., and Matsushima, Y. see Akiba, S.
Utaka, K., Matshushima, Y., Akiba, S., Sakai, K., Kushiro, Y., and Noda, Y. see Matshushima, Y.
Utaka, K., Yamamoto, S., Akiba, S., Sakai, K., Matsushima, Y., Sakaguchi, S., and Seki, N. see Yamamoto, S.


## V


Vahey, D., Hartman, N., Kidd, R., and Browning, M. see Hartman, N.
Valenzuela, A., Jacard, B., and Maldonado, O. see Jacard, B.
Valette, S., Morque, A., and Mottier, P. High-performance integrated Fresnel lenses on oxidised silicon substrate 13 e240
Van der Ziel, J.P., Levine, B.F., Logan, R.A., and Bethea, C.G. see Levine, B.F.
van der Ziel, J.P., Logan, R.A., Henry, C.H., and Temkin, H. see Logan, R.A.
van der Ziel, J.P., Logan, R.A., Temkin, H., and Henry, C.H. see Logan, R.A.
Vandamme, J., Bonte, L., Baert, D., De Bilde, J., and Dhooghe, W. see Bonte, L.
Vander Vorst, A., Vanhoenacker, D., and Mercier, L. Fluctuations on OTS-earth copolar link against diurnal and seasonal variations 915
Vandewalle, J., Desmedt, Y., and Govaerts, R. see Desmedt, Y.
Vanhoenacker, D., Vander Vorst, A., and Mercier, L. see Vander Vorst, A.
Varnham, M.P., Birch, R.D., and Payne, D.N. see Birch, R.D.
Vassallo, C., Alard, F., Jeunhomme, L., Monerie, M., and Sansonetti, P. see Alard, F.
Vassallo, C., Sansonetti, P., Alard, F., Kammerer, P., Francois, P.L., Monerie, M., Gabriagues, J.M., and Dupont, P. see Sansonetti, P.
Vaterkowski, J.L., and Evanno, M.H. see Evanno, M.H.
Vaucher, A.M., Li, M.G., and Lee. C.H. Diode-laser-controlled millimetre-wave propagation in a silicon waveguide 1066
Venkataramani, Y., and Venkateswaran, S. Active R multifunction circuit synthesis 96
Venkatesan, R., and Narraway, J.J. see Narraway, J.J.
Venkateswaran, S., and Venkataramani, Y. see Venkataramani, Y.
Vescan, L., Selders, J., Kräutle, H., Kütt, W., and Beneking, H. Be-implanted p-n junctions in $Ga_{0.47}In_{0.53}As$ 533
Vetelino, J.F., Bailey, D.S., Josse, F., Lee, D.L., Andle, J., Soluch, W., and Chai, B.H.T. see Bailey, D.S.
Viaro, U., Lepschy, A., and Mian, G. see Lepschy, A.
Vilar, E., Shepherd, P.R., Faulkner, N., and Bradsell, P. see Shepherd, P.R.
Villarruel, C.A., Burns, W.K., and Moeller, R.P. see Burns, W.K.
Voges, E., and Neyer, A. see Neyer, A.
Vogt, H., Hosticka, B.J., Kleine, U., and Zimmer, G. see Hosticka, B.J.
Von Helmolt, C.H. Electrical and acoustical cross-talk in integrated optical strip waveguide devices 969
Voos, M., Razeghi, M., Poisson, M.A., Larivain, J.P., de Cremoux, B., and Duchemin, J.P. see Razeghi, M.
Vorhaus, J.L., Ayasli, Y., Reynolds, L.D., and Hanes, L. see Ayasli, Y.
Vu, D.P., and Haond, M. see Haond, M.
Vu, D.-P., Haond, M., and Adès, C. see Haond, M.
Vukusic, J.I., Chen, J., and Sibbett, W. see Chen, J.


## W


Wada, O., Yamakoshi, S., Fujii, T., Hiyamizu, S., and Sakurai, T. AlGaAs/GaAs microcleaved facet (MCF) laser monolithically integrated with photodiode 189
Wada, T., and Dang, R.L.M. Modification of ICCG method for application to semiconductor device simulators 265
Wagatsuma, M., Kimura, T., Shuto, Y., and Yamakawa, S. Optical fibre coating speed prediction from flow properties of coating materials 731
Wagatsuma, M., Chida, K., Sakaguchi, S, and Kimura, T. see Chida, K.
Wagner, L.F., and Chang, F.Y. see Chang, F.Y.
Wagner, R.E., Boenke, M.M., and Will, D.J. see Boenke, M.M.
Wah, P.K.S., and Siegenthaler, T. Practical transform techniques for error and erasure correction 432 e584
Wakabayashi, H., Amano, K., Niiro, Y., Furusawa, K., and Nunokawa, M. see Amano, K.
Wakabayashi, H., Namihira, Y., and Yamamoto, H. see Namihira, Y.
Wake, D., Smith, D.R., Hooper, R.C., and Smyth, P.P. see Smith, D.R.
Wakefield, B., Elliott, C.R., and Regnault, J.C. see Elliott, C.R.
Walf, G., Albrecht, W., Elze, G., Enning, B., and Wenke, G. see Albrecht, W.
Walton, A.J., Analouei, A.R., and Burrow, N.G. see Analouei, A.R.
Ward, J.S., and Stanier, B.J. Implementation of convolution and Fourier transforms using 1-bit systolic arrays 799
Warne, D.H., Morgan, D.P., and Selviah, D.R. see Morgan, D.P.
Warne, D.H., Selviah, D.R., and Morgan, D.P. see Selviah, D.R.
Watanabe, H., Katoh, K., and Yasui, M. see Katoh, K.
Watanabe, T., Abe, Y., Kishino, K., Tanbun-Ek, T., Arai, S., Koyama, F., Matsumoto, K., and Suematsu, Y. see Abe, Y.
Watkins, E., Feng, M., Eu, V.K., Siracusa, M., Kimura, H., and Winston, H. see Feng, M.
Watson, B.K., Ghosh, S., and Adatia, N. see Ghosh, S.
Webb, R.P. Output noise spectrum from demodulator in an optical PFM system 634 e802
Weder, E., and Guggenbühl, W. Improved analytical solution of settling behaviour of op-amps 627
Weglein, R.D. Nondestructive film thickness measurement on industrial diamond 1003
Weglein, R.D. Rayleigh wave absorption via acoustic microscopy 20
Wei, C.J., Zhao, Y.Y., and Beneking, H. see Zhao, Y.Y.
Wei, T., Donalds, L.J., French, W.G., Mitchell, W.C., and Swinehart, R.M. see Donalds, L.J.
Weidel, E., and Rode, M. see Rode, M.
Wellekens, C.J. Equivalence of two designs of bilinear switched-capacitor ladder filters 246

Weller, J.F., Goldberg, L., and Taylor, H.F. see Goldberg, L.
Wemple, S.H., and Nassau, K. see Nassau, K.
Weng, K.C.-K., Gunshor, R.L., Pierret, R.F., and Tsubouchi, K. Electronic erasure of stored reference signals in a metal-ZnO-$SiO_2$-Si induced junction storage correlator 1078
Weng, T., Neidert, R.E., and Binari, S.C. see Neidert, R.E.
Wenke, G., Albrecht, W., Elze, G., Enning, B., and Walf, G. see Albrecht, W.
West, C.L. High-performance SAW convolver using 3-phase unidirectional transducers 401
West, R.H., and Lenham, A.P. Characteristics of light induced annealing in irradiated optical fibres 483
Westbrook, L.D., Nelson, A.W., and Dix, C. High-quality InP surface corrugations for 1.55 μm InGaAsP DFB lasers fabricated using electron-beam lithography 863
Westcott, B.S., and Brickell, F. Compensation for feed crosspolarisation in shaped dual offset reflectors 126
Weston, C.R., Clarke, R., and Midgley, D see Clarke, R.
Whitbread, T., and Chu, P.L. see Chu, P.L.
White, K.I. Design parameters for dispersion-shifted triangular-profile single-mode fibres 725
Whitehouse, C.R., Cameron, D.C., Irving, L.D., and Woodward, J. see Cameron, D.C.
Wickramasinghe, H.K., Ameri, S., and See, C.W. Differential phase contrast optical microscope with 1 Å-depth resolution 973
Wickramasinghe, H.K., Martin, Y., Ball, S., and Ash, E.A. Thermodisplacement imaging of current in thin-film circuits 700
Wickramasinghe, H.K., and Smith, I.R. see Smith, I.R.
Wight, D.R., Wright, P.J., and Cockayne, B. High-efficiency blue luminescence from MOCVD-grown ZnSe at room temperature 593
Will, D.J., Boenke, M.M., and Wagner, R.E. see Boenke, M.M.
Willson, A.N., and Reames, C.P. see Reames, C.P.
Winch, R.G. K-band FET doubling oscillator 946
Winston, H., Feng, M., Eu, V.K., Siracusa, M., Watkins, E., and Kimura, H. see Feng, M.
Witte, K.-H., Klein, K.-F., and Heinlein, W.E. see Klein, K.-F.
Wong, K.K., Pun, E.Y.B., Andonovic, I., Laybourn, P.J.R., and De La Rue, R.M. see Pun, E.Y.B.
Wong, K.P., and Humpage, W.D. see Humpage, W.D.
Wong, W.T., and Yeung, K.S. see Yeung, K.S.
Wood C.E.C., Eastman, L.F., Board, K., Singer, K., and Malik, R. Regenerative switching device using MBE-grown gallium arsenide 676
Wood, C.E.C., Hollis, M.A., and Eastman, L.F. see Hollis, M.A.
Wood, C.E.C., Xin, S.H., DeSimone, D., Palmateer, S., and Eastman, L.F. see Xin, S.H.
Wood, M.A. Precise calibration of a rotary vane attenuator at 35 GHz using a homodyne network analyser 1025
Wood, M.A. Tunable low-reflection waveguide termination 174
Woodward, J., Brown, G.T., Cockayne, B., and Cameron, D.C. Substrate effects on performance of InP MOSFETs 415
Woodward, J., Cameron, D.C., Irving, L.D., and Whitehouse, C.R. see Cameron, D.C.
Wright, P.J., Wight, D.R., and Cockayne, B. see Wight, D.R.
Wu, R.H., Allsopp, D., and Peaker, A.R. Hole traps in n-type $Ga_{1-x}Al_xAs$ grown by organometallic vapour phase epitaxy 75
Wunsch, A.D. Transverse current on strip dipole antenna 664 e1065
Wyatt, R., Smith, D.W., and Cameron, K.H. Megahertz linewidth from a 1.5 μm semiconductor laser with HeNe laser injection 292
Wyatt, R., Hodgkinson, T.G., and Smith, D.W. see Hodgkinson, T.G.

X

Xie, W., and Bedrosian, S.D. see Bedrosian, S.D.
Xin, S.H., Wood, C.E.C., DeSimone, D., Palmateer, S., and Eastman, L.F. 1.40 eV emission band in GaAs 3

Y

Yabuta, T., Ishihara, K., and Negishi, Y. Submarine optical-fibre design considering low elongation under tension 943
Yamada, J., Kawana, A., Nagai, H., Kimura, T., and Miya, T. 1.55 μm optical transmission experiments at 2 Gbit/s using 51.5 km dispersion-free fibre 98
Yamaguchi, E., and Kobayashi, T. New method for determining distribution of interface states in an MIS system 290
Yamaguchi, M., Hashimoto, K.Y., Igarashi, Y., and Kogo, H. see Hashimoto, K.Y.
Yamaguchi, M., Yamamoto, A., Shibukawa, A., and Uemura, C. see Yamamoto, A.
Yamakawa, S., Wagatsuma, M., Kimura, T., and Shuto, Y. see Wagatsuma, M.
Yamakoshi, S., Wada, O., Fujii, T., Hiyamizu, S., and Sakurai, T. see Wada, O.
Yamamoto, A., Shibukawa, A., Uemura, C., and Yamaguchi, M. Low-temperature (~77 K) properties of InP MOSFETS using anodic-oxide gate insulator 710
Yamamoto, A., and Uemura, C. Anodic oxide film as gate insulator for InP MOSFETs 63
Yamamoto, H., Namihira, Y., and Wakabayashi, H. see Namihira, Y.
Yamamoto, H., Tatekura, K., and Ejiri, Y. see Tatekura, K.
Yamamoto, H., Tatekura, K., and Nunokawa, M. see Tatekura, K.
Yamamoto, S., Utaka, K., Akiba, S., Sakai, K., Matsushima, Y., Sakaguchi, S., and Seki, N. 280 Mbit/s single-mode fibre transmission with DFB laser diode emitting at 1.53 μm 239
Yamamoto, Y., Mukai, T., and Kimura, T. see Mukai, T.
Yamamoto, Y., Saito, S., and Kimura, T. see Saito, S.
Yamanaka, K. Analysis of SAW attenuation measurement using acoustic microscopy 587
Yamane, Y., Yamasaki, K., and Kurumada, K. see Yamasaki, K.
Yamanishi, M., Suemune, I., and Kohno, M. see Suemune, I.
Yamao, Y., Suzuki, H., and Kikuchi, H. see Suzuki, H.
Yamasaki, K., Asai, K., Mizutani, T., and Kurumada, K. Self-align implantation for $n^+$-layer technology (SAINT) for high-speed GaAs ICs 119
Yamasaki, K., Yamane, Y., and Kurumada, K. Below 20 ps/gate operation with GaAs SAINT FETs at room temperature 592
Yamashita, K., Noguchi, K., Murakami, Y., and Ashiya, F. see Noguchi, K.
Yamauchi, J., Nakano, H., and Iio, S. see Nakano, H.
Yamauchi, R., Miyamoto, M., and Inada, K. Practical determination of equivalent-step-index profiles for single-mode fibres 550
Yamauchi, Y., Mikami, O., Nakagome, H., and Kanbe, H. see Mikami, O.
Yamazaki, E., Murakami, T., and Asai, K. see Murakami, T.
Yamazaki, S., Shirai, T., Yasuda, K., Mikawa, T., Nakajima, K., and Kaneda, T. see Shirai, T.
Yao, S.K., Asawa, C.K., Stearns, R.C., Mota, N.L., and Downs, J.W. see Asawa, C.K.
Yariv, A., Blauvelt, H., and Margalit, S. see Blauvelt, H.
Yarlagadda, R., and Hershey, J.E. Benchmark synchronisation of m-sequences 68
Yasu, M., Kawachi, M., Tomaru, S., Edahiro, T., and Sakaguchi, S. see Kawachi, M.
Yasuda, K., Shirai, T., Yamazaki, S., Mikawa, T., Nakajima, K., and Kaneda, T. see Shirai, T.
Yasui, M., Katoh, K., and Watanabe, H. see Katoh, K.
Yasumoto, M., and Enomoto, T. Integrated MOS four-quadrant analogue multiplier using switched-capacitor technique 769
Yasumoto, M., Ishihara, T., Enomoto, T., and Aizawa, T. see Ishihara, T.
Yasumoto, Masa-Aki., Enomoto, T., and Ishihara, T. see Enomoto, T.
Yaz, E. Two fast algorithms to compute the discrete receding horizon control gains 500
Ye, R., and Tsividis, Y. Bandgap voltage reference sources in CMOS technology 24
Yen, K.H., and Berenz, J.J. High-efficiency millimetre-wave InP TEOs made by liquid phase epitaxy 171
Yen, K.H., Stokes, R.B., Lau, K.F., Kong, A., and Kagiwada, R.S. Low-loss low-ripple SAW filters using three bidirectional centrosymmetric transducers 403
Yeung, K.S., and Wong, W.T. Root-locus plot of systems with time delay 480
Yokoshima, I., Iwasaki, T., and Nakamura, K. see Iwasaki, T.
Yokota, H., Okoshi, T., Oyamada, K., and Nishimura, M. see Okoshi, T.
Yoneyama, T., Gomi, J., and Nishida, S. see Gomi, J.
Yoshida, K., Hanamitsu, K., Ohsaka, S., Nishi, H., Hori, K., and Takusagawa, M. see Hanamitsu, K.
Yoshida, S., Haneishi, M., and Nambara, T. see Haneishi, M.
Yoshimi, M., Kawabuchi, K., Takigawa, T., Takahashi, M., and Kato, Y. Lower submicron pattern definition by high-voltage electron-beam lithography 880
Yoshioka, K., Kawanishi, H., Hiraoka, M., Nishio, K., Nakagomi, T., and Tanaka, S. see Kawanishi, H.
Yoshizawa, T., Kurokawa, T., and Nara, S. High-precision moulded connector for single-mode optical fibres 598
Yu, Y.N., and Lim, C.M. see Lim, C.M.

Z

Zhao, Y.Y., Wei, C.J., and Beneking, H. Transferred-electron oscillations in $In_{0.53}Ga_{0.47}As$ 835
Ziegler, H., and Bromba, M.U.A. see Bromba, M.U.A.
Zimmer, G., Hosticka, B.J., Kleine, U., and Vogt, H. see Hosticka, B.J.
Zipperian, T.E., Myers, D.R., Biefeld, R.M., and Dawson, L.R. see Myers, D.R.
Zirath, H., Cho, A.Y., Kollberg, E., Snell, W.W., and Schneider, M.V. see Cho, A.Y.

# Subject index


### ACOUSTO-OPTICS

Analysis of SAW attenuation measurement using acoustic microscopy. K.Yamanaka 587
Differential phase contrast in the acoustic microscope. I.R.Smith and H.K.Wickramasinghe 92
Differential phase contrast optical microscope with 1 Å-depth resolution. H.K.Wickramasinghe, S.Ameri and C.W.See 973
Effect of leaky SAW parameters on V(z) curves obtained by acoustic microscopy. J.Kushibiki, A.Ohkubo and N.Chubachi 668
SAW attenuation measurement in the acoustic microscope. I.R.Smith and H.K.Wickramasinghe 955
Theorectical analysis for V(z) curves obtained by acoustic microscope with line-focus beam. J.Kushibiki, A.Ohkubo and N.Chubachi 663
Thermal wave imaging through radio frequency induction heating. J.Saniie, M.Luukkala, A.Lehto and R.Rajala 651
Thermodisplacement imaging of current in thin-film circuits. H.K.Wickramasinghe, Y.Martin, S.Ball and E.A.Ash 700

### ANTENNAS

Broadband circular disc microstrip antenna. J.M Griffin and J.R.Forrest 266
Characteristics of annular-ring microstrip antenna. J.S.Dahele and K.F.Lee 1051
Concentric ring and Jerusalem cross arrays as frequency selective surfaces for a 45D incidence diplexer. R.Cahill and E.A.Parker 313
Correlation of 6 and 4 GHz depolarisation on slant paths. A.Ogawa and J.E.Allnutt 230
Crosspolar levels of ring arrays in reflection of 45° incidence: influence of lattice spacing. R.Cahill and E.A.Parker 1060
Current distribution on the elements of a square loop frequency selective surface. S.M.A.Hamdy and E.A.Parker 624
Design of hybrid diversity on overwater paths. J.A.Garcia-Lopez, J.M.Ferrandiz and J.M.Selga 420
Effect of antenna polarisation on rain scattering. J.Awaka, M.Shimada, T.Isobe and E.Ouchi 205
Effect of disc reflectors on radiation impedance of short-backfire antenna. S.D.Marougi 154
Equivalent circuit model for arrays of square loops. R.J.Langley and E.A.Parker 294
Far field radiated by rectangular patch microstrip antenna. G.Dubost 991
Fast integration techniques for reflector antenna pattern analysis. A.D.Craig and P.D.Simms 60
Ground station antenna crosspolarisation measurements with an imperfectly polarised ancillary antenna. K.M.Keen 924
Hybrid-mode feed for multiband applications having a dual-depth corrugation boundary. S.Ghosh, N.Adatia and B.K.Watson 860
Improvements to a surface-wave antenna measurement range with troublesome site effects. K.M.Keen, R.R.Grime and B.E.Stemp 439
Influence of surface-wave excitation on efficiency of space-wave launching in microstrip disc antennas. S.B.deA.Fonseca and A.J.Giarola 406
Mutual coupling between microstrip antennas. E.Penard and J.-P.Daniel 605
Mutual coupling between microstrip patch antennas. M.Malkomes 520
New application for radiation resistance. T.S.M.Maclean 378
New wideband high-gain stripline planar array for 12 GHz satellite TV. E.Rammos 252
Novel leaky-wave antenna for millimetre waves based on groove guide. A.A.Oliner and P.Lampariello 1105
Novel technique for antenna gain measurement in satellite earth stations. P.Daly and D.Tits 1089
Radiation patterns in far field from two H-plane coupled rectangular microstrip antennas. C.M.Krowne 645
Resolution of monochromatic signal sources using a simple receiving antenna array. Y.C.Cheah and F.J.Paoloni 923
Rotation of plane of polarisation of a beam of microwaves by corrugated reflection surfaces. P.O.Paul and K.G.Nair 338
Shaped wire antennas with maximum directivity. D.K.Cheng and C.H.Liang 816
Slotted antenna array excited by a coplanar waveguide. A.Nešić 275
Study on ellipticity properties of single-feed-type circularly polarised microstrip antennas. M.Haneishi, T.Nambara and S.Yoshida 191
Tapered backfire helical antenna with loaded termination. H.Nakano, J.Yamauchi and S.Iio 158
Transverse current on strip dipole antenna. A.D.Wunsch 664 e1065

### BIOMEDICAL ELECTRONICS

Measurements substantiating localised microwave hyperthermia within a thorax phantom. M.Melek, A.P.Anderson, B.H.Brown and J.Conway 437

### CIRCUIT THEORY AND DESIGN

94 GHz balanced fin-line mixer. W.Menzel and H.Callsen 5
Active R multifunction circuit synthesis. Y.Venkataramani and S.Venkateswaran 96
Algorithm for finding the common spanning trees of two graphs (Comment & Reply). S.R.Schach 988
Application of complementary transformation to NIC compensated amplifiers. T.S.Rathore 400
Cascade synthesis of a class of mixed lumped-distributed networks. H.Baher 105
Compact matrix scheme for use in computer analysis of switched-capacitor networks. C.Lau and J.I.Sewell 840
Digital method of sweep frequency generation. J.J.Hill and P.M.Jewson 1017
Exact design of switched-capacitor bandpass ladder filters. M.S.Tawfik, C.Terrier, C.Caillon and J.Borel 1101
Excess delay factor associated with dominant poles of trimmed distributed RC networks. A.R.Analouei, A.J.Walton and N.G.Burrow 681
False-lock sources in charge-pump phase-lock loops. G.Niekolaas, R.C.Den Dulk and L.K.Regenbogen 568
FIR filter for generating multi-level signals from single-bit noise sequences. J.R.Jordan and B.Kiani-Shabestari 739
Floating voltage-controlled resistors in CMOS technology. M.Banu and Y.Tsividis 678 e936
General stray-insensitive first-order active SC network. P.V.Ananda Mohan, V.Ramachandran and M.N.S.Swamy 1
Global convergence of Newton's method in the DC analysis of single-transistor networks. C.P.Reames and A.N.Willson 519
High-Q- SC biquad with a minimum capacitor spread. G.Fischer and G.S.Moschytz 1087
High-speed NMOS operational amplifier fabricated using VLSI technology. T.Ishihara, T.Enomoto, M.Yasumoto and T.Aizawa 159
Improved analytical solution of settling behaviour of op-amps. E.Weder and W.Guggenbühl 627
Improvement of on-resistance of MOS-gated devices. E.Baudelot, J.P.Chante and J.J.Urgell 546
Inductorless current conveyor allpass filter using grounded capacitors. K.Pal and R.Singh 47 e240
Integrated MOS four-quadrant analogue multiplier using switched-capacitor technique. M.Yasumoto and T.Enomoto 769
Integrated tapped MOS analogue delay line using switched capacitor technique. T.Enomoto, T.Ishihara and Masa-Aki.Yasumoto 193
Monolithic 2-20 GHz GaAs travelling-wave amplifier. Y.Ayasli, L.D.Reynolds, J.L.Vorhaus and L.Hanes 596
Netwoek equivalence for crystal prototype Brune section. C.R.Dillon 374
New clock feedthrough cancellation technique for analogue MOS switched-capacitor circuits. K.Martin 39
New method for approximating time-delay systems with delay-free systems. B.Maione and B.Turchiano 622
New method of approximating the acceptable region of nonlinear resistive networks. A.Macura and J.Rutkowski 654
Nonperiodic sampling and identifiability. M.de la Sen e350
Novel active-compensated variable-phase inverting integrator. M.V.Popovich and O.Katić 1080
Novel grounded-capacitor ideal FDNR and oscillator using current conveyors. R.Nandi 145
Novel lossless synthetic floating inductor employing a grounded capacitor. R.Senani 413 e584
Novel SC integrator realising the bilinear z-transform. H.Jamal and F.E.Holmes 390
Novel variable-frequency oscillator with single resistor control using DVCCS/DVCVS. R.Nandi 144
Output correlation functions of power-law nonlinearities fed by Gaussian noise. N.M.Blachman 347
Parasitic insensitive toggle-switched capacitor and its applications to switched-capacitor networks. J.C.M.Bermudez and B.B.Bhattacharyya 734 e936
Parasitic insensitive toggle-switched capacitor and its applications to switched-capacitor networks (Comment). F.Maloberti and F.Montecchi 1061
Resistive multiport scattering matrix realisation using operational amplifiers. J.Pospíšil 525
Simple low-cost correlator and multiplier circuits. P.J.Glen 914
Simple method for obtaining the equations of switched-capacitor circuits. Y.Tsividis and S.C.Fang 728
Six-port reflectometer circuit comprising three directional couplers. E.J.Griffin 491
Solution to instability problems of grid-connected PWM DC-AC inverters. L.Bonte, D.Baert, J.Vandamme, J.De Bilde and W.Dhooghe 600
Special cases of Fliege's complementary transformation for active RC networks. J.K.Stevenson and D.G.Haigh 514
Strays-insensitive switched-capacitor network realisation for nth-order voltage transfer functions. C.Karagöz and C.Acar 966
Switching speed of a circuit with positive feedback. P.J.Langlois 172
Synthesis of dual-feedback ideal op-amp oscillator circuits. N.Boutin 579
z-plane analysis of networks of distributed and discrete systems. W.D.Humpage and K.P.Wong 502

### CODES AND CODING

Application of transform techniques to digital line codes and data transmission. D.G.W.Ingram and T.T.Tjhung 949
Buffering strategy for variable-symbol-rate speech waveform coders. J.N.Holmes 691
Extension of RSA crypto-structure: A Galois approach. D.W.Kravitz and I.S.Reed 255
Extension of RSA crypto-structure: a Galois approach (Comment & Reply). P.Delsarte and P.Piret 582
Fast decipherment algorithm for RSA public-key cryptosystem. J.-J.Quisquater and C.Couvreur 905
Graphic image coding based on a pattern-dependent runlength model. Y.S.Shim and J.K.Kim 476
How iterative transformations can help to crack the Merkle-Hellman cryptographic scheme. Y.Desmedt, J.Vandewalle and R.Govaerts 910
Implementation of digital signatures. B.Arazi 900
New runlength-limited and DC-free line code of minimum bandwidth. D.Y.Kim and J.K.Kim 1040
Power spectra of 6B4T and 3B2T codes. G.S.Poo 884
Practical transform techniques for error and erasure correction. P.K.S.Wah and T.Siegenthaler 432 e584
Residue number system error checking using expanded projection. W.K.Jenkins 927
Short cycling in the Kravitz-Reed public key encryption system. J.Gait 706

### COMPUTERS

Fault coverage of pattern-sensitive fault-detection algorithms for semiconductor memories. D.Sarma, C.A.Papachristou and F.T.Saifuddin 950
Z8001-based central processing unit with capability addressing. P.Corsini and L.Lopriore 780

### CONTROL THEORY

Compensation of discrete systems to variations in their parameters by changing sampling period. M.B.Paz, M.De La Sen, S.Dormido and M.Mellado 404
Direct method of reducing order of linear systems using Koenig's theorem. C.P.Therapos 826
Identification of continuous-time state-space model from samples of input-output data. Z.Qi-Jie and N.K.Sinha 50
Iterative approach to multivariable control. J.Hickin 671

Limit cycles in relay systems. D.P.Atherton 922
Nonperiodic sampling and model matching. M.de la Sen 311
Numerical inversion of a class of Laplace transforms. C.P.Therapos and J.E.Diamessis 620
Optimal scalar Lyapunov functions for decentralised stabilisation of interconnected systems. H.M.Soliman and R.J.Fleming 993
Output feedback optimal controller for linear single-input system. C.M.Lim and Y.N.Yu 36
Root-locus plot of systems with time delay. K.S.Yeung and W.T.Wong 480
Sensitivity of principal phases. R.W.Daniel 754
Suboptimal control with incomplete state feedback. C.P.Therapos 996
Two fast algorithms to compute the discrete receding horizon control gains. E.Yaz 500

### DATA TRANSMISSION

Application of transform techniques to digital line codes and data transmission. D.G.W.Ingram and T.T.Tjhung 949
Simple low-cost correlator and multiplier circuits. P.J.Glen 914

### DIELECTRICS AND DIELECTRIC DEVICES

Breakdown voltage of a plasma-filled gap. J.Santiago, P.R.Smy and R.M.Clements 165
Dielectric constant of semi-insulating indium phosphide. R.E.Neidert, S.C.Binari and T.Weng 987
Dielectric-waveguide filters using parallel-coupled grating resonators. G.L.Matthaei, C.E.Harris, D.C.Park and Y.Kim 509
Double polysilicon plate capacitors with oxide/nitride insulator. G.Gildenblat, M.Ghezzo and J.Norton 34
New radial power combiner using tubular dielectric cavities. J.Obregon, J.P.Balabaud, P.Guillon and Y.Garault 771

### DIGITAL CIRCUITS

Asummability testing. A.K.Sarje 938
Bidirectional ripple clock scheme for serial-parallel-serial charge-coupled devices. M.J.M.Pelgrom and L.J.M.Esser 289
Novel architecture for a time division switch. P.L.Nicholson 1100
Simple received signal/eye amplitude monitor for digital repeaters. P.Cochrane and E.Powell 388

### ELECTROLUMINESCENCE

High-efficiency blue luminescence from MOCVD-grown ZnSe at room temperature. D.R.Wight, P.J.Wright and B.Cockayne 593

### ELECTROMAGNETIC WAVES

Comparison of modal analysis and equivalent circuit representation of E-plane arm of the Jerusalem cross. S.M.A.Hamdy and E.A.Parker 94
Currents induced on a conducting halfplane by a plane wave at arbitrary incidence. G.Morris 610
Excitation of multimode guide by stripline-fed slots. B.N.Das and A.Biswas 801
Finite-element approximation of electromagnetic diffraction by arbitrarily shaped surfaces. A.Bendali, D.Clair and J.Tourneur 641
Measurement of mutual scattering between spheres by use of microwave open resonator. B.Mahmid and L.J.Auchterlonie e240
New computation method for characteristic modes. A.H.Nalbantoğlu 994
Periodic multielement strip gratings. M.J.Archer 958
Propagation constants of cylindrical dielectric waveguides with arbitrary refractive-index profile using 'resonance' technique. C.D.Papageorgiou and A.C.Boucouvalas 786
Scatterer reconstruction from multistatic far-field data. H.-J.Meckelburg 341
STW resonances on corrugated plates of finite thickness. B.A.Auld, A.Renard and J.Henaff 183
Utilisation d'un nouveau type de noeud dans la methode TLM en 3 dimensions. P.Saguet and E.Pic 478
Wave propagation in transversely inhomogeneous dielectric waveguide. P.Y.P.Chen 736

### ELECTRON DEVICES

Determination of resonant frequency for 2nd-harmonic-mode millimetre-wave transferred-electron oscillators. R.N.Bates 198
Enhancement of resist plasma erosion rates by electron-beam hardening. R.A.Morgan and C.J.Pollard 1038
High-efficiency millimetre-wave InP TEOs made by liquid phase epitaxy. K.H.Yen and J.J.Berenz 171
Transferred-electron oscillations in $In_{0.53}Ga_{0.47}As$. Y.Y.Zhao, C.J.Wei and H.Beneking 835

### EPITAXY AND EPITAXIAL GROWTH

Growth effects of $In_{0.53}Ga_{0.47}As$ on InP structured substrates. N.Chand, A.V.Syrbu and P.A.Houston 613

### FILTERS

2-phase circulating shift register for switched-capacitor N-path filters. H.C.Patangia and J.Cartinhour 444
750 MHz microstrip bandpass filter on barium tetratitanate substrate. G.Ohm and G.Schmöller 661
Active-phase-compensated biquadratic highpass filter. K.K.Tuladhar 184
Benchmark synchronisation of m-sequences. R.Yarlagadda and J.E.Hershey 68
Constrained LMS adaptive algorithm. A.Segalen and G.Demoment 226
Design of high-order filters with restricted component values. K.Ramakrishna and K.Rajgopal 457
Dielectric-waveguide filters using parallel-coupled grating resonators. G.L.Matthaei, C.E.Harris, D.C.Park and Y.Kim 509
Digital filters with fast coefficient implementation. J.J.Narraway and R.Venkatesan 852
Effects of parasitics in lowpass elliptic filters for MIC. F.Giannini, M.Salerno and R.Sorrentino 284
Efficient determination of FIR Wiener filters with linear phase. D.Manolakis, N.Kalouptsidis and G.Carayannis 429
Equivalence of two designs of bilinear switched-capacitor ladder filters. C.J.Wellekens 246
Exact design of elliptic switched-capacitor filters by synthesis. J.Taylor 807
FIR digital filters with simultaneous conditions on amplitude and delay. H.Baher 296
FIR filter for generating multi-level signals from single-bit noise sequences. J.R.Jordan and B.Kiani-Shabestari 739
Further results on maximally flat nonrecursive digital filters. M.U.A.Bromba and H.Ziegler 1014
Low-frequency noise reduction in SC ladder filters. F.Maloberti and F.Montecchi 674
Low-noise state-space realisation of bandpass active filter (Comment). P.E.Fleischer, A.Ganesan and J.Tow 149
Low-noise state-space realisation of bandpass active filter (Comment & Reply). J.R.Carey 685
Modification of shanks conjecture on stability of 2-D planar least-square inverse polynomials. P.S.Reddy, D.R.Reddy and M.N.S.Swamy 456
New frequency transformation for the accurate design of SC ladder filters. E.Hökenek, U.W.Brugger and G.S.Moschytz 276
Novel switched-capacitor pseudo-N-path filter. U.Kleine and J.Pandel 66
Parasitic-compensated second-order switched-capacitor filters. P.V.Ananda Mohan, V.Ramachandran and M.N.S.Swamy 531
Second-order Q and $\omega$ shifts in RC active filters having nonideal amplifiers. R.Moon and F.W.Stephenson 365
Second-order recursive digital filter that is free from all constant-input limit cycles. L.E.Turner 743
Sensitivity comparison of symmetric and asymmetric dual-mode bandpass filters. H.N.Shamasundara, C.M.Kudsia and M.N.S.Swamy 552
Sensitivity of the symmetric fom filter. E.J.P.May and H.H.Mehdi 8
Simple design technique for inherently stable fan filters. R.A.King and A.H.Kayran 127
Simple dielectric waveguide bandpass filter. G.L.Matthaei, C.E.Harris, Y.M.Kim, D.C.Park and J.P.Duvall 798
Stable fan filter design using two-variable reactance functions. L.T.Bruton and N.R.Bartley 217
Switched-capacitor FIR cell for n-path filters. S.M.Faruque 431
Transfer functions of wave-digital filters. E.C.Tan 722
Variable lowpass wave-digital filters. E.C.Tan 324

### IMAGE PROCESSING

Automatic temperature mapping system based on holographic interferometry. G.Lucarini, F.Piazza, C.Morandi and A.Pierfederici 623
Effects of border variations due to spatial quantisation on binary-image template matching. D.Lavie and W.K.Taylor 418
Fuzzy-measure justification of some grey-tone image experimental data. S.D.Bedrosian and W.Xie 615

### INTEGRATED CIRCUITS

Analysis of printed transmission lines for monolithic integrated circuits. Y.C.Shih and T.Itoh 585
Automatic start-up technique for complementary PTAT current generators. B.L.Hart 776
Bandgap voltage reference sources in CMOS technology. R.Ye and Y.Tsividis 24
Capacitors made by anodisation of aluminium for wideband GaAs ICs. M.Binet 197
Enhancement of resist plasma erosion rates by electron-beam hardening. R.A.Morgan and C.J.Pollard 1038
Full-wave analysis of integrated transmission lines on layered lossy media. R.Sorrentino and G.Leuzzi 607
K-band FET doubling oscillator. R.G.Winch 946
Modified current mirror with a 'voltage-following' capability. B.L.Hart and R.W.J.Barker 970
Monolithic integrated amplifiers for 400 Mbit/s optical repeater. S.Tsuyuki, K.Suto, T.Kamoto and T.Sakai 340
Monolithic integration of optoelectronic, electronic and passive components in GaAlAs/GaAs multilayers. A.C.Carter, N.Forbes and R.C.Goodfellow 72
New high-voltage CMOS technology. N.D.Jankovic and R.S.Popovic 115
Quasiplanar 3 dB hybrid for millimetre-wave integrated circuits. H.Callsen and L.-P.Schmidt 161
Self-align implantation for $n^+$ -layer technology (SAINT) for high-speed GaAs ICs. K.Yamasaki, K.Asai, T.Mizutani and K.Kurumada 119
W-band broadband integrated circuit mixers. R.S.Tahim, G.M.Hayashibara and K.Chang 471

### INTEGRATED OPTICS

AlGaAs/GaAs microcleaved facet (MCF) laser monolithically integrated with photodiode. O.Wada, S.Yamakoshi, T.Fujii, S.Hiyamizu and T.Sakurai 189
Combined dry and wet etching techniques to form planar (011) facets in GaInAsP/InP double heterostructures. L.A.Coldren, K.Furuya, B.I.Miller and J.A.Rentschler 235
Efficient waveguide Bragg-deflection grating on $LiNbO_3$. E.Y.B.Pun, K.K.Wong, I.Andonovic, P.J.R.Laybourn and R.M.De La Rue 740 e896
Fabrication of curved structures by electron-beam lithography. P.G.Flavin 865
High-performance integrated Fresnel lenses on oxidised silicon substrate. S.Valette, A.Morque and P.Mottier 13 e240
Lloyd's mirror interference in a medium - A new method for determining photoelastic index variation. Hong-Du.Liu and Zhe-Chuan Feng 251
Novel deposit/spin waveguide interconnection (DSWI) technique for semiconductor integrated optics. K.Furuya, B.I.Miller, L.A.Coldren and R.E.Howard 204
Optical Y-junctions and S-bends formed by preferentially etched single-mode rib waveguides in InP. P.Buchmann and A.J.N.Houghton 850
Preparation and properties of monolithically integrated lenses on InGaAsP/InP light-emitting diodes. J.Heinen 831

### LASERS AND LASER APPLICATIONS

1.5 $\mu$m GaInAsP/InP buried heterostructure lasers fabricated by hybrid combination of liquid-and vapour-phase epitaxy. O.Mikami, H.Nakagome, Y.Yamauchi and H.Kanbe 237
1.5 $\mu$m GaInAsP/InP distributed Bragg reflector lasers with built-in optical waveguide. O.Mikami, T.Saitoh and H.Nakagome 458

20 Gbit/s optical time multiplexing with TJS GaAlAs lasers. A.Alping, T.Andersson, R.Tell and S.T.Eng 422
4 Gbit/s direct modulation of 1.3 μm InGaAsP/InP semiconductor lasers. K.Hagimoto, N.Ohta and K.Nakagawa 796
7 Gbit/s coherent pulse generation in an actively mode-locked GaAlAs diode laser. Y.Suzuki and T.Sato 821
(AlGa)As strip buried-heterostructure lasers prepared by hybrid crystal growth. W.T.Tsang and R.A.Logan 397
Anomalous effect of carriers on dielectric constant of (In, Ga) (As, P) lasers operating at 1.3 μm wavelength. S.E.H.Turley 590
Astigmatism of semiconductor lasers with $\cosh^{-2}(x)$ profile of gain. J.Pietzsch 1015
Auger recombination rate in InGaAsP lasers. M.G.Burt 806
Automatic temperature mapping system based on holographic interferometry. G.Lucarini, F.Piazza, C.Morandi and A.Pierfederici 623
Capillary bonded components for injection laser transmitter modules. L.D.Comerford and M.J.Brady 629
Combined dry and wet etching techniques to form planar (011) facets in GaInAsP/InP double heterostructures. L.A.Coldren, K.Furuya, B.I.Miller and J.A.Rentschler 235
Current/frequency-modulation characteristics for directly optical frequency-modulated injection lasers at 830 nm and 1.3 μm. G.Jacobsen, H.Olesen, F.Birkedahl and B.Tromborg 874
Current-induced frequency modulation in diode lasers. A.Dandridge and L.Goldberg 302
CW longitudinal mode spectra of multiple quantum well stripe lasers. C.Lindström, D.Halido, D.R.Scifres and R.D.Burnham 876
CW operation of DFB-BH GaInAsP/InP lasers in 1.5 μm wavelength region. T.Matsuoka, H.Nagai, Y.Itaya, Y.Noguchi, Y.Suzuki and T.Ikegami 27
CW room-temperature visible single quantum well $Ga_{0.73}Al_{0.27}As$ diode lasers grown by metalorganic chemical vapour deposition. R.D.Burnham, D.R.Scifres and W.Streifer 507
Dielectric guiding due to an inverted gain profile in GaAs/GaAlAs lasers. P.Brosson, E.J.T.Manganote and F.C.Prince 932
Diode laser array excited star coupler suitable for Fibernet II. D.R.Scifres, M.D.Bailey, R.E.Norton, R.D.Burnham and E.G.Rawson 1028
Diode-laser-controlled millimetre-wave propagation in a silicon waveguide. A.M.Vaucher, M.G.Li and Lee. C.H. 1066
Dispersion effects using a 1.52 μm laser. D.A.Frisch and I.D.Henning 129
Double-channel planar buried-heterostructure laser diode with effective current confinement. I.Mito, M.Kitamura, Ke.Kobayashi and Ko.Kobayashi 953
Dual-wavelength (GaAl)As laser. N.Bouadma, J.C.Bouley and J.Riou 871
Dual wavelength InGaAsP/InP TJS lasers. S.Sakai, T.Aoki and M.Umeno 18
Effect of semiconductor laser phase noise on BER performance in an optical DPSK heterodyne-type experiment. F.Favre and D.Le Guen 964
Experimental observation of asymmetric detuning characteristics in semiconductor laser injection locking. K.Kobayashi, H.Nishimoto and R.Lang 54
Far-field radiation patterns of multiple quantum well lasers grown by MO-CVD. D.Halido, C.Lindström and D.R.Scifres 765
FM sideband injection locking of diode lasers. L.Goldberg, H.F.Taylor and J.F.Weller 1019
GaInAsP/InP DH laser on semi-insulating InP substrate with terrace structrue. T.Matsuoka, Y.Suzuki, Y.Noguchi and H.Nagai 359
GaSb photodiode for detection of 1.73 μm radiation of Er:YLF laser. C.Heinz and W.Schmidt auf Altenstadt 859
Generation of single-longitudinal-mode subnanosecond light pulses by high-speed current modulation of monolithic two-section semiconductor lasers. K.J.Ebeling, L.A.Coldren, B.I.Miller and J.A.Rentschler 901
High-efficiency short-cavity InGaAsP laser with one high-reflectivity mirror. T.P.Lee, C.A.Burrus, P.L.Liu and A.G.Dentai 805
High-frequency intensity noise behaviour during accelerated life tests of narrow-stripe proton-isolated DH AlGaAs lasers for optical communications. J.W.M.Biesterbos and H.W.M.Salemink 300 e584
High-peak-power picosecond optical pulse generation from highly RF-modulated InGaAsP DH diode laser. N.Onodera, H.Ito and H.Inaba 811
High-power diode lasers for optical recording with operating lifetimes in excess of 10 000 h. M.Ettenberg and D.Botez 153
High-quality InP surface corrugations for 1.55 μm InGaAsP DFB lasers fabricated using electron-beam lithography. L.D.Westbrook, A.W.Nelson and C.Dix 863
High-quantum -efficiency low-threshold microcleaved $Al_xGa_{1-x}As$ lasers. B.F.Levine, J.P.Van der Ziel, R.A.Logan and C.G.Bethea 690
High-$T_0$ low-threshold crescent InGaAsP MESA-substrate buried-heterojunction lasers. N.Tamari and H.Shtrikman 177
Influence of pressure on temperature sensitivity of $Ga_xIn_{1-x}As_yP_{1-y}$ lasers. A.R.Adams, D.Patel, P.D.Greene and G.D.Henshall 919
InGaAsP/InP (1.3 μm) buried-crescent lasers with separate optical confinement. R.A.Logan, J.P.van der Ziel, H.Temkin and C.H.Henry 895
InGaAsP/InP dual-wavelength BH laser array. H.Naqai, Y.Suzuki and Y.Noguchi 371
InGaAsP/InP dual wavelength lasers. S.Sakai, T.Aoki and M.Umeno 17
InGaAsP planar buried heterostructure laser diode (PBH-LD) with very low threshold current. I.Mito, M.Kitamura, K.Kaede, Y.Odagiri, M.Seki, M.Sugimoto and K.Kobayashi 2
Intensity fluctuations in longitudinal modes of a nearly single-mode AlGaAs laser. I.Joindot and C.Boisrobert 304
Lateral grating array high power CW visible semiconductor laser. D.R.Scifres, R.D.Burnham and W.Streifer 549
Locking bandwidth asymmetry in injection-locked GaAlAs lasers. L.Goldberg, H.F.Taylor and J.F.Weller 986
Low-threshold current CW operation of multimode infil buried heterostructure 1.3 μm GaInAsP lasers. R.Plastow, M.Harding, I.Griffith, A.C.Carter and R.C.Goodfellow 262
Low-threshold-current distributed-feedback InGaAsP/InP CW lasers. S.Akiba, K.Utaka, K.Sakai and Y.Matsushima 77
Low-threshold GaInAsP/InP MESA lasers. R.A.Logan, C.H.Henry, J.P.van der Ziel and H.Temkin 782
Low-threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM VPE. S.Hersee, M.Baldy, P.Assenat, B.De Cremoux and J.P.Duchemin 618
Low-threshold oxide stripe GaAs/GaAlAs lasers grown by MOCVD. C.S.Hong, D.Kasemset, N.B.Patel, M.E.Kim and P.D.Dapkus 497
Low-threshold single quantum well (60 AÅ) GaAlAs lasers grown by MO-CVD with Mg AS *p*-type dopant. R.D.Burnham, W.Streifer, D.R.Scifres, C.Lindström, T.L.Paoli and N.Holonyak 1095
MBE-grown InGaAs/InP BH lasers with LPE burying layers. Y.Kawamura, Y.Noguchi, H.Asahi and H.Nagai 91
Measurement of beam parameters of index-guided and gain-guided single-frequency InGaAsP injection lasers. T.P.Lee. C.A.Burrus, D.Marcuse, R.J.Nelson and A.G.Dentai 902
Measurement of radiative and Auger recombination rates in p-type InGaAsP diode lasers. C.B.Su, J.Schlafer, J.Manning and R.Olshansky 595
Measurement of radiative recombination coefficient and carrier leakage in 1.3μm InGaAsP lasers with lightly doped active layers. C.B.Su, J.Schlafer, J.Manning and R.Olshansky 1108
Megahertz linewidth from a 1.5 μm semiconductor laser with HeNe laser injection. R.Wyatt, D.W.Smith and K.H.Cameron 292
Miniature solid-state directional laser Doppler velocimeter. J.D.C.Jones, M.Corke, A.D.Kersey and D.A.Jackson 967
Mode locking of Brewster-angled semiconductor lasers. J.Chen, W.Sibbett and J.I.Vukusic 426
Molecular-beam epitaxially grown 1.3 μm GaInAsP/InP double-heterostructure lasers. W.T.Tsang, F.K.Reinhart and J.A.Ditzenberger 785
New 1.5 μm wavelength GaInAsP/InP distributed feedback laser. Y.Itaya, T.Matsuoka, Y.Nakano, Y.Suzuki, K.Kuroiwa and T.Ikegami 1006
Observation of transient spectra and mode partition noise of injection lasers. P-L.Liu, T.P.Lee, C.A.Burrus, I.P.Kaminow and J.-S.Ko 904
Optical FSK signal detection in a heterodyne system using semiconductor lasers. S.Saito, Y.Yamamoto and T.Kimura 470
Optical phase modulation in an injection locked AlGaAs semiconductor laser. S.Kobayashi and T.Kimura 210
Optically pumped laser action at 77 K of InGaP/InGaAlP double heterostructures grown by MBE. H.Asahi, Y.Kawamura, H.Nagai and T.Ikegami 62
Optogalvanic stabilisation of a $CO_2$ laser with an electrodynamic tuning element. J.Jirmann and W.Dürr 69
Output power saturation of BH laser under high current operation. Y.Nakano, K.Takehei, Y.Noguchi, Y.Suzuki and H.Nagai 501
Picosecond dispersionless transmission of InGaAsP injection laser pulses at the minimum chromatic dispersion wavelength in a 27 km-long single-mode fibre. C.Lin, A.Tomita, A.R.Tynes, P.F.Glodis and D.L.Philen 882
Polarisation characteristics of a travelling-wave-type semiconductor laser amplifier. J.C.Simon 438
Pressure dependence of threshold current in $Ga_xIn_{1-x}As_yP_{1-y}$ lasers. D.Patel, A.R.Adams, P.D.Greene and G.D.Henshall 527
Quantum mechanical explanation of spontaneous emission K-factor. D.Marcuse 920
Reduction of optical phase noise in semiconductor lasers. K.W.Cobb and B.Culshaw 336
Room-temperature CW operation of 1.3 μm distributed-feedback GaInAsP/InP lasers. Y.Uematsu, H.Okuda and J.Kinoshita 857
Room-temperature CW operation of 1.60 μm GaInAsP/InP buried-heterostructure integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide. Y.Abe, K.Kishino, T.Tanbun-Ek, S.Arai, F.Koyama, K.Matsumoto, T.Watanabe and Y.Suematsu 410
Room temperature CW operation of GaInAsP/InP double heterostructure diode lasers emitting at 1.5 μm grown by low pressure metalorganic chemical vapour deposition (LP-MO CVD). M.Razeghi, P.Hirtz, R.Blondeau, J.P.Larivain, L.Noel, B.de Cremoux and J.P.Duchemin 132
Room-temperature operation of a transverse-distributed-feedback cavity laser. I.Suemune, M.Kohno and M.Yamanishi 745
S/N performance of an AlGaAs laser preamplifier and a linear repeater system. T.Mukai, Y.Yamamoto and T.Kimura 382
Schottky barrier restricted GaAlAs laser. H.Temkin, A.K.Chin and B.V.Dutt 701
Semiconductor laser FSK modulation and optical direct discrimination detection. S.Saito, Y.Yamamoto and T.Kimura 468
Semicylindrical Zn-diffused stripe GaAlAs laser diodes with very low threshold currents. K.Hanamitsu, S.Ohsaka, K.Yoshida, H.Nishi, K.Hori and M.Takusagawa 853
Short-cavity GaAlAs laser by wet chemical etching. N.Bouadma, J.Riou and J.C.Bouley 879
Shunt current and excess temperature sensitivity of $I_{th}$ and $\eta_{ex}$ in 1.3 μm InGaAsP DH lasers. H.Namizaki, R.Hirano, H.Higuchi, E.Oomura, Y.Sakakibara and W.Susaki 703
Simple formula giving spectrum-narrowing ratio of semiconductor-laser output obtained by optical feedback. K.Kikuchi and T.Okoshi 10
Simple RF-excited $CO_2$ laser. J.Jirmann and K.Stanik 790
Simple spectral control technique for external cavity laser transmitters. K.R.Preston 1092
Spontaneous emission factor of narrow-stripe gain-guided diode lasers (Comment and Reply). E.Patzak 278
Statistical analysis of instantaneous laser spectra. I.D.Henning and D.A.Frisch 465
Stripe-geometry laser with in-situ ohmic contact and self-aligned native surface oxide mask for current isolation prepared by molecular beam epitaxy. W.T.Tsang, R.A.Logan and J.A.Ditzenberger 123
Suppression of stimulated Brillouin scattering during transmission of high-power narrowband laser light in monomode fibre. D.Cotter 638
Surface-emitting GaInAsP/InP injection laser with short cavity length. Y.Motegi, H.Soda and K.Iga 461
Technique for measuring true time-resolved spectra of a semiconductor laser. I.Henning 368
Temperature dependence of threshold current of GaAs quantum well lasers. N.K.Dutta 451
Theory for self-sustained pulsations in semiconductor lasers. J.Buus 718
Ultra-low threshold, graded-index waveguide, separate confinement, CW buried-heterostructure lasers. W.T.Tsang, R.A.Logan and J.A.Ditzenberger 845
Very low threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM-VPE. S.D.Hersee, M.Baldy, P.Assenat, B.De Cremoux and J.P.Duchemin 870
Wide bandwidth, high-repetition-rate optoelectronic modulation of millimetre waves in GaAs waveguide. M.G.Li, W.L.Cao, V.K.Mathur and C.H.Lee 454

## LIGHT-EMITTING DIODES

1.3 μm InGaAsP/InP light emitting diodes with internally defined emission area prepared by single-step LPE technique. J.Heinen 23
$Ga_xIn_{1-x}As_yP_{1-y}/Ga_xIn_{1-x}As_yP_{1-y}$ DH visible LED grown on (100) GaAs by LPE in the range of 670-680 nm. H.Kawanishi and M.Hiraoka 602
InGaAsP/InP LEDs integrated with monitoring detector. S.Sakai, T.Aoki and M.Umeno 157
Preparation and properties of monolithically integrated lenses on InGaAsP/InP light-emitting diodes. J.Heinen 831

## LOGIC AND LOGIC DESIGN

DICMOS-novel MOS logic. B.J.Hosticka, U.Kleine, H.Vogt and G.Zimmer 930
High-speed low-power DCFL using planar two-dimensional electron GAS FET technology. F.N.Tung, P.Delescluse, D.Delagebeaudeuf, M.Laviron, J.Chaplart and N.T.Linh 517
High-speed processing of serial input logic data. P.D.Picton 148
Karnaugh map extended to six or more variables. A.K.Halder 868
Memory based transforms. P.J.Langlois 146
Speed power in planar two-dimensional electron GAS FET DCFL circuit: a theoretical approach. D.Delagebeaudeuf and N.T.Linh 510
Turn-on delay for Josephson logic devices with high damping. P.Migny and B.Placais 777

## MEASUREMENT

Autocorrelation function parameters used to indicate incipient blockage in a pneumatic transport system. C.M.Beck, R.M.Henry, B.T.Lowe and A.Plaskowski 705
Automatic temperature mapping system based on holographic interferometry. G.Lucarini, F.Piazza, C.Morandi and A.Pierfederici 623
BSO/fibre-optic voltmeter with excellent temperature stability. Y.Kuhara, Y.Hamasaki, A.Kawakami, Y.Murakami, M.Tatsumi, H.Takimoto, K.Tada and T.Mitsui 1055
Confocal Fabry-Perot sensor. D.A.Jackson, A.D.Kersey and M.Corke 227
High-stability measuring equipment for very small variations of optical-fibre loss. Y.Namihira, H.Wakabayashi and H.Yamamoto 124
Miniature solid-state directional laser Doppler velocimeter. J.D.C.Jones, M.Corke, A.D.Kersey and D.A.Jackson 967
Nondestructive film thickness measurement on industrial diamond. R.D.Weglein 1003
Novel technique for antenna gain measurement in satellite earth stations. P.Daly and D.Tits 1089
Pseudoheterodyne detection scheme for optical interferometers. D.A.Jackson, A.D.Kersey, M.Corke and J.D.C.Jones 1081
Wideband measurement of microwave characteristics of soils. A.Al-Attar, H.F.Scott and D.J.Daniels 194

## MEMORIES

Fault coverage of pattern-sensitive fault-detection algorithms for semiconductor memories. D.Sarma, C.A.Papachristou and F.T.Saifuddin 950
GaAs 256-bit static RAM. K.Ohwada, M.Ino, T.Mizutani and K.Asai 299

## MICROPROCESSORS AND MICROPROCESSOR APPLICATIONS

Implantation of microprocessors in trellis decoding of convolutional codes. H.F.Rashvand 121
Worst-case arbitration time in S-100-type computer bus systems. D.M.Taub 833

## MICROWAVE CIRCUITS AND SYSTEMS

Active load technique for load-pull characterisation at microwave frequencies. G.P.Bava, U.Pisani and V.Pozzolo 178
Automatic analysis of two-port active microwave network. S.Li and R.G.Bosisio 1033
Closed-form expressions for the even-mode capacitance of thick coupled microstriplines. S.S.Bedair 561
Direct coupling between two dielectric resonators. P.Skalický 332
First-order theory of the five-port symmetrical star junction. A.J.Belfort and A.L.Cullen 841
Improved six-port circuit for complex reflection coefficient measurements. J.A.Dobrowolski 748
Low-loss Lange coupler. J.L.Hobdell, J.W.Biggin and K.S.Band 815
New nondirectional waveguide multicoupler as part of a simple microwave six-port reflectometer. U.Stumper 757
New technique for 2-port measurement using an 8-port directional coupler. A.L.Cullen 343
S-parameter characterisation of a transition from a 50 Ω coaxial line to a non-50 Ω microstrip line. J.R.Souza and E.C.Talboys 348
Waveguide/resonant-disc circuits for millimetre-wave devices. W.H.Haydl, R.Bosch and J.Rüdiger 307

## MICROWAVE DEVICES AND COMPONENTS

Accurate model for effective dielectric constant of microstrip with validity up to millimetre-wave frequencies. M.Kirschning and R.H.Jansen 272
Conversion loss of an MIC balanced mixer: calculation and measurements. B.Schüppert 823
Dispersion characteristics of slot lines on a ferrite substrate by a mode-matching technique. G.Böck 536
Fin-line pin-diode attenuators and switches for 94 GHz range. H.Meinel and H.Callsen 541
Fine tuning of a millimetre-wave open resonator. C.H.Luen and L.J.Auchterlonie 358
First-order design method and experimental results for microstrip surface circulators with external matching circuits. P.S.Hall, C.J.Prior and P.A.Ramsdale 1043
FM noise measurement of W-band impatt diodes with a quasi-optical direct detection system. W.Harth, D.Leistner and J.Freyer 355
Impatt oscillator for groove guide at 95 GHz. D.J.Harris and S.Mak 399
Improved whisker pointing technique for micron-size diode contact. R.J.Mattauch and G.Green 143
Low-frequency limitations of ultrabroadband matched microwave amplifiers. F.Perez and J.Obregon 31
Microwave diplexer using magnetostatic surface and backward volume waves. D.D.Stancil 269
Microwave open resonator: a paradox. A.C.Lynch 464
Microwave parametric upper-sideband down convertor with conversion gain. R.Geissler 428
New radial power combiner using tubular dielectric cavities. J.Obregon, J.P.Balabaud, P.Guillon and Y.Garault 771
Numerical analysis of shielded dielectric resonators including substrate, support disc and tuning post. U.S.Hong and R.H.Jansen 1000
Observation of crosspolar effects using a mocrowave open resonator. D.Smith and L.J.Auchterlonie 1031
Precise calibration of a rotary vane attenuator at 35 GHz using a homodyne network analyser. M.A.Wood 1025
Stabilisation of a W-band microstrip oscillator by a dielectric resonator. G.B.Morgan 556
Ultrabroadband balanced fin-line mixer. W.Menzel and H.Callsen 724
Unsymmetric broadside-coupled striplines. T.Kitazawa, H.Kumagami and Y.Hayashi 425
Use of low dielectric constant substrates for microstrip time-delay triggered Trapatt oscillators. N.Nazoa-Ruiz and C.S.Aitchison 1052

## MODELLING

Accurate model for effective dielectric constant of microstrip with validity up to millimetre-wave frequencies. M.Kirschning and R.H.Jansen 272
Adaptive prediction of an ARMA lattice. A.C.Tsoi 222
Cauer continued fraction methods for model reduction (Comment & Reply). S.A.Marshall 788
Discrete time MRAS with reduced implementation complexity. A.A.A.Karim, R.Nagarajan and K.B.Mirza e150
Frequency-domain approach to model-reduction problem. A.Lepschy, G.Mian and U.Viaro 829
Hybrid models of 3-port immittance convertors and current and voltage conveyors. T.Dostál and J.Pospíšil 887
Improvements to a surface-wave antenna measurement range with troublesome site effects. K.M.Keen, R.R.Grime and B.E.Stemp 439
Intermittent fault coverage during test of electronic components and systems. J.Bicknell 522
Modified Ebers-Moll model. H.Kuntman 293
Nonperiodic sampling and model matching. M.de la Sen 311
Remarks on system simplification under consideration of time responses. N.Ashoor and V.Singh 496
Simple model for threshold voltage of a nonuniformly doped short-channel MOS transistor. A.M.Asenov 481
System reduction by Cauer continued-fraction expansion about s=a and s=∞ alternately. R.Parthasarathy and K.N.Jayasimha 376
System reduction by Cauer continued-fraction expansion about s=a and s=∞ alternately (Comment & Reply). J.Pal 1009
Transmission-line model analysis of a lossy rectangular microstrip patch. G.Dubost 281

## MODULATION

4 Gbit/s direct modulation of 1.3 μm InGaAsP/InP semiconductor lasers. K.Hagimoto, N.Ohta and K.Nakagawa 796
Relation between power spectrum and phase spectrum of oscillators. P.R.Shepherd, N.Faulkner, E.Vilar and P.Bradsell 614
Single-chip CMOS MSK coherent demodulator. H.Suzuki, Y.Yamao and H.Kikuchi 581

## OPTICAL COMMUNICATION

140 Mbit/s thick-film hybrid regenerator. L.Bickers, D.W.Faulkner and P.Cochrane 553
400 Mbit/s transmission test using a 1.53 μm DFB laser diode and 104 km single-mode fibre. K.Iwashita, K.Nakagawa, T.Matsouka and M.Nakahara 937
Design parameters for dispersion-shifted triangular-profile single-mode fibres. K.I.White 725
Experiences with an optical long-haul 2.24 Gbit/s transmission system at a wavelength of 1.3 μm. W.Albrecht, G.Elze, B.Enning, G.Walf and G.Wenke 746
Experimental assessment of a 140 Mbit/s coherent optical receiver at 1.52 μm. T.G.Hodgkinson, R.Wyatt and D.W.Smith 523
Experimental comparison of a germanium avalanche photodiode and InGaAs PINFET receiver for longer wavelength optical communication systems. D.R.Smith, R.C.Hooper, P.P.Smyth and D.Wake 453
Laser mode partition noise in optical wideband transmission links. G.Grosskopf, L.Küller and E.Patzak 493
Modified Chernoff bound for binary optical communication. J.R.F.Da Rocha and J.J.O'Reilly 708
OH reduction in preforms by isotope exchange (Comment). J.Stone and P.J.Lemaire 185
Optical FSK signal detection in a heterodyne system using semiconductor lasers. S.Saito, Y.Yamamoto and T.Kimura 470
OTDR in single-mode fibre at 1.55 μm using a semiconductor laser and PINFET receiver. P.Healey and Smith D.R. 959
Phototransistors in digital optical communications systems for 1-1.6 μm wavelength. M.C.Brain and D.R.Smith 772 e936
Simple spectral control technique for external cavity laser transmitters. K.R.Preston 1092

## OPTICAL FIBRES

102 km optical fibre transmission experiments at 1.52 μ using an external cavity controlled laser transmitter module. K.H.Cameron, P.J.Chidgey and Preston K.R. 650 e802
102 km unrepeatered monomode fibre system experiment at 140 Mbit/s with an injection locked 1.52 μm laser transmitter. D.J.Malyon and A.P.McDonna 445
1.55 μm optical transmission experiments at 2 Gbit/s using 51.5 km dispersion-free fibre. J.Yamada, A.Kawana, H.Nagai, T.Kimura and T.Miya 98
1.5 μm optical heterodyne system operating over 30 km of monomode fibre. T.G.Hodgkinson, D.W.Smith and R.Wyatt 929
20-channel micro-optic grating demultiplexer for 1.1-1.6 μm band using a small focusing parameter graded-index rod lens. M.Seki, K.Kobayashi, Y.Odagiri, M.Shikada, T.Tanigawa and R.Ishikawa 257
280 Mbit/s single-mode fibre transmission with DFB laser diode emitting at 1.53 μm. S.Yamamoto, K.Utaka, S.Akiba, K.Sakai, Y.Matsushima, S.Sakaguchi and N.Seki 239
50 km, two-repeaters sea trial of optical-fibre submarine cable system. K.Amano, Y.Niiro, K.Furusawa, M.Nunokawa and H.Wakabayashi 952
52 km-long single-mode optical fibre fault location using the stimulated Raman scattering effect. K.Noguchi, Y.Murakami, K.Yamashita and F.Ashiya 41
Analytical approximation for W-type fibre propagation parameters. M.Monerie 386
Anisotropy in spun single-mode fibres. A.J.Barlow, J.J.Ramskov-Hansen and D.N.Payne 200
Attenuation measurements on single pieces of fibre and extrapolation over longer distances. G.Cancellieri 1062

Autocorrelation function measurements with fibre interferometers. K.Mochizuki 820
Birefringence in elliptical-cladding single-polarisation fibres. Y.Namihira, Y.Ejiri and K.Mochizuki 89
Capillary bonded components for injection laser transmitter modules. L.D.Comerford and M.J.Brady 629
Characteristics of light induced annealing in irradiated optical fibres. R.H.West and A.P.Lenham 483
Chirp pulse transmission through a single-mode fibre. K.Iwashita, K.Nakagawa, Y.Nakano and Y.Suzuki 873
Clock recovery for a 5 Gbit/s fibre-optic system. B.Bentland, L.A.Bergman, R.Tell and S.T.Eng 547
Compact and rugged all-fibre coupler for wavelength division multiplexing. M.Rode and E.Weidel 989
Comparison between techniques for measuring the $LP_{11}$-mode cutoff wavelength in monomode fibres. P.D.Nichols 1008
Degree of polarisation in a birefringent single-mode optical fibre. B.Crosignani and P.Di Porto 15
Deposition mechanism of fine glass particles and high-rate production of fibre preforms in the VAD process. H.Suda, S.Sudo and M.Nakahara 779
Design parameters for dispersion-shifted triangular-profile single-mode fibres. K.I.White 725
Designing single-mode fibres for near-IR(1.1-1.7 μm) frequency generation by phase-matched four-photon mixing in the minimum chromatic dispersion region. C.Lin, W.A.Reed, A.D.Pearson, Hen-Tai.Shang and P.F.Glodis 87
Determination of stress profiles in optical-fibre preforms. R.B.Calligaro, D.N.Payne, R.S.Anderssen and B.A.Ellem 474
Determination of structural parameter variations in single-mode optical fibres by time-domain reflectometry. M.P.Gold and A.H.Hartog 489
Diode laser array excited star coupler suitable for Fibernet II. D.R.Scifres, M.D.Bailey, R.E.Norton, R.D.Burnham and E.G.Rawson 1028
Dispersion-free single-mode doubly clad fibres with small pure bend losses. P.L.Francois 818
Effect of source near- and far-field variations on the accuracy of multimode fibre attenuation measurements. A.B.Sharma, S.J.Halme, E.J.R.Hubach and M.Lähteenoja 49
Effects of mode conversion on backscattering measurements of multimode optical fibres. P.Di Vita 637
Elastic tube splice performance with single-mode and multimode fibres. P.Melman and W.J.Carlsen 320
Electric field sensitive optical fibre using piezoelectric polymer coating. L.J.Donalds, W.G.French, W.C.Mitchell, R.M.Swinehart and T.Wei 327
Evidence of fundamental mode cutoff in depressed inner cladding single-mode fibres. P.Sansonetti, F.Alard, C.Vassallo, P.Kammerer, P.L.Francois, M.Monerie, J.M.Gabriagues and P.Dupont 989
Excitation-dependent material dispersion in graded-index fibres. K.-F.Klein, W.E.Heinlein and K.-H.Witte 100
Experimental 1.51 μm monomode fibre link containing an injection locked repeater. D.W.Smith and D.J.Malyon 43
Experimental investigation of variation of backscattered power level with numerical aperture in multimode optical fibres. M.Eriksrud and A.R.Mickelson 130
Fabrication and evaluation of MCVD single-mode fibres with and without central index depression. B.J.Ainslie, K.J.Beales, D.M.Cooper and C.R.Day 809
Fabrication and testing of a nickel-coated single-mode fibre magnetometer. N.Hartman, D.Vahey, R.Kidd and M.Browning 224
Fabrication of low-loss $Al_2O_3$-doped silica fibres. Y.Ohmori, F.Hanawa and M.Nakahara 761
Fabrication of polarisation-maintaining fibres using gas-phase etching. R.D.Birch, D.N.Payne and M.P.Varnham 1036
Fabrication of single-polarisation single-mode-fibre couplers. M.Kawachi, B.S.Kawasaki, K.O.Hill and T.Edahiro 962
Fast method for calculating cutoff frequencies in single-mode fibres with arbitrary index profiles. P.Y.P.Chen 1048
Feedback effects in a laser diode due to Rayleigh backscattering from an optical fibre. L.Goldberg, H.F.Taylor and J.F.Weller 353
Fibre-optic variable delay lines. J.E.Bowers, S.A.Newton and H.J.Shaw 999
Field installation of a 31.5 km monomode optical fibre system operated at 140 Mbit/s and 650 Mbit/s. J.R.Stern, D.B.Payne, D.J.McCartney, P.Healey, P.Lindsey, D.M.Russ and J.H.Stewart 631
Filter response of single-mode fibre recirculating delay lines. J.E.Bowers, S.A.Newton, W.V.Sorin and H.J.Shaw 110
Finite-element analysis of birefringence in azimuthally inhomogeneous optical fibre. P.L.Chu, P.Y.P.Chen and R.A.Sammut 441
Fluoride glass preforms prepared by a rotational casting process. D.C.Tran, C.F.Fisher and G.H.Sigel 657
Fundamental-mode cutoff in depressed inner cladding fibres. M.Monerie 642
Fundamental mode spot-size measurement in single-mode optical fibres (Comment). C.A.Millar 395
Fundamental mode spot-size measurements in single-mode optical fibres (Reply to). F.Alard, L.Jeunhomme, M.Monerie, P.Sansonetti and C.Vassallo 693 e936
Fused conically tapered fibre-optical power divider. E.G.Rawson and M.D.Bailey 447
Fusion splicing of a 31.6 km monomode optical fibre system. D.B.Payne, D.J.McCartney and P.Healey 82
Germanium-oxide glass optical fibre prepared by VAD method. H.Takahashi, I.Sugimoto and T.Sato 398
Glass-gel-coated single-mode-fibre coupler with programmable power splitting ratio. K.P.Koo and D.C.Tran 941
High efficiency single-mode fibre to $Ti:LiNbO_3$ waveguide coupling. V.Ramaswamy, R.C.Alferness and M.Divino 30
High-precision moulded connector for single-mode optical fibres. T.Yoshizawa, T.Kurokawa and S.Nara 598
High-sensitivity fibre-optic accelerometer. A.D.Kersey, D.A.Jackson and M.Corke 559
High-sensitivity fibre-optic strain sensors for measuring structural distortion. C.K.Asawa, S.K.Yao, R.C.Stearns, N.L.Mota and J.W.Downs 362
High-speed coating of optical fibres with thermally curable silicone resin using a pressurised die. K.Chida, S Sakaguchi, M.Wagatsuma and T.Kimura 713
High-stability measuring equipment for very small variations of optical-fibre loss. Y.Namihira, H.Wakabayashi and H.Yamamoto 124
High-strength small reinforcement for spliced optical fibre. Y.Mimura, O.Shinbori, T.Kamibayashi and C.Ota 190
Image transmission through a single optical fibre by colour coding. G.T.Liang, F.Facq and J.Arnaud 660
Influence of waveguide dispersion in fluoride glass fibres. K.C.Byron 673
Interferometric measurements of minimum dispersion spectra in short lengths of single-mode fibre. L.G.Cohen and J.Stone 564
Large graded-index preforms fabricated by high-rate VAD. K.Chida, H.Okazaki and M.Nakahara 330
Length dependence of joint losses in multimode optical fibres. G.Coppa and P.Di Vita 84
Lens aberration effect on a laser-diode-to-single-mode-fibre coupler. M.Sumida and K.Takemoto 586
Low-loss fibre-coupled waveguide directional coupler modulator. R.C.Alferness, L.L.Buhl and M.D.Divino 490
Low-loss fibres by a pressurised MCVD method. E.Modone, G.Parisi and G.Roba 721
Low-loss quadruple-clad single-mode lightguides with dispersion below 2 ps/km nm over the 1.28 μm-1.65 μm wavelength range. L.G.Cohen, W.L.Mammel and S.J.Jang 1023
Low-loss splicing of a 62.4 km single-mode-fibre link. J.S.Leach, G.J.Cannell, A.J.Robertson and P.Gurton 697
Material dispersion in fluoride glasses. K.Jinguji, M.Horiguchi, S.Shibata, T.Kanamori, S.Mitachi and T.Manabe 164
Material dispersion slope in optical-fibre waveguides. K.Nassau and S.H.Wemple 450
Measurement of polarisation mode dispersion in elliptical-core single-mode fibres at 1.3μm. S.Rabov and W.E.Heinlein 907
Measurement of strain relief in an experimental optical fibre cable. R.Kashyap, M.H.Reeve, S.Hornung, G.R.Bandurek and J.E.Nevett 263
Measurement of stresses in elliptical optical fibre or preform. P.L.Chu 707
Measurement of stresses in optical fibre or preform. P.L.Chu and T.Whitbread 28
Microbending losses of $P_2O_5$-doped graded-index multimode fibre. Y.Murakami, K.Ishihara, Y.Negishi and N.Kojima 774
Microlens formation on VAD single-mode fibre ends. M.Kawachi, T.Edahiro and H.Toba 71
Minimum-dispersion spectra of single-mode fibres measured with subpicosecond resolution by white-light crosscorrelation. J.Stone and L.G.Cohen 716
Modal dispersion in single-mode fibres: simple approximation issued from mode spot size spectral behaviour. P.Sansonetti 647
Modal equalisation for two-mode fibre link using a step-index fibre. Y.Kato, K.Kitayama, S.Seikai and N.Uchida 356
Momentary look at noncircular monomode fibres. R.A.Sammut 221
Monomode fibre with ultra-low loss and minimum dispersion at 1.55 μm. B.J.Ainslie, K.J.Beales, D.M.Cooper, C.R.Day and J.D.Rush 842
New method for precise characterisation of multimode optical fibres. A.Barthelemy, P.Facq, C.Froehly and J.Arnaud 247
New optical fibre fabrication method. K.Susa, I.Matsuyama, S.Satoh and T.Suganuma 499
New optical monitoring method for arc-fusion splice of single-mode fibres and high-precision estimation of splice loss. Y.Kato, T.Tanifuji, M.Tokuda and N.Uchida 972
Normalised frequency dependence of polarisation mode dispersion due to thermal-stress-induced birefringence in an elliptical core single-mode fibre. N.Shibata, N.Uchida, M.Tateda and S.Seikai 563
Novel core alignment method for low-loss splicing of single-mode fibres utilising UV-excited fluorescence of Ge-doped silica core. K.Tatekura, H.Yamamoto and M.Nunokawa 712
Novel method for making single-mode optical fibre directional couplers. G.Schöner, E.Klement, G.Schiffner and N.Douklias 566
Numerical parametric studies for controlling the wavelength of minimum dispersion in germania fluoro-phosphosilicate single-mode fibres. L.G.Cohen, W.L.Mammel and S.Lumish 38
Observation of low noise in a passive fibre gyroscope. W.K.Burns, R.P.Moeller and C.A.Villarruel 648
Observation of stimulated Brillouin scattering in low-loss silica fibre at 1.3 μm. D.Cotter 495
OH absorption in $GeO_2$-doped fused silica fibres. A.V.Belov, E.M.Dianov, P.N.Lebedev, A.N.Guryanov and V.F.Hopin 836
OH reduction in preforms by isotope exchange (Comment). J.Stone and P.J.Lemaire 185
Optical coupling in coaxial fibres. J.R.Cozens, A.C.Boucouvalas, M.J.Lee, D.G.Morris and A.Al-Assam 679
Optical fibre coating speed prediction from flow properties of coating materials. M.Wagatsuma, T.Kimura, Y.Shuto and S.Yamakawa 731
Orientation- and polarisation-dependent cutoff wavelengths in elliptical-core single-mode fibres. K.-F.Klein and W.E.Heinlein 640
Orientation-dependent time delays of the first higher-order mode in elliptical-core fibres. K.-F.Klein and W.E.Heinlein 947
OTDR in single-mode fibre at 1.55 μm using a semiconductor laser and PINFET receiver. P.Healey and Smith D.R. 959
OTDR in single-mode fibre at 1.5 μm using heterodyne detection. P.Healey and D.J.Malyon 862
Polarisation-holding in a high-birefringence fibre. S.C.Rashleigh and M.J.Marrone 326
Polarisation stability in long lengths of monomode fibre. R.A.Harmon 1058
Power spectrum of microbends in monomode optical fibres. K.J.Blow, N.J.Doran and S.Hornung 448
Practical determination of equivalent-step-index profiles for single-mode fibres. R.Yamauchi, M.Miyamoto and K.Inada 550
Prediction of modal dispersion in single-mode fibres from spectral behaviour of mode spot size. P.Sansonetti 136
Preparation of low-loss fluoride glass fibre. S.Mitachi and T.Miyashita 170
Pyroelectric substitution method for calibrating optical fibre components attenuation. T.Iwasaki, I.Yokoshima and K.Nakamura 385
Raman amplification at 1.118 μm in single-mode fibre and its limitation by Brillouin scattering. G.A.Koepf, D.M.Kalen and K.H.Greene 942
Reduction of loss due to OH in optical fibres by a two-step OH→ OD exchange process. J.Stone and P.J.Lemaire 78
Relations between moments of index profile and moments of deflection function and phase function of optical fibre or preform. P.L.Chu 832
Self-locating elliptically cored fibre with an accessible guiding region. R.B.Dyott and Schrank P.F. 980 e1065
Sensitivity to geometrical parameters in a dispersion-free multicomponent fibre. P.L.Francois 484 e802
Side-tunnel fibre: an approach to polarisation-maintaining waveguiding scheme. T.Okoshi, K.Oyamada, M.Nishimura and H.Yokota 824
Single-mode-fibre point and extended temperature sensors. S.J.Petuchowski, G.H.Sigel and T.G.Giallorenzi 814
Single-mode optical-fibre index profiling with improved resolution. P.L.Chu 911

Splicing of single-polarisation fibres by an optical short-pulse method. Y.Sasaki, N.Shibata and J.Noda 997
Strain of optical fibres of an optical submarine cable on the sea bed. K.Tatekura, H.Yamamoto and Y.Ejiri 414
Stress difference in elliptically cladded fibres. Y.Ejiri, Y.Namihira and K.Mochizuki 603
Submarine optical-fibre design considering low elongation under tension. T.Yabuta, K.Ishihara and Y.Negishi 943
Substrate-tube lithography for optical fibres. R.H.Stolen, R.E.Howard and W.Pleibel 764
Suppression of stimulated Brillouin scattering during transmission of high-power narrowband laser light in monomode fibre. D.Cotter 638
Technique for minimising effect of detector inhomogeneity on fibre attenuation measurements. A.B.Sharma, E.J.R.Hubach, M.Lahteenoja and S.J.Halme 56
Technique for reducing spatial and wavelength variations of launch spot in fibre attenuation measurements. A.B.Sharma, M.Lähteenoja, S.J.Halme and E.J.R.Hubach 244
Temperature sensing in twisted single-mode fibres. D.Langeac 1022
Thermal-stress-induced birefringence in single-mode elliptical optical fibre. P.L.Chu 45
Transient stimulated Brillouin scattering in long single-mode fibres. D.Cotter 504
Transmission characteristics of a cabled and jointed 30 km monomode optical fibre link. B.P.Nelson and S.Hornung 270
Transmission experiments through 101 km and 84 km single-mode fibre at 274 Mbit/s and 420 Mbit/s. M.M.Boenke, R.E.Wagner and D.J.Will 897
Tunable fibre Raman oscillator in the 1.32-1.41 $\mu$m spectral region using a low-loss, low $OH^-$ single-mode fibre. C.Lin and P.F.Glodis 696
Ultralong multimode optical fibre fault location using Raman optical time domain reflectometry. K.Noguchi, Y.Murakami, Y.Kimura and K.Ishihara 542
Unrepeatered video transmission using pulse frequency modulation over 100 km of monomode optical fibre. D.J.T.Heatley 369
Wholly synthesised VAD single-mode fibre. M.Kawachi, M.Yasu, S.Tomaru, T.Edahiro and S.Sakaguchi 328

## OPTICS

Autocorrelation function measurements with fibre interferometers. K.Mochizuki 820
Coaxial optical coupler. J.R.Cozens and A.C.Boucouvalas 138
Compensation for feed crosspolarisation in shaped dual offset reflectors. B.S.Westcott and F.Brickell 126
Current/frequency-modulation characteristics for directly optical frequency-modulated injection lasers at 830 nm and 1.3 $\mu$m. G.Jacobsen, H.Olesen, F.Birkedahl and B.Tromborg 874
CW longitudinal mode spectra of multiple quantum well stripe lasers. C.Lindström, D.Halido, D.R.Scifres and R.D.Burnham 876
Determination of material characteristics of bleached photographic emulsions used in volume phase holography. R.R.A.Syms and L.Solymar 249
Effect of semiconductor laser phase noise on BER performance in an optical DPSK heterodyne-type experiment. F.Favre and D.Le Guen 964
Generation of single-longitudinal-mode subnanosecond light pulses by high-speed current modulation of monolithic two-section semiconductor lasers. K.J.Ebeling, L.A.Coldren, B.I.Miller and J.A.Rentschler 901
High-peak-power picosecond optical pulse generation from highly RF-modulated InGaAsP DH diode laser. N.Onodera, H.Ito and H.Inaba 811
InGaAsP/InP (1.3 $\mu$m) buried-crescent lasers with separate optical confinement. R.A.Logan, J.P.van der Ziel, H.Temkin and C.H.Henry 895
Material dispersion in fluoride glasses. K.Jinguji, M.Horiguchi, S.Shibata, T.Kanamori, S.Mitachi and T.Manabe 164
Material dispersion slope in optical-fibre waveguides. K.Nassau and S.H.Wemple 450
Microwave signal generation using an optical self-heterodyne technique. L.Goldberg, J.F.Weller and H.F.Taylor 317
Miniature solid-state directional laser Doppler velocimeter. J.D.C.Jones, M.Corke, A.D.Kersey and D.A.Jackson 967
Multiphonon absorption in infra-red fluoride glasses. H.Poignant 199
New method for measuring ultrawide frequency response of optical detectors. L.Piccari and P.Spano 116
Nonreciprocal circuit for laser-diode-to-single-mode-fibre coupling employing a YIG sphere. T.Sugie and M.Saruwatari 1026
Optical coupler for laser redundancy system. R.Kishimoto 140
Optical excitation of quartz resonators. E.Dieulesaint, D.Royer and H.Rakouth 381
Optical gain measurements of 1.3 $\mu$m $In_{1-x}Ga_xAs_yP_{1-y}$ as function of injected current density. F.C.Prince, T.J.S.Mattos and N.B.Patel 1054
Optical receiver front-end nonlinear distortion. M.Nakamura, T.Tamura and T.Ozeki 361
Optical tap array using distributed-index planar microlens. M.Oikawa, K.Iga and S.Misawa 316
Optical-waveguide micro-displacement sensor. M.Izutsu, A.Enokihara and T.Sueta 867
Output noise spectrum from demodulator in an optical PFM system. R.P.Webb 634 e802
Passive compensation scheme suitable for use in the single-mode fibre interferometer. A.D.Kersey, D.A.Jackson and M.Corke 392
Picosecond dispersionless transmission of InGaAsP injection laser pulses at the minimum chromatic dispersion wavelength in a 27 km-long single-mode fibre. C.Lin, A.Tomita, A.R.Tynes, P.F.Glodis and D.L.Philen 882
Printed geodesic lenses in glass with ion-exchanged film waveguides. H.-J.Lillienhof, B.Pantschew and D.Schulz 344
Rayleigh scattering in $ZrF_4$-based glasses. D.C.Tran, G.H.Sigel, K.H.Levin and R.J.Ginther 1046
Simple field calculation for monomode optical waveguides. S.Geckeler 683
Suppression of unwanted self-focusing effects in nonlinear optical experiments using liquid crystal. M.Kawachi, B.S.Kawasaki and K.O.Hill 609
Viscosity and optical measurement on fluoride glasses. H.Poignant and D.C.Tran 1044

## OPTOELECTRONICS

Analogue-to-digital conversion using integrated electro-optic interferometers. G.D.H.King and R.Cebulski 1099
Hybrid electro-optical multivibrator operating by finite feedback delay. A.Neyer and E.Voges 59
Optoelectronic digital/analogue convertor-emitter. C.A.Ribeiro and F.C.de Prince 1021
Optoelectronic generation of microwave power. R.Heidemann, Th.Pfeiffer and D.Jäger 783
Transmipedance optical preamplifier having a common-collector front end. M.J.N.Sibley and R.T.Unwin 985
Ultrafast optoelectronic switching in CdS. V.Brückner and F.Kerstan 885
Wide bandwidth, high-repetition-rate optoelectronic modulation of millimetre waves in GaAs waveguide. M.G.Li, W.L.Cao, V.K.Mathur and C.H.Lee 454

## PHOTOELECTRIC DEVICES

1.0-1.6 $\mu$m planar avalanche photodiode by LPE grown InP/InGaAs/InP DH structure. T.Shirai, S.Yamazaki, K.Yasuda, T.Mikawa, K.Nakajima and T.Kaneda 575
Electron-irradiated extrinsic silicon detectors for 3-5 $\mu$m focal-plane arrays. E.F.Maher, D.V.Eddolls, B.R.Holeman and R.G.Humphreys 216
Formation of shallow photodiodes by implantation of boron into mercury cadmium telluride. P.G.Pitcher, P.L.F.Hemment and Q.V.Davis 1090
Noise, responsivity and prospects for long-term stability of silicon reach-through avalanche photodiodes. M.C.Brain 65
Temporal resolution of an $Al_xGa_{1-x}As/GaAs$ bias-free photodetector. C.Y.Chen, C.G.Bethea, A.Y.Cho and P.A.Garbinski 890
ZAP! Introducing the zero-bias avalanche photodiode. T.P.Pearsall 512

## PIEZOELECTRIC DEVICES AND MATERIALS

Electric field sensitive optical fibre using piezoelectric polymer coating. L.J.Donalds, W.G.French, W.C.Mitchell, R.M.Swinehart and T.Wei 327
Improving the linearity of piezoelectric ceramic actuators. C.V.Newcomb and I.Flinn 442
Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki e150
Organic piezoelectric high-frequency thin-film transducers. A.I.Morozov, M.A.Kulakov, L.M.Dorozhkin, G.M.Pleshkov and B.A.Chayanov 878
Study of SAW properties of temperature-compensated orientations in berlinite. D.S.Bailev, F.Josse, D.L.Lee, J.Andle, W.Soluch, J.F.Vetelino and B.H.T.Chai 168

## RADAR

Anisotropic linear target recognition from RCS diagram. J.Saillard 181
Ray analysis of mutual coupling between point scatterers in RCS diagram. G.Chassay 574
RCS diagram records processing in Chebyshev space. J.Saillard 729 e896
Use of point contributors model for a radar target taking into account mutual coupling by double reflection. G.Chassay 893

## RADIO LINKS

Amplitude and phase scintillation measurements on 8.2 km line-of-sight path at 30 GHz. M.H.A.J.Herben 287
Evaluation of outage probability of microwave radio relay systems carrying both analogue (FM) and digital (FSK) RF channels. F.Ananasso 175
Packet radio in a Rayleigh channel. F.Kuperus and J.Arnbak 506
Single-chip CMOS MSK coherent demodulator. H.Suzuki, Y.Yamao and H.Kikuchi 581
VHF radio link for ground-air-ground communications using an integrated voice-data modulation. G.Benelli 555

## RADIOWAVE PROPAGATION

Analysis of rain attenuation models for slant path. G.Macchiarella 486
Behaviour of spectrum-conserving RBQPSK digital radio during multipath propagation. G.D.Richman 467
Comparison of a one- and a two-frequency technique for frequency scaling of rain attenuation statistics. H.N.Kheirallah and R.L.Olsen 51
Effects of broadband noise in radio-frequency six-port scattering-parameter measurements. R.N.Clarke and D.A.Granville-George 1110
Effects of filtering on rate of change of rain-induced attenuation. E.Matricciani 477
Effects of filtering on statistics of rain-induced fade durations. E.Matricciani 253
Empirical model for rainfall rate distribution. F.Moupfouma and J.Dereffye 460
Fluctuations on OTS-earth copolar link against diurnal and seasonal variations. A.Vander Vorst, D.Vanhoenacker and L.Mercier 915
Mobile propagation in London at 936 MHz. K.A.Hughes 141
Novel method for predicting site diversity gain on satellite-to-ground radio paths. J.E.Allnutt and D.V.Rogers 233
Radio propagation within buildings at 900 MHz. S.E.Alexander 913
Raindrop size distribution from microwave scattering measurements in equatorial and tropical climates. F.Maupfouma and J.Tiffon 1012
Reflection of spherical waves at plane interfaces where relative index of refraction is near unity. E.Krogager 689
Relationship between path length and attenuation of radio waves transmitted in a uniform rain-filled medium. S.A.J.Upton, B.G.Evans and A.R.Holt 515
Results of XPD site-diversity measurements at 11.8 GHz. J.R.Larsen 81
Theoretical random process for prediction of rain attenuation statistics in site diversity satellite links above 10 GHz. C.Capsoni and E.Matricciani 917
Urban mobile radio propagation at 900 MHz. M.F.Ibrahim and J.D.Parsons 113

## SEMICONDUCTOR DEVICES AND MATERIALS

1.0-1.6 $\mu$m planar avalanche photodiode by LPE grown InP/InGaAs/InP DH structure. T.Shirai, S.Yamazaki, K.Yasuda, T.Mikawa, K.Nakajima and T.Kaneda 575
1.40 eV emission band in GaAs. S.H.Xin, C.E.C.Wood, D.DeSimone, S.Palmateer and L.F.Eastman 3
1.5 $\mu$m GaInAsP/InP distributed Bragg reflector lasers with built-in optical waveguide. O.Mikami, T.Saitoh and H.Nakagome 458
4 Gbit/s direct modulation of 1.3 $\mu$m InGaAsP/InP semiconductor lasers. K.Hagimoto, N.Ohta and K.Nakagawa 796
7 Gbit/s coherent pulse generation in an actively mode-locked GaAlAs diode laser. Y.Suzuki and T.Sato 821
AlGaAs/GaAs JFETs by organometallic and molecular beam epitaxy. T.J.Maloney, R.R.Saxena and Y.G.Chai 112

Amorphous-silicon silicon-nitride field-effect transistors. K.Katoh, M.Yasui and H.Watanabe 599

Amorphous-silicon TFT array for LCD addressing. M.V.C.Stroomer, M.J.Powell, B.C.Easton and J.A.Chapman 858

Analysis of efficiency limitations in high-low emitter back surface field silicon solar cells. L.Prat and L.Castañer 789 e896

Anodic oxide film as gate insulator for InP MOSFETs. A.Yamamoto and C.Uemura 63

Anomalous effect of carriers on dielectric constant of (In, Ga) (As, P) lasers operating at 1.3 μm wavelength. S.E.H.Turley 590

Astigmatism of semiconductor lasers with $\cosh^{-2}(x)$ profile of gain. J.Pietzsch 1015

Auger recombination rate in InGaAsP lasers. M.G.Burt 806

Be-implanted p-n junctions in $Ga_{0.47}In_{0.53}As$. L.Vescan, J.Selders, H.Kräutle, W.Kütt and H.Beneking 533

Below 20 ps/gate operation with GaAs SAINT FETs at room temperature. K.Yamasaki, Y.Yamane and K.Kurumada 592

Broadband millimetre-wave PIN-diode attenuator with double-ridge waveguide flanges. L.-P.Schmidt and H.Meinel 839

C-2C ladder voltage dividers for application in all-MOS A/D convertors. S.P.Singh, A.Prabhakar and A.B.Bhattacharyya 537

Calculation of I/V characteristics for ion-implanted GaAs MESFETs. N.McIntyre 208

Capillary bonded components for injection laser transmitter modules. L.D.Comerford and M.J.Brady 629

Changes in photovoltaic and dark electrical properties of hydrogenerated amorphous silicon diodes induced by forward bias carrier injection. I.Sakata and Y.Hayashi 1075

Characteristics of anodic native oxide MIS diodes of $In_{0.53}Ga_{0.47}As$. J.Shirafuji, M.Amano, M.Inoue and Y.Inuishi 653

Comparison of interface state density in MIS structure deduced from DLTS and Terman measurements. E.Rosencher and D.Bois 545

Compensation tendency of short-channel and narrow-channel effects in small-geometry IGFETs. A.A.Naem and A.R.Boothroyd 135

Contact resistance of polysilicon silicon interconnections. G.K.Reeves and H.B.Harrison 1083

CW room-temperature visible single quantum well $Ga_{0.73}Al_{0.27}As$ diode lasers grown by metalorganic chemical vapour deposition. R.D.Burnham, D.R.Scifres and W.Streifer 507

Determination of spatial surface state density distribution in MOS and SIMOS transistors after channel hot electron injection. H.E.Maes and G.Groeseneken 372

Dielectric constant of semi-insulating indium phosphide. R.E.Neidert, S.C.Binari and T.Weng 987

Dielectric guiding due to an inverted gain profile in GaAs/GaAlAs lasers. P.Brosson, E.J.T.Manganote and F.C.Prince 932

Direct measurement of FM noise in 80 GHz solid-state oscillators. T.J.Simmons and D.C.Smith 308

Double-channel planar buried-heterostructure laser diode with effective current confinement. I.Mito, M.Kitamura, Ke.Kobayashi and Ko.Kobayashi 953

Double heterojunction NpN GaAlAs/GaAs bipolar transistor. H.Beneking and L.M.Su 25

Dual-wavelength (GaAl)As laser. N.Bouadma, J.C.Bouley and J.Riou 871

Electron mobility in degenerate tellurium doped $In_{0.53}Ga_{0.47}As$ LPE layers. P.A.Claxton, J.Shirafuji, P.A.Houston and P.N.Robson 213

Electronic erasure of stored reference signals in a metal-ZnO-$SiO_2$-Si induced junction storage correlator. K.C.-K.Weng, R.L.Gunshor, R.F.Pierret and K.Tsubouchi 1078

Electronically scanned CMT detector array for the 8-14 μm band. R.A.Ballingall, I.D.Blenkinsop, C.T.Elliott, I.M.Baker and D.Jenner 285

Encapsulant-free annealing of ion-implanted GaP. D.R.Myers, R.M.Biefeld, T.E.Zipperian and L.R.Dawson 323

Enhanced low temperature diffusion of electron-beam evaporated aluminium into $SiO_2$ thin films. H.F.Ragaie 74

Enhancement of electron velocity in modulation -doped (Al, Ga)As/GaAs FETs at cryogenic temperatures. T.J.Drummond, S.L.Su, W.G.Lyons, R.Fischer, W.Kopp, H.Morkoc, K.Lee and M.S.Shur 1057

Evidence of detrimental surface effects on GaAs power MESFETs. J.M.Dumas, J.Paugam and C.le Mouellic 1094

Far-field radiation patterns of multiple quantum well lasers grown by MO-CVD. D.Halido, C.Lindström and D.R.Scifres 765

Fast annealing of 4 in arsenic-implanted silicon wafers using an imaging furnace. M.Haond, C.Adès and D.-P.Vu 694

FM sideband injection locking of diode lasers. L.Goldberg, H.F.Taylor and J.F.Weller 1019

$Ga_{1-x}Al_xAs$ material for high-sensitivity pressure sensors. A.K.Saxena 644

GaAlAs-GaAs ballistic hetero-junction bipolar transistor. D.Ankri and L.F.Eastman 750

GaAs 256-bit static RAM. K.Ohwada, M.Ino, T.Mizutani and K.Asai 299

GaSb photodiode for detection of 1.73 μm radiation of Er:YLF laser. C.Heinz and W.Schmidt auf Altenstadt 859

$Ga_xIn_{1-x}As_yP_{1-y}/Ga_xIn_{1-x}As_zP_{1-z}$ DH visible LED grown on (100) GaAs by LPE in the range of 670-680 nm. H.Kawanishi and M.Hiraoka 602

Generalised ICCG method for solution of asymmetric, sparse, linear systems of discretised semiconductor device equations. F.Y.Chang and L.F.Wagner 658

Growth and optical properties of single-crystal metastable (GaAs) $_{1-x}Ge_x$ alloys. S.A.Barnett, M.A.Ray, A.Lastras, B.Kramer, J.E.Greene, P.M.Raccah and L.L.Abels 891

Growth effects of $In_{0.53}Ga_{0.47}As$ on InP structured substrates. N.Chand, A.V.Syrbu and P.A.Houston 613

High-efficiency blue luminescence from MOCVD-grown ZnSe at room temperature. D.R.Wight, P.J.Wright and B.Cockayne 593

High-efficiency GaAs power MESFETs prepared by ion implantation. M.Feng, H.Kanbar, V.K.Eu and M.Siracusa 1097

High-efficiency short-cavity InGaAsP laser with one high-reflectivity mirror. T.P.Lee, C.A.Burrus, P.L.Liu and A.G.Dentai 805

High-mobility $Ga_{0.47}In_{0.53}As$ thin epitaxial layers grown by MBE, very closely lattice-matched to InP. J.Massies, J.Rochette, P.Delescluse, P.Etienne, J.Chevrier and N.T.Linh 758

High-mobility selectively doped GaAs/AsAlAs structures grown by low-pressure OM-VPE. S.D.Hersee, J.P.Hirtz, M.Baldy and J.P.Duchemin 1076

High-quality InP surface corrugations for 1.55 μm InGaAsP DFB lasers fabricated using electron-beam lithography. L.D.Westbrook, A.W.Nelson and C.Dix 863

High-quantum -efficiency low-threshold microcleaved $Al_xGa_{1-x}As$ lasers. B.F.Levine, J.P.Van der Ziel, R.A.Logan and C.G.Bethea 690

High-speed-response InGaAs/InP heterostructure avalanche photodiode with InGaAsP buffer layers. Y.Matshushima, S.Akiba, K.Sakai, Y.Kushiro, Y.Noda and K.Utaka 945

High-speed two-dimensional electron-Gas FET logic. P.N.Tung, D.Delagebeaudeuf, M.Laviron, P.Delescluse, J.Chaplart and N.T.Linh 109

Hole traps in n-type $Ga_{1-x}Al_xAs$ grown by organometallic vapour phase epitaxy. R.H.Wu, D.Allsopp and A.R.Peaker 75

Hydrogen-induced DLTS signal in Pd/n-Si Schottky diodes. M.C.Petty 314

Hydrogen passivation of deep donor centres in high-purity epitaxial GaAs. S.J.Pearton and A.J.Tavendale 715

Implantation annealing by thermal imaging. D.Eirug Davies and E.F.Kennedy 282

Improved theory of ballistic transport in one dimension. A.J.Holden and B.T.Debney 558

Influence of gate intervals on the behaviour of submicron dual-gate FETs. E.Allamando, G.Salmer, M.Bouhess and E.Constant 791

Influence of pressure on temperature sensitivity of $Ga_xIn_{1-x}As_yP_{1-y}$ lasers. A.R.Adams, D.Patel, P.D.Greene and G.D.Henshall 919

InGaAs enhancement-mode MISFETs using double-layer gate insulator. K.Ishii, T.Sawada, H.Ohno and H.Hasegawa 1034

InGaAsP/InP LEDs integrated with monitoring detector. S.Sakai, T.Aoki and M.Umeno 157

InGaAsP/InP Schottky collector phototransistor. M.Naitoh, S.Sakai and M.Umeno 656

InP high mobility enhancement MISFETs using anodically grown double-layer gate insulator. T.Sawada and H.Hasegawa 742

Interdigitated pn junction device with novel capacitance-voltage characteristic, ultralow capacitance and low punch-through voltage. F.Capasso, R.A.Logan and W.T.Tsang 760

Inversion-mode InP MISFET employing phosphorus-nitride gate insulator. T.Kobayashi and Y.Hirota 180

Ion beam annealed $As^+$ implanted silicon. P.L.F.Hemment, E.Maydell-Ondrusz and P.D.Scovell 57

Large-area low-frequency discharge-produced a-Si:H. G.J.Smith, W.I.Milne and P.Blackborow 211

Large-signal operation of PIN impatt diodes for pulsed oscillators at millimetre-wave frequencies. M.Claassen and W.Harth 737

Lateral grating array high power CW visible semiconductor laser. D.R.Scifres, R.D.Burnham and W.Streifer 549

Lateral pnp GaAs bipolar transistor prepared by ion implantation. H.Kräutle, P.Narozny and H.Beneking 259

Liquid phase epitaxy of a new semiconductor AlGaInSb. E.Lendvay 407

Locking bandwidth asymmetry in injection-locked GaAlAs lasers. L.Goldberg, H.F.Taylor and J.F.Weller 986

Low field mobility, effective saturation velocity and performance of submicron GaAs MESFETs. M.S.Shur 909

Low-frequency emissions from deep levels in GaAs MESFETs. M.B.Das and P.K.Ghosh 207

Low-resistance ohmic contacts to p-InP. C.L.Cheng, L.A.Coldren, B.I.Miller, J.A.Rentschler and C.C.Shen 755

Low-temperature (~77 K) properties of InP MOSFETS using anodic-oxide gate insulator. A.Yamamoto, A.Shibukawa, C.Uemura and M.Yamaguchi 710

Low-threshold GaInAsP/InP MESA lasers. R.A.Logan, C.H.Henry, J.P.van der Ziel and H.Temkin 782

Low-threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM VPE. S.Hersee, M.Baldy, P.Assenat, B.De Cremoux and J.P.Duchemin 618

Low-threshold single quantum well (60 AÅ) GaAlAs lasers grown by MO-CVD with Mg AS *p*-type dopant. R.D.Burnham, W.Streifer, D.R.Scifres, C.Lindström, T.L.Paoli and N.Holonyak 1095

Lower submicron pattern definition by high-voltage electron-beam lithography. M.Yoshimi, K.Kawabuchi, T.Takigawa, M.Takahashi and Y.Kato 880

LPE growth of $In_{0.48}Ga_{0.52}As_{0.01}P_{0.99}$ lattice-matched to GaAs from an In melt rich in P. H.Kawanishi, M.Hiraoka, K.Yoshioka, K.Nishio, T.Nakagomi and S.Tanaka 384

Measurement of beam parameters of index-guided and gain-guided single-frequency InGaAsP injection lasers. T.P.Lee, C.A.Burrus, D.Marcuse, R.J.Nelson and A.G.Dentai 902

Measurement of J/V characteristics of a GaAs submicron $n^+$-$n^-$-$n^+$ diode. M.A.Hollis, L.F.Eastman and C.E.C.Wood 570

Measurement of radiative and Auger recombination rates in p-type InGaAsP diode lasers. C.B.Su, J.Schlafer, J.Manning and R.Olshansky 595

Measurement of radiative recombination coefficient and carrier leakage in 1.3μm InGaAsP lasers with lightly doped active layers. C.B.Su, J.Schlafer, J.Manning and R.Olshansky 1108

Mobility calculation of two-dimensional electron gas in GaAs/AlGaAs heterostructure at 4.2 K. Y.Takeda, H.Kamei and A.Sasaki 309

Modification of ICCG method for application to semiconductor device simulators. T.Wada and R.L.M.Dang 265

Modified Ebers-Moll model. H.Kuntman 293

Modulation-doped (Al, Ga)As/GaAs FETs with high transconductance and electron velocity. S.L.Su, R.Fischer, T.J.Drummond, W.G.Lyons, R.E.Thorne, W.Kopp and H.Morkoc 794

Molecular-beam epitaxially grown 1.3 μm GaInAsP/InP double-heterostructure lasers. W.T.Tsang, F.K.Reinhart and J.A.Ditzenberger 785

Monolithic 2-20 GHz GaAs travelling-wave amplifier. Y.Ayasli, L.D.Reynolds, J.L.Vorhaus and L.Hanes 596

Monte Carlo analysis of sensitivity of threshold voltage in small geometry MOSFETs. A.R.Alvarez and L.A.Akers 42

Monte Carlo particle simulation of GaAs submicron $n^+$ -i-$n^+$ diode. Y.Awano, K.Tomizawa, N.Hashizume and M.Kawashima 133

Monte Carlo simulation of GaAs submicron $n^+$-$n^-$-$n^+$ diode with GaAlAs heterojunction cathode. K.Tomizawa, Y.Awano, N.Hashizume and F.Suzuki 1067

Monte-Carlo simulation of space-charge injection FET. R.Fauquembergue, M.Pernisek and E.Constant 670

N-channel MISFETs on semi-insulating InP for logic applications. L.Henry, D.Lecrosnier, H.L'Haridon, J.Paugam, G.Pelous, F.Richou and M.Salvi 102

New 1.5 μm wavelength GaInAsP/InP distributed feedback laser. Y.Itaya, T.Matsuoka, Y.Nakano, Y.Suzuki, K.Kuroiwa and T.Ikegami 1006

New chemical etching solution for InP and GaInAsP gratings. T.Saitoh, O.Mikami and H.Nakagome 408

New explanation of $N_D^{-1}$ dependence of specific contact resistance for n-GaAs. Wu.Dingfen and K.Heime 940

New method for determining distribution of interface states in an MIS system. E.Yamaguchi and T.Kobayashi 290
New ultra-low-noise avalanche photodiode with separated electron and hole avalanche regions. F.Capasso 12
Nonradiative regions in GaInAsP/InP double heterostructure laser material: correlation with dislocation clusters in the substrates. C.R.Elliott, J.C.Regnault and B.Wakefield 7
Novel sampled-data MOS multiplier. D.Brodarac, D.Herbst, B.J.Hosticka and B.Hoefflinger 229
Novel triple-layer resist system. Y.Todokoro 543
Observation of transient spectra and mode partition noise of injection lasers. P-L.Liu, T.P.Lee, C.A.Burrus, I.P.Kaminow and J.-S.Ko 904
OM-VPE growth of Mg-doped GaAs. C.R.Lewis, W.T.Dietze and M.J.Ludowise 569
Optical gain measurements of 1.3 $\mu$m $In_{1-x}Ga_xAs_yP_{1-y}$ as function of injected current density. F.C.Prince, T.J.S.Mattos and N.B.Patel 1054
Optimisation of implantation conditions for the formation of buried $SiO_2$ layers in silicon. H.Mossadeq, R.J.Bennett and K.V.Anand 215
Oxidation of (n)-InP by nitric acid. C.Michel and J.J.Ehrhardt 305
Parametric photovoltaic cell. G.De Mey 334
PIN-GaAs FET optical receiver with a wide dynamic range. B.Owen 626
Planar enhancement mode two-dimensional electron GaAs FET associated with a low AlGaAs surface potential. D.Delagebeaudeuf, M.Laviron, P.Delescluse, Pham.N.Tung, J.Chaplart and N.T.Linh 103
Planar self-aligned ion-implanted InP MOSFET. D.C.Cameron, L.D.Irving, C.R.Whitehouse and J.Woodward 534
Plasma anodisation of $Ga_{1-x}In_xAs$ (x=0.35 and 0.10) and study of MOS interface properties. S.Gourrier and J.P.Chane 156
Polarisation characteristics of a travelling-wave-type semiconductor laser amplifier. J.C.Simon 438
Preparation and properties of monolithically integrated lenses on InGaAsP/InP light-emitting diodes. J.Heinen 831
Pressure dependence of threshold current in $Ga_xIn_{1-x}As_yP_{1-y}$ lasers. D.Patel, A.R.Adams, P.D.Greene and G.D.Henshall 527
Processing of titanium films on silicon using a multiscanned electron beam. E.A.Maydell-Ondrusz, P.L.F.Hemment, K.G.Stephens and S.Moffat 752
Punch-through technique for charge collection in an extrinsic Si IRCCD. A.D.Brotherton, A.Gill, J.M.Shannon and G.J.Parker 167
Q-band (26-40 GHz) GaAs FET single-stage amplifier. C.H.Oxley, A.H.Peake and R.H.Bennett 260
Rapid method of determination of carrier mobility against temperature in GaAs MESFETs. B.Kim and B.Das 844
Recrystallisation of CVD poly-Si on insulator by dual electron-beam processing. J.R.Davis, R.A.McMahon and H.Ahmed 163
Rectifying GaAs-GaAlAs-GaAs structures by MOCVD compositional grading. A.Escobosa, H.Kräutle and H.Beneking 888
Redistribution of implanted oxygen in GaAs. P.N.Favennec, B.Deveaud, M.Salvi, A.Martinez and C.Armand 202
Reduction of FM noise in impatt oscillators by optical illumination. A.J.Seeds and J.R.Forrest e106
Regenerative switching device using MBE-grown gallium arsenide. Wood C.E.C., L.F.Eastman, K.Board, K.Singer and R.Malik 676
Room-temperature CW operation of 1.3 $\mu$m distributed-feedback GaInAsP/InP lasers. Y.Uematsu, H.Okuda and J.Kinoshita 857
Room-temperature operation of a transverse-distributed-feedback cavity laser. I.Suemune, M.Kohno and M.Yamanishi 745
Schottky barrier restricted GaAlAs laser. H.Temkin, A.K.Chin and B.V.Dutt 701
Selected-area molecular beam epitaxy on ion-implanted GaAs substrates. P.N.Favennec, L.Henry, A.Regreny and M.Salvi 933
Self-align implantation for n$^+$-layer technology (SAINT) for high-speed GaAs ICs. K.Yamasaki, K.Asai, T.Mizutani and K.Kurumada 119
Semiconductor alloy resonator-type HF isolators. L.Laurinavičius and R.Tolutis 243
Semiconductor laser FSK modulation and optical direct discrimination detection. S.Saito, Y.Yamamoto and T.Kimura 468
Semicylindrical Zn-diffused stripe GaAlAs laser diodes with very low threshold currents. K.Hanamitsu, S.Ohsaka, K.Yoshida, H.Nishi, K.Hori and M.Takusagawa 853
Short-cavity GaAlAs laser by wet chemical etching. N.Bouadma, J.Riou and J.C.Bouley 879
Short-channel GaAs FET fabricated like a MESFET but operating like a JFET. H.Morkoc 258
Shunt current and excess temperature sensitivity of $I_{th}$ and $\eta_{ex}$ in 1.3 $\mu$m InGaAsP DH lasers. H.Namizaki, R.Hirano, H.Higuchi, E.Oomura, Y.Sakakibara and W.Susaki 703
Silicon implanted super low-noise GaAs MESFET. M.Feng, V.K.Eu, M.Siracusa, E.Watkins, H.Kimura and H.Winston 21
Silicon solar cells with reduced temperature sensitivity. M.A.Green, K.Emery and A.W.Blakers 97
Simple and accurate size calculation of MOS transistor. P.Bernardson 632
Simple model for threshold voltage of a nonuniformly doped short-channel MOS transistor. A.M.Asenov 481
Single-carrier-type dominated impact ionisation in multilayer structures. H.Blauvelt, S.Margalit and A.Yariv 375
Single-crystal metal-semiconductor microjunctions prepared by molecular beam epitaxy. A.Y.Cho, E.Kollberg, H.Zirath, W.W.Snell and M.V.Schneider 424
Single-mode InGaAsP/InP buried waveguide structures grown on channelled {111} B InP substrates. T.M.Benson, A.V.Syrbu, N.Chand and P.A.Houston 812
Small-reflection operation of substrate-edge excited optoelectronic mocrostrip transmission-type switches. W.Platte 977
Spatial distribution of hot electrons as a physical limit to MOS transistor performance. S.Schmitt-Landsiedel and G.Dorda 1041
Stable monolithic GaAs FET oscillator. C.Tsironis, C.Kermarrec, J.Faguet and P.Harrop 345
Statistical analysis of instantaneous laser spectra. I.D.Henning and D.A.Frisch 465
Substrate effects on performance of InP MOSFETs. J.Woodward, G.T.Brown, B.Cockayne and D.C.Cameron 415
Surface-emitting GaInAsP/InP injection laser with short cavity length. Y.Motegi, H.Soda and K.Iga 461
Switching behaviour of $Al_2O_3$-n GaAs MISFETs. W.S.Lee and J.G.Swanson 1049
T-emitter bipolar power transistor with negative-temperature-gradient current gain. N.D.Janković 1085
TEG in LP-MO CVD $Ga_{0.47}In_{0.53}As$-InP superlattice. M.Razeghi, M.A.Poisson, J.P.Larivain, B.de Cremoux, J.P.Duchemin and M.Voos 339
Temperature dependence of threshold current of GaAs quantum well lasers. N.K.Dutta 451
Temporal resolution of an $Al_xGa_{1-x}As$/GaAs bias-free photodetector. C.Y.Chen, C.G.Bethea, A.Y.Cho and P.A.Garbinski 890
Theory for self-sustained pulsations in semiconductor lasers. J.Buus 718
Thin MBE GaAs millimetre-wave diode using Ge substrate. A.Christou, J.E.Davey and D.Covington 367
Three-dimensional simulation of inverse narrow-channel effect. N.Shigyo, M.Konaka and R.L.M.Dang 274
Threshold voltage of ion implanted GaAs MESFET. T.Mizutani, S.Ishida, T.Honda and Y.Kawasaki 53
Transmipedance optical preamplifier having a common-collector front end. M.J.N.Sibley and R.T.Unwin 985
Tunnelling through GaAs-$Al_xGa_{1-x}As$-GaAs double heterojunctions. D.Delagebeaudeuf, P.Delescluse, P.Etienne, J.Massies, M.Laviron, J.Chaplart and T.Linh 85
Ultra-low threshold, graded-index waveguide, separate confinement, CW buried-heterostructure lasers. W.T.Tsang, R.A.Logan and J.A.Ditzenberger 845
Use of incoherent light for annealing implanted Si wafers and growing single-crystal Si on $SiO_2$. M.Haond and D.P.Vu 727
Variation of minority carrier lifetime with level of injection in p-n junction devices. S.K.Agarwal, S.C.Jain and S.Harsh 298
Velocity/field characteristic measurement using a high-frequency modulated solid-state laser diode. M.H.Evanno and J.L.Vaterkowski 417
Very low threshold GRIN-SCH GaAs/GaAlAs laser structure grown by OM-VPE. S.D.Hersee, M.Baldy, P.Assenat, B.De Cremoux and J.P.Duchemin 870

## SIGNAL PROCESSING

Buffering strategy for variable-symbol-rate speech waveform coders. J.N.Holmes 691
Cascaded bandpass vth-law devices. A.K.Gupta, W.B.Garner and E.J.Baghdady 926
Efficient adaptive linear predictor. G.Martinelli 617
Further results on maximally flat nonrecursive digital filters. M.U.A.Bromba and H.Ziegler 1014
Implementation of convolution and Fourier transforms using 1-bit systolic arrays. J.S.Ward and B.J.Stanier 799
Implementation of signal processing functions using 1-bit systolic arrays. J.V.McCanny and J.G.McWhirter 241
Method for superimposing data on amplitude-modulated signals. G.B.Lockhart and Y.O.Al-Jalili 379
Multidimensional bilinear transformations. S.-C.Pei 1069
Number of spectral coefficients necessary to identify a class of Boolean functions. J.Muzio, D.M.Miller and S.L.Hurst 577
Optimal real-time interpolation for D/A conversion of sparsely sampled signals. J.M.De Carvalho and J.V.Hanson 961
Phase-shift keying: symbol error rate in presence of random fluctuation noise - an elementary treatment. D.Maurice 1112
Power spectra of digital FM signals with complex signalling pulse shapes. K.M.Sundara Murthy and K.W.Cattermole 848
Relation between power spectrum and phase spectrum of oscillators. P.R.Shepherd, N.Faulkner, E.Vilar and P.Bradsell 614
Serial synthesis of minimum-shift-keyed signals. N.Ekanayake 827
Some properties of multidimensional sampling rate conversion. D.S.R.Gunawardena, A.H.Kayran and R.A.King 321
Spectral method of Boolean function complexity. S.L.Hurst, D.M.Miller and J.C.Muzio 572
State-sequenced polarity crosscorrelator. M.A.Browne, R.J.Deloughry, R.G.Green and R.Thorn 528
Temporal quantisation noise. J.J.O'Reilly 219
Uniform analogue to digital conversion of a normal random process. G.M.Papadourakis and Taylor F.J. e966
Vector quantiser of video signals. T.Murakami, K.Asai and E.Yamazaki 1005

## SOLAR CELLS

Analysis of efficiency limitations in high-low emitter back surface field silicon solar cells. L.Prat and L.Castañer 789 e896
Silicon solar cells with reduced temperature sensitivity. M.A.Green, K.Emery and A.W.Blakers 97

## SUPERCONDUCTING DEVICES

First measurement of a superconducting microstrip-line attenuation constant at 10 GHz. R.Pöpel 1103
Phase-plane analysis of simple Josephson junction model. V.Dvorak e150

## SURFACE ACOUSTIC WAVES

Analysis of SAW attenuation measurement using acoustic microscopy. K.Yamanaka 587
Finite-element analysis of flat overlay waveguides for acoustic surface waves using acoustic surface impedance. M.Koshiba, K.Hayata and M.Suzuki 530 e936
High-performance SAW convolver using 3-phase unidirectional transducers. C.L.West 401
Influence of size and shape on reflection of surface acoustic waves by thin aluminium dots on lithium niobate. F.Huang and E.G.S.Paige 232
Leaky SAW velocity on water/silicon boundary measured by acoustic line-focus beam. J.Kushibiki, K.Horii and N.Chubachi 732
Low-loss low-ripple SAW filters using three bidirectional centrosymmetric transducers. K.H.Yen, R.B.Stokes, K.F.Lau, A.Kong and R.S.Kagiwada 403
Multiplier/detector for SAW spectrum analysers. P.J.Hall 699
Narrow-aperture chirp transducers for SAW convolvers. D.P.Morgan, D.H.Warne and D.R.Selviah 80
New technique for wavefront distortion compensation of apodised interdigital transducers. W.Soluch 1002
Nondestructive film thickness measurement on industrial diamond. R.D.Weglein 1003
Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki e150
Propagation characteristics of leaky SAWs on water/$LiNbO_3$ boundary measured by acoustic microscope with line-focus beam. J.Kushibiki, A.Ohkubo and N.Chubachi 6

Radiation conductance of SSBW IDT on rotated Y-cuts of $LiNbO_3$. K.Y.Hashimoto, Y.Igarashi, H.Kogo and M.Yamaguchi 331
SAW attenuation measurement in the acoustic microscope. I.R.Smith and H.K.Wickramasinghe 955
Semiconductor surface studies with SAW oscillator structures. R.Rademeyer, B.Davari and P.Das 1065
Spatial uniformity measurement of SAW convolvers. D.R.Selviah, D.H.Warne and D.P.Morgan 837
Study of SAW properties of temperature-compensated orientations in berlinite. D.S.Bailey, F.Josse, D.L.Lee, J.Andle, W.Soluch, J.F.Vetelino and B.H.T.Chai 168

## SWITCHING AND SWITCHING CIRCUITS

Analytical and simulation study of simple rearrangeable multiexchange networks. A.K.M.M.Rahman Khan 1073
Asummability testing. A.K.Sarje 938
New form of liquid crystal touch switch. M.J.Bradshaw, C.Hilsum and E.P.Raynes 1106
Novel architecture for a time division switch. P.L.Nicholson 1100
Proposed use of rearrangement in multiexchange telecommunication networks. J.E.Flood 1072
Regenerative switching device using MBE-grown gallium arsenide. Wood C.E.C., L.F.Eastman, K.Board, K.Singer and R.Malik 676
Switching behaviour of $Al_2O_3$-n GaAs MISFETs. W.S.Lee and J.G.Swanson 1049
Switching speed of a circuit with positive feedback. P.J.Langlois 172
Ultrafast optoelectronic switching in CdS. V.Brückner and F.Kerstan 885

## TELECOMMUNICATION

Analytical and simulation study of simple rearrangeable multiexchange networks. A.K.M.M.Rahman Khan 1073
Joint statistics of rain intensity in eight Italian locations for satellite communication networks. F.Barbaliscia and A.Paraboni 118
Number-theoretic transforms with 2 as a root of unity. P.Duhamel and H.Hollmann 978
Outage prediction of digital radio systems. J.C.Campbell and R.P.Coutts 1071
Performance of FH-MFSK serial search synchroniser for mobile radio. R.Agusti-Comes and G.Junyent-Giralt 393
Proposed use of rearrangement in multiexchange telecommunication networks. J.E.Flood 1072
Results of a new optimisation technique leading to optimum pulses for MSK-type signals. N.Boutin, L.Dussault and S.Morissette 975

## ULTRASONICS

Frequency control of ultrasonic transducers. R.Clarke, D.Midgley and C.R.Weston 684
Leaky SAW velocity on water/silicon boundary measured by acoustic line-focus beam. J.Kushibiki, K.Horii and N.Chubachi 732
Photodisplacement microscopy using a semiconductor laser. Y.Martin and E.A.Ash 763
Pulse-compression subsurface acoustic microscopy. Y.Guangqi, M.Nikoonahad and E.A.Ash 767
Rayleigh wave absorption via acoustic microscopy. R.D.Weglein 20
Uniaxially strained $ZnO/SiO_2/Si$ SAW resonators. S.J.Martin, R.L.Gunshor, R.F.Pierret and G.Gorodetsky 1030
Visualisation of ultrasonic waves launched by $PVF_2$ piezofilm transducers. D.I.Crecraft, C.J.S.Davies and K.G.Hall 16

## WAVEGUIDES

Analysis of conductor-backed coplanar waveguide. Y.C.Shih and T.Itoh 538
Analysis of slow-wave phenomena in coplanar waveguide on a semiconductor substrate. Y.Fukuoka and T.Itoh 589
Application of finite-element method to H-plane waveguide discontinuities. M.Koshiba, M.Sato and M.Suzuki 364 e802
Approximate scalar finite-element analysis of anisotropic optical waveguides. M.Koshiba, K.Hayata and M.Suzuki 411
Broadband end launcher for X band rectangular waveguide. T.S.Gangadharan 354
Broadband millimetre-wave PIN-diode attenuator with double-ridge waveguide flanges. L.-P.Schmidt and H.Meinel 839
Calculation of coupling of two grooves in a parallel-plate guide. J.Meissner 956
Diode-laser-controlled millimetre-wave propagation in a silicon waveguide. A.M.Vaucher, M.G.Li and Lee. C.H. 1066
Electrical and acoustical crosstalk in integrated optical strip waveguide devices. C.H.Von Helmolt 969
Estimation of single-mode waveguide dispersion using an equivalent-step-index approach. V.A.Bhagavatula 319
Finite-element analysis of the discontinuities in a dielectric slab waveguide bounded by parallel plates. M.Koshiba, K.Ooishi, T.Miki and M.Suzuki 33
Momentary look at noncircular monomode fibres. R.A.Sammut 221
Numerical analysis of planar arbitrarily anisotropic defused optical waveguides using finite-element method. M.Koshiba and M.Suzuki 579
Numerical analysis of two-dimensional piezoelectric waveguides for surface acoustic waves by finite-element method. M.Koshiba, M.Okada and M.Suzuki e150
Optical Y-junctions and S-bends formed by preferentially etched single-mode rib waveguides in InP. P.Buchmann and A.J.N.Houghton 850
Parallel-planes approximation for propagation in rectangular tunnels. B.Jacard, A.Valenzuela and O.Maldonado 1011
Propagation constants of cylindrical dielectric waveguides with arbitrary refractive-index profile using 'resonance' technique. C.D.Papageorgiou and A.C.Boucouvalas 786
Radiation loss in open-waveguide directional couplers. T.Corzani, L.Maniá and G.Falciasecca 847
Room-temperature CW operation of 1.60 μm GaInAsP/InP buried-heterostructure integrated laser with butt-jointed built-in distributed-Bragg-reflection waveguide. Y.Abe, K.Kishino, T.Tanbun-Ek, S.Arai, F.Koyama, K.Matsumoto, T.Watanabe and Y.Suematsu 410
Simple dielectric waveguide bandpass filter. G.L.Matthaei, C.E.Harris, Y.M.Kim, D.C.Park and J.P.Duvall 798
Simple equivalent network for a rectangular dielectric image guide. M.Koshiba, H.Ishii and M.Suzuki 473
Single-mode InGaAsP/InP buried waveguide structures grown on channelled {111} B InP substrates. T.M.Benson, A.V.Syrbu, N.Chand and P.A.Houston 812
Theoretical analysis of hybrid modes in a dual-depth corrugated waveguide feed. N.Sridhar and G.P.Srivastava 793 e896
Tunable low-reflection waveguide termination. M.A.Wood 174
Wave propagation in transversely inhomogeneous dielectric waveguide. P.Y.P.Chen 736
Wave propagation in transversely inhomogeneous dielectric waveguide. J.Gomi, T.Yoneyama and S.Nishida 463
Wide bandwidth, high-repetition-rate optoelectronic modulation of millimetre waves in GaAs waveguide. M.G.Li, W.L.Cao, V.K.Mathur and C.H.Lee 454

PRINTED BY Unwin Brothers Limited
THE GRESHAM PRESS OLD WOKING SURREY ENGLAND